Miele

PRI 210 [EL STW AB] Rotary ironer, electrically heated With the latest controls and flexible working height.



- Performance ?? kg/h*, roller diameter 210 mm, working width 1000 mm
- Ideal ergonomics heightadjustable and optional plinth
- State-of-the-art controls Touch display
- Selection of the most important settings favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

EAN: 4002516422266 / Material number: 11741270 / Old Material Number: 53210005EU

Construction type and version	
Construction type	Laundry infeed and outfeed at the front
Can be set up against a wall	at the nont
Range	Professional
Outer casing	
Roller diameter in mm	Iron grey 210
	1000
Working width in mm	
Heater plate material	Aluminium
Padding	Supple steel wool
Ironer cover	ARAMID needle-felt cloth
Application	
Suitable for the hotel and catering industry	<u> </u>
Suitable for retirement and care homes	<u> </u>
Suitable for launderettes	<u> </u>
Suitable for residential homes and apartments	<u>•</u>
Suitable for hospitals	<u> </u>
Suitable for offshore use	•
Suitable for marine use	•
Suitable for camp sites	•
Suitable for domestic use	•
Performance data	
Tested operating hours	20000
Control system	
Control system	Touch display
Touch display (optional)	Touch-Display PRI
Programme setting	Setting of defined
	programme parameters
Minimum ironing speed, controlled in m/min	1.5
Maximum ironing speed, controlled in m/min	4.0
Adjustable temperature	Infinitely variable
Standard electrical connection	
Heating type	Electric
Electrical connection	AC 230V 50-60HZ
Electric heater rating in kW	3.00
Total connected load in kW	3.40
Fuse rating in A	16
Dimensions and weight	
External dimensions, height in mm	1032
External dimensions, width in mm	1579
External dimensions, depth in mm	476
External dimensions, gross height in mm	1374
External dimensions, gross width in mm	1763
External dimensions, gross water in mm	660
	122
Net weight in kg	
Gross weight in kg	136
Maximum floor load in N/m ²	1235
Emissions data	70 (D(A) 00 D
Emission sound pressure level in the workplace	<70 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	3.30

With 15 % residual moisture – performance data according to DIN 11902: the achievable ironing performance depends on overall conditions such as, for example, the type of laundry and the experience of the contribute.



PRI 210 [EL STW AB] Rotary ironer, electrically heated With the latest controls and flexible working height.



EAN: 4002516422266 / Material number: 11741270 / Old Material Number: 53210005EU

Features	
Automatic finger guard	•
FlexControl footswitch	•
Airing bar	•
Feed-in board	•
Pick-off bands	•
Laundry box (optional)	•
Laundry return feed	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Plinth (optional)	•
Option of ironing when seated	•
APRI 319 care set for the heater plate included in the scope of delivery	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Peak load cut-out/energy management	•
Standards, test certificates and symbols	
VDE	•
CE	•
EAC	•
WEEE	•
VDE-EMC	•
RCM	•
Splash-proof IPX0	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•