

## PFD 104 SCVi XXL [MAR]

Fully integrated XXL dishwasher with 3D MultiFlex tray with baskets, approved by Lloyd's Register.



- Wash performance: 14 place settings in just 36 min\*
- 13 % less energy consumption\*\*
- Door opens automatically after two knocks – Knock2open
- Door closes on its own AutoClose
- Innovative design and maximum convenience – 3D MultiFlex tray

EAN: 4002516424178 / Material number: 11750880 / Old Material Number: 61010405MAR

Construction type and version	
Construction type and version Construction type	Fully intograted dishwasher
XXL dishwashers	Fully integrated dishwasher
	Drofil in a
Range	ProfiLine  Freely water freezy leader
Wash system	Fresh water front loader
Number of levels	2
Front	Without front
Side panels	Galvanised
Fascia color	Obsidian black
Application	
Suitable for offshore and marine services	•
Performance data	
Tested virucidal efficacy	
Proven hygiene	•
Shortest programme duration in min.	36
Maximum final rinse temperature in °C	75
Cleaning performance, place settings/cycle	14
Service life in wash cycles	12500
Control system	
Control system	Electronic controls
Programme selection	Programme selector buttons
Max. delay start in h	24
Time left display	•
Dishwashing programmes [number]	8
Programme sequence indicator	•
	•
Programme sequence indicator Choice of display language Check filter indicator	
Choice of display language	
Choice of display language Check filter indicator	
Choice of display language Check filter indicator Standard electrical connection Electrical connection	•
Choice of display language Check filter indicator Standard electrical connection	3N AC 400V 50HZ 7.10
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW	• • 3N AC 400V 50HZ
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	3N AC 400V 50HZ 7.10 7.30
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m	3N AC 400V 50HZ 7.10 7.30
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	3N AC 400V 50HZ 7.10 7.30
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection	* 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW	3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW	* 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A	3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage	** 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number]	** 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16
Choice of display language Check filter indicator  Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar	• 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16
Choice of display language Check filter indicator  Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN]	** 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16  1 1.00-10.00 22
Choice of display language Check filter indicator  Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN] Drain pump head height from floor level, max. in c	• 3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16  1 1.00-10.00 22 100
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN] Drain pump head height from floor level, max. in c Integrated water softener	3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16  1 1.00-10.00 22 100 •
Choice of display language Check filter indicator  Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN] Drain pump head height from floor level, max. in c Integrated water softener Maximum water hardness in mmol/I	3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16  1 1.00-10.00 22 100  6.50
Choice of display language Check filter indicator  Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN] Drain pump head height from floor level, max. in c Integrated water softener Maximum water hardness in mmol/I Water protection system	• • • • • • • • • • • • • • • • • • •
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN] Drain pump head height from floor level, max. in c Integrated water softener Maximum water hardness in mmol/I Water protection system Length of water drain hose in cm	3N AC 400V 50HZ 7.10 7.30 16 1.70  AC 230V 50HZ 1.90 2.10 10-16  1 1.00-10.00 22 100  6.50
Choice of display language Check filter indicator Standard electrical connection Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Length of mains connection cable in m Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold or hot water [number] Required flow pressure in bar Drain pump [DN] Drain pump head height from floor level, max. in c Integrated water softener Maximum water hardness in mmol/I Water protection system	• • • • • • • • • • • • • • • • • • •

Depending on site conditions (temperature of incoming water / power connection) values given may vary.

<sup>&</sup>quot; Based on the ECO programme, compared to predecessor.



## PFD 104 SCVi XXL [MAR]

Fully integrated XXL dishwasher with 3D MultiFlex tray with baskets, approved by Lloyd's Register.



EAN: 4002516424178 / Material number: 11750880 / Old Material Number: 61010405MAR

Futament alimentations and windth in second	500
External dimensions, net width in mm	598
External dimensions, net depth in mm	550
External dimensions, gross height in mm	970
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	690
Usable space in wash cabinet, height in mm	580
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper baske	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Required niche width in mm	600
Net weight [kg]	48
Gross weight in kg	57
Maximum floor load in N/m <sup>2</sup>	1000
Emissions data	00 10(4) 00 0
Emissions – sound pressure at workplace	33 dB(A) re 20 μPa
Sound power (LwA) in dB(A) re 1 pW	45.0
Programmes	
Universal	•
Short	•
Hygiene	
Cold/Pre-wash	•
Glasses	•
Plastics	•
Energy save/Eco	•
Intensive	•
Basket design	
MaxiComfort P baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	4
FlexCare cup rack [number]	2
Height-adjustable upper basket	•
Patented 3D MultiFlex tray	•
Features	
Drying	Extra drying, Active
	condensation drying
1 combi dispenser in the door for powder cleaning agent	•
and rinsing agent	
Wash cabinet made from high-quality stai	•
BrilliantLight And Oliver and Oli	•
AutoClose	•
EcoFeedback	•
Brilliant GlassCare	•
Adjustable final rinse temperature	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
WiFi module	•
Standards, test certificates and symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•



## PFD 104 SCVi XXL [MAR]

Fully integrated XXL dishwasher with 3D MultiFlex tray with baskets, approved by Lloyd's Register.



EAN: 4002516424178 / Material number: 11750880 / Old Material Number: 61010405MAR

VDE	•
EMC radio suppressed	•
DIN EN 17735	•
EN 1717	•
Lloyd's Register	•