

## PFD 104 SCVi XXL [MAR]

Fully integrated XXL dishwasher with 3D MultiFlex cutlery tray with baskets, approved by Lloyd's Register.



- Wash performance: 14 place settings in just 24 min\*
- 13 % less energy consumption\*\*
- Door opens automatically after two knocks – Knock2open
- Door closes on its own AutoClose
- Innovative design and maximum convenience 3D MultiFlex tray

EAN: 4002516424192 / Material number: 11750900 / Old Material Number: 61010415MAR

| Construction type and version                                       |                                |
|---|--------------------------------|
| Construction type   | Fully integrated dishwasher    |
| XXL dishwashers   | 1 dily integrated disriwasilei |
|   | ProfiLine                      |
| Range Wash system   | Fresh water front loader       |
| Wash system  Number of levels                                       |                                |
|   | 2                              |
| Front   | Without front                  |
| Side panels   | Galvanised                     |
| Fascia color  | Obsidian black                 |
| Application   |                                |
| Suitable for offshore and marine services                           | •                              |
| Performance data  |                                |
| Tested virucidal efficacy   | •                              |
| Proven hygiene  | •                              |
| Shortest programme duration in min.                                 | 24                             |
| Maximum final rinse temperature in °C                               | 75                             |
| Cleaning performance, place settings/cycle                          | 14                             |
| Service life in wash cycles   | 12500                          |
| Miele MOVE  |                                |
| Network-enabled with Miele MOVE                                     | •                              |
| Control system  |                                |
| Control system  | Electronic controls            |
| Programme selection   | Programme selector             |
|   | buttons                        |
| Max. delay start in h   | 24                             |
| Time left display   | <u> </u>                       |
| Programmes [number]   | 8                              |
| Programme sequence indicator  | •                              |
| Choice of display language  | •                              |
| Check filter indicator  | •                              |
| Standard electrical connection                                      |                                |
| Electrical connection   | 2N AC 120/208-240V,<br>60HZ    |
| Heater rating in kW   | 3.50-3.80                      |
| Total connected load in kW  | 3.70-4.00                      |
| Fuse rating in A  | 30                             |
| Length of mains connection cable in m                               | 1.70                           |
| Possible voltage variant 1  |                                |
| Electrical connection   | AC 120V 60HZ                   |
| Heater rating in kW   | 1.30                           |
| Total connected load in kW  | 1.40                           |
| Fuse rating in A  | 15                             |
| Water connection/drainage   | 1.0                            |
| Cold or hot water [number]  | 1                              |
| Required flow pressure in bar                                       | 1.00-10.00                     |
|   | <del></del>                    |
| Drain pump [DN]  Prain pump boad beight from floor level, may, in a | 22                             |
| Drain pump head height from floor level, max. in c                  | 100                            |
| Integrated water softener   |                                |
| Maximum water hardness in mmol/l                                    | 6.50                           |
| Water protection system   | Waterproof system              |

Depending on site conditions (temperature of incoming water / power connection) values given may vary.

<sup>&</sup>quot; Based on the ECO programme, compared to predecessor.



## PFD 104 SCVi XXL [MAR]

Fully integrated XXL dishwasher with 3D MultiFlex cutlery tray with baskets, approved by Lloyd's Register.



EAN: 4002516424192 / Material number: 11750900 / Old Material Number: 61010415MAR

| Length of water drain hose in cm                          | 150                    |
|---|------------------------|
| Dimensions and weight                                     |                        |
| External dimensions, height in mm                         | 845                    |
| External dimensions, net width in mm                      | 598                    |
| External dimensions, net depth in mm                      | 550                    |
| External dimensions, gross height in mm                   | 970                    |
| External dimensions, gross width in mm                    | 670                    |
| External dimensions, gross depth in mm                    | 690                    |
| Usable space in wash cabinet, height in mm                | 580                    |
| Usable space in wash cabinet, width in mm                 | 510                    |
| Usable space in wash cabinet, depth of upper baske        | 450                    |
| Usable space in wash cabinet, depth of lower basket in mm | 450                    |
| In-feed height above floor in mm                          | 210                    |
| Required niche width in mm                                | 600                    |
| Net weight [kg]   | 48                     |
| Gross weight in kg  | 57                     |
| Maximum floor load in N/m <sup>2</sup>                    | 1000                   |
| Emissions data  |                        |
| Emissions – sound pressure at workplace                   | 33 dB(A) re 20 µPa     |
| Sound power (LwA) in dB(A) re 1 pW                        | 45.0                   |
| Programmes  | 40.0                   |
| Universal   | •                      |
| Short   | •                      |
| Hygiene   | •                      |
| Cold/Pre-wash   | •                      |
| Glasses   | •                      |
| Plastics  | •                      |
| Energy save/Eco   | •                      |
| Intensive   | ·-                     |
|   |                        |
| Basket design  MayiComfort P hockets                      |                        |
| MaxiComfort P baskets  Flovible Flovi inc. basket design  | •                      |
| Flexible FlexLine basket design                           |                        |
| FlexCare glass holder [number]                            | 4                      |
| FlexCare cup rack [number]                                | 2                      |
| Height-adjustable upper basket                            | •                      |
| Patented 3D MultiFlex tray                                |                        |
| Features Drying   | Extra drying, Active   |
| 1 combi dispenser in the door for powder cleaning agent   | condensation drying  • |
| and rinsing agent   |                        |
| Wash cabinet made from high-quality stai                  | •                      |
| BrilliantLight  | •                      |
| AutoClose   | •                      |
| EcoFeedback   | •                      |
| Brilliant GlassCare                                       | •                      |
| Adjustable final rinse temperature                        | •                      |
| Optical interface   | •                      |
| SmartStart  | •                      |
| FlexiTimer with EcoStart                                  | •                      |
| WiFi module   | •                      |



## PFD 104 SCVi XXL [MAR]

Fully integrated XXL dishwasher with 3D MultiFlex cutlery tray with baskets, approved by Lloyd's Register.



EAN: 4002516424192 / Material number: 11750900 / Old Material Number: 61010415MAR

| Standards, test certificates and symbols     |   |
|--|---|
| CE   | • |
| Complies with Machinery Directive 2006/42/EC | • |
| VDE  | • |
| EMC radio suppressed                         | • |
| DIN EN 17735                                 | • |
| EN 1717                                      | • |
| Lloyd's Register                             | • |