

PDR 918 [SI] Professional vented dryer, steam heating with programmable M Touch Pro controls for the maximum in flexibility.



- Drum volume 325.00 I, load size13.0 kg-18.0 kg
- Unique, gentle fabric care honeycomb drum
- Excellent energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516443438 / Material number: 11795580 / Old Material Number: 52918012EU

Construction type and version	
	Front loader
Construction type	Performance Plus
Range Front	Stainless steel
Load size with a load ratio of 1:25	13.0
Load size with a load ratio of 1.25 Load size with a load ratio of 1:18	18.0
Drum volume in I	325.00
Drying system	Exhaust air
Door opening [Ø] in mm	520
Door opening angle in degrees	
Door hinge	left •
Convertible door hinging	<u> </u>
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	
Suitable for retirement and care homes	
Suitable for facility management	
Suitable for dry cleaners	
Suitable for commercial laundries	
Suitable for fire brigades and rescue services	
Suitable for studs, riding schools and stables	
Suitable for universities, nurseries, and schools	
Suitable for hospitals	
Suitable for sports clubs	_ •
Suitable for beauty salons, spas, and fitness centres	
Suitable for doctors' and dentists' practices	
Suitable for the petrochemicals industry	
Suitable for the food-processing industry	
Suitable for amusement parks & holiday complexes	
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in I/hour	15.00
Specific energy consumption in kWh/kg	0.64
Programme duration in min.	
Service life in drying cycles	40000
Control system	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture
- A - II	controlled
Max. delay start in h	
Time left display	
Programme sequence indicator	_
Selectable display languages	•
Standard electrical connection	
Heating type	Indirect steam
Electrical connection	1N AC 230V 50/60HZ
Electric heater rating in kW	0.00
Steam heater rating in kW	28.00
Total connected load in kW	0.60



PDR 918 [SI] Professional vented dryer, steam heating with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516443438 / Material number: 11795580 / Old Material Number: 52918012EU

Fuse rating in A	10
Dimensions and weight of dryer	
External dimensions, height in mm	1400
External dimensions, width in mm	906
External dimensions, depth in mm	1035
External dimensions, gross height in mm	1526
External dimensions, gross width in mm	1090
External dimensions, gross depth in mm	1125
Net weight in kg	207.5
Gross weight in kg	221
Maximum floor load in N/m ²	2300
Emissions data	
Emission sound pressure level in the workplace	50 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	4.50
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
WiFi tumble dryer	•
Connector Box	•
LAN module (optional)	•
Capacities	
Respirator masks [number]	12
Overalls [number]	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Down duvets [number]	1
Down pillows [number]	3
Cloths, 22 g [number]	295
Cotton mops, 40 cm [number]	68
Cotton mops, 50 cm [number]	59
Microfibre mops, 40 cm [number]	108
Microfibre mops, 50 cm [number]	76
Summer horse blankets [number]	3
Standards, test certificates and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
**	•



PDR 918 [SI] Professional vented dryer, steam heating with programmable M Touch Pro controls for the maximum in flexibility.



EAN: 4002516443438 / Material number: 11795580 / Old Material Number: 52918012EU

UKCA •

Complies with Machinery Directive 2006/42/EC