

PDR 922 HP [EL APDR 902]

Professional heat-pump dryer incl. powerful heat pump APDR 902 lowest energy consumption, without complicated exhaust ducting installation.



- Drum volume 400.00 l, load size16.0 kg-22.0 kg
- Unique, gentle fabric care honeycomb drum
- Automatic heat exchanger cleaning thanks to StreamClean process
- 60 % lower energy consumption than vented dryer*
- Connected for the future using LAN and WiFi
- Fig. shows tumble dryer with heat pump module (order separately)

EAN: 4002516443636 / Material number: 11795880 / Old Material Number: 52922023EU

EAN: 4002516443636 / Material number: 11795880 / Old	TMaterial Number: 52922023E0
Construction type and version	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Load size with a load ratio of 1:25	16.0
Load size with a load ratio of 1:18	22.0
Drum volume in I	400.00
Drying system	Heat pump
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Convertible door hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	`
Suitable for hospitals	
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	<u> </u>
Suitable for the food-processing industry	<u> </u>
Suitable for amusement parks & holiday complexes	<u> </u>
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in I/hour	12.60
Specific energy consumption in kWh/kg	0.21
Programme duration in min.	42
Service life in drying cycles	40000
Control system	
Control system	M Touch Pro
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard electrical connection	
Heating type	Heat pump with CleanStream
Electrical connection	3N AC 400V 50HZ
	3.1.13 100 7 001 12

Heat pump dryers consume up to 60 % less energy than an electrically heated vented dryer.



PDR 922 HP [EL APDR 902]

Professional heat-pump dryer incl. powerful heat pump APDR 902 lowest energy consumption, without complicated exhaust ducting installation.



EAN: 4002516443636 / Material number: 11795880 / Old Material Number: 52922023EU

Total connected load in kW 16.00	Electric heater rating in kW	0.00
Total connected load in kW 6.00		
Fuse rating in A Dimensions and weight of dryer External dimensions, height in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross height in mm 1164 External dimensions, gross height in mm 1526 External dimensions, gross width in mm External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1254 Net weight in kg Gross weight in kg Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. External dimensions, net height in mm 1370 External dimensions, net width in mm 906 External dimensions, net width in mm 426 External dimensions, gross height in mm 1530 Net weight in kg 184.4 External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in M.J/h Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry 9 SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant R450a Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) • Connection options Payment system (optional) • Capacities Respirator masks [number] 16		
External dimensions, height in mm External dimensions, keight in mm External dimensions, depth in mm External dimensions, gepth in mm 1164 External dimensions, gross height in mm 1526 External dimensions, gross height in mm 1526 External dimensions, gross width in mm 1090 External dimensions, gross width in mm 1254 Net weight in kg 180.2 Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. External dimensions, net height in mm 1370 External dimensions, net width in mm 906 External dimensions, net depth in mm 426 External dimensions, gross height in mm 1530 Net weight in kg 184.4 External dimensions, gross height in mm 1000 External dimensions, gross septh in mm 1000 External dimensions, gross beight in mm 1000 External dimensions, gross beight in mm 1000 External dimensions, gross depth in mm 2170 External dimensions, gross depth in mm 2180 External dimensions, gross depth in mm 3800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace End sidesipation into the room in MJ/h 4,70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airiflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Peach of the proper optional Peach of the proper optio		
External dimensions, height in mm 1400 External dimensions, width in mm 906 External dimensions, depth in mm 1164 External dimensions, gross height in mm 1526 External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1254 Net weight in kg 180.2 Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. External dimensions, net height in mm External dimensions, net width in mm 1370 External dimensions, net height in mm 426 External dimensions, gross height in mm 1530 Net weight in kg 184.4 External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emission sound pressure level in the workplace 53 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 4,70 Features 1 CleanStream (heat exchanger cleaning) • Intellig		
External dimensions, width in mm 906 External dimensions, gross height in mm 1164 External dimensions, gross width in mm 1090 External dimensions, gross width in mm 1090 External dimensions, gross width in mm 1254 Net weight in kg 180.2 Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. 1370 External dimensions, net height in mm 1370 External dimensions, net depth in mm 426 External dimensions, gross height in mm 1530 Net weight in kg 184.4 External dimensions, gross width in mm 1000 External dimensions, gross width in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data 800 Emissions ound pressure level in the workplace 53 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 4.70 Features 10 CleanStream (heat exchanger cleaning) • Intelligent drum reversal •		1400
External dimensions, gross height in mm 1526 External dimensions, gross wight in mm 1526 External dimensions, gross wight in mm 1090 External dimensions, gross depth in mm 1254 Net weight in kg 180.2 Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. 1370 External dimensions, net height in mm 1370 External dimensions, net width in mm 906 External dimensions, gross height in mm 1530 Not weight in kg 184.4 External dimensions, gross width in mm 1000 External dimensions, gross width in mm 400 External dimensions, gross depth in mm 400 External dimensions depth in mm 400 <t< td=""><td></td><td></td></t<>		
External dimensions, gross height in mm External dimensions, gross width in mm 1090 External dimensions, gross depth in mm 1254 Net weight in kg 180.2 Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. External dimensions, net height in mm 1370 External dimensions, net width in mm External dimensions, net depth in mm 426 External dimensions, gross height in mm 1530 Net weight in kg External dimensions, gross height in mm 1630 Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross width in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow 1.0 External filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16		
External dimensions, gross width in mm External dimensions, gross depth in mm 1254 Net weight in kg 180.2 Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. External dimensions, net height in mm 1370 External dimensions, net height in mm External dimensions, net depth in mm 906 External dimensions, gross height in mm 1530 Net weight in kg External dimensions, gross width in mm 1530 Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) • Capacities Respirator masks [number] 16		
External dimensions, gross depth in mm		
Net weight in kg Gross weight in kg Haximum floor load in N/m² Dimensions/weight of HP mod. External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm External dimensions, set depth in mm Hot weight in kg External dimensions, gross height in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg External dimensions, gross width in mm Hot weight in kg Hot Watternal Hot Watte		
Gross weight in kg 195 Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. 1370 External dimensions, net height in mm 1370 External dimensions, net width in mm 906 External dimensions, gross height in mm 426 External dimensions, gross height in mm 1530 Net weight in kg 184.4 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data 217.0 Maximum floor load in N/m² 1809 Emission sound pressure level in the workplace 53 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) • Intelligent drum reversal • Axial airflow • Large-surface fluff filter • PerfectDry • SoftLift drum ribs • Communication slot • Emergency switch-off • Machine-independent accessories • Efficiency and sustainability • Coolant R450a Refrigerant global warming potential in kg CO2e 2299 Connection options		180.2
Maximum floor load in N/m² 2092 Dimensions/weight of HP mod. 1370 External dimensions, net height in mm 1370 External dimensions, net width in mm 906 External dimensions, gross height in mm 426 External dimensions, gross height in mm 1530 Net weight in kg 184.4 External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data 1809 Emission sound pressure level in the workplace 53 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 4.70 Features 53 dB(A) re 20 μPa CleanStream (heat exchanger cleaning) • Intelligent drum reversal • Axial airflow • Large-surface fluff filter • PerfectDry • SoftLift drum ribs • Communication slot • Emergency switch-off • Machine-independent accessories • Efficiency and sustainability • <td></td> <td>195</td>		195
External dimensions, net height in mm External dimensions, net width in mm 906 External dimensions, net depth in mm 426 External dimensions, gross height in mm 1530 Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross width in mm 1000 External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 184.4 External dimensions, gross depth in mm 800 Gross weight in kg 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Appliance global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16		2092
External dimensions, net height in mm External dimensions, net width in mm 906 External dimensions, net depth in mm 426 External dimensions, gross height in mm 1530 Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross width in mm 1000 External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 184.4 External dimensions, gross depth in mm 800 Gross weight in kg 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Appliance global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16	Dimensions/weight of HP mod.	
External dimensions, net depth in mm External dimensions, gross height in mm 1530 Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross width in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] Respirator masks [number] 160	•	1370
External dimensions, net depth in mm External dimensions, gross height in mm 1530 Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross width in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] Respirator masks [number] 160	External dimensions, net width in mm	906
Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry 9offLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] Respirator masks [number] 16		426
Net weight in kg External dimensions, gross width in mm 1000 External dimensions, gross depth in mm 800 Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry 9offLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] Respirator masks [number] 16	External dimensions, gross height in mm	1530
External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm B00 Gross weight in kg B17.0 Existernal dimensions, gross depth in mm B00 Emission swight in kg B18.09 Emission sound pressure level in the workplace Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] R60 1800 217.0 1800 217.0 1800 247.0 1800 4.70 4.70 4.70 4.70 4.70 4.70 4.70 4.		184.4
External dimensions, gross depth in mm Gross weight in kg 217.0 Maximum floor load in N/m² 1809 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.70 Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16		1000
Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16		800
Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16		217.0
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16	Maximum floor load in N/m ²	1809
Heat dissipation into the room in MJ/h Features CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 4 4.70 4.70 4.70 4.70 4.70 4.70 4.70 4.70 6 6 6 6 6 6 6 6 7 7 8 8 8 8 8 8 8 8 8 8 8	Emissions data	
CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16	Emission sound pressure level in the workplace	53 dB(A) re 20 μPa
CleanStream (heat exchanger cleaning) Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • • • • • • • • • •	Heat dissipation into the room in MJ/h	4.70
Intelligent drum reversal Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16	Features	
Axial airflow Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16	CleanStream (heat exchanger cleaning)	•
Large-surface fluff filter PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16	Intelligent drum reversal	•
PerfectDry SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • • • • • • • • • • • • •	Axial airflow	•
SoftLift drum ribs Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • • • • Communication slot • R450a R450a 605 Appliance global warming potential in kg CO2e 2299 Consection options • • Capacities Respirator masks [number]	Large-surface fluff filter	•
Communication slot Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • • • Communication slot • R450a 605 Ap450a 605 Ap299 CO2e 2299 Connection options • • Capacities Respirator masks [number]	PerfectDry	•
Emergency switch-off Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number]	SoftLift drum ribs	•
Machine-independent accessories Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • ### A450a Re450a ### CO2e	Communication slot	•
Efficiency and sustainability Coolant Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] R450a R450a R450a R450a R450a Feb. 605 2299 Conection options • Connection options • Capacities Respirator masks [number]	Emergency switch-off	•
Coolant R450a Refrigerant global warming potential in kg CO2e 605 Appliance global warming potential in kg CO2e 2299 Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] R450a R650a R6	Machine-independent accessories	•
Refrigerant global warming potential in kg CO2e Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 605 2299 CO2e 2299 • • • • • • • • • • • • Capacities Respirator masks [number]	Efficiency and sustainability	
Appliance global warming potential in kg CO2e Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 2299 • • Conector Box • 16		
Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] - • • • • • • • • • • • • • • • • • •		605
Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number]		2299
Optical interface for service access Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • 16		
Peak load cut-out/energy management (optional) WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] 16		•
WiFi tumble dryer Connector Box LAN module (optional) Capacities Respirator masks [number] • 16		•
Connector Box LAN module (optional) Capacities Respirator masks [number] 16		•
LAN module (optional) Capacities Respirator masks [number] 16		
CapacitiesRespirator masks [number]16		•
Respirator masks [number] 16		•
	•	10
Overails [number] 3	Respirator masks [number]	7.6
	Overalla favorbari	



PDR 922 HP [EL APDR 902]

Professional heat-pump dryer incl. powerful heat pump APDR 902 lowest energy consumption, without complicated exhaust ducting installation.



EAN: 4002516443636 / Material number: 11795880 / Old Material Number: 52922023EU

Over jackets [number]	5
Synthetic duvets [number]	2
Synthetic pillows [number]	3
Down duvets [number]	2
Down pillows [number]	4
Cloths, 22 g [number]	364
Cotton mops, 40 cm [number]	84
Cotton mops, 50 cm [number]	73
Microfibre mops, 40 cm [number]	133
Microfibre mops, 50 cm [number]	94
Summer horse blankets [number]	3
Standards, test certificates and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•