## Miele

## PW 6241 [EL SOM WEK MF]

Washing machine, electrically heated

For marine requirements, powder detergent dispenser, liquid dispensing module.



- Large programme variety application-specific wash programmes
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %\*, g-factor541
- Gentle laundry care thanks to the Miele honeycomb drum
- Drum volume 240 I, load size 24.0 kg

EAN: 4002516447054 / Material number: 11813670 / Old Material Number: 51624105SOM

| Construction type and version   |                     |
|---|---------------------|
| Construction type   | Front loader        |
| Range   | Professional        |
| Front   | Stainless steel     |
| Control panel colour  | Stainless steel     |
| Load ratio  | 1:10                |
| Load in kg  | 24.0                |
| Drum volume in I  | 240                 |
| Door opening [Ø] in mm  | 430                 |
| Door opening angle in degrees   | 180                 |
| Door hinge  | right               |
| Maintenance-free motor with frequency converter   | •                   |
| Honeycomb drum  | •                   |
| Application   |                     |
| Suitable for marine use   | •                   |
| Performance data  |                     |
| Tested virucidal efficacy   | •                   |
| Proven hygiene  | •                   |
| Specific water consumption for cold water connection in I/kg                            | 9.00                |
| Specific energy consumption for cold water connection in kWh/kg                         | 0.26                |
| Specific water consumption for hot water connection in I/kg                             | 8.80                |
| Specific energy consumption for hot water connection in kWh/kg                          | 0.10                |
| Water consumption with cold water connection in I                                       | 216.0               |
| Energy consumption with cold water connection in kW                                     | 6.24                |
| Programme duration in minutes with cold water connection                                | 60                  |
| Water consumption with hot water connection in I  | 211.0               |
| Energy consumption with hot water connection in kW                                      | 2.40                |
| Programme duration in minutes with cold water and hot water connection                  | 49                  |
| Water consumption in ECO programme with cold water connection in I                      | 212.3               |
| Energy consumption in ECO programme with cold water                                     | 5.04                |
| Programme duration in minutes with cold water connection in ECO programme               | 46                  |
| Water consumption in ECO programme with hot water connection in I                       | 212.5               |
| Energy consumption in ECO programme with hot water                                      | 1.44                |
| Programme duration in minutes with cold water and hot water connection in ECO programme | 36                  |
| Residual moisture with cold rinse in %  | 46                  |
| Residual moisture with hot rinse in %   | 43                  |
| Spin speed in rpm   | 1100                |
| g factor  | 541                 |
| Tested operating hours  | 30000               |
| Control system  |                     |
| Control system  | Profitronic M       |
| Programmability   | Freely programmable |
| Max. delay start in h   | Freely selectable   |
|   |                     |

Residual moisture specification relates to a hot rinse during the last rinse cycle.



## PW 6241 [EL SOM WEK MF]

Washing machine, electrically heated

For marine requirements, powder detergent dispenser, liquid dispensing module.



EAN: 4002516447054 / Material number: 11813670 / Old Material Number: 51624105SOM

| Time left display  | •                           |
|--|-----------------------------|
| Programme sequence indicator                             | •                           |
| Selectable display languages                             | •                           |
| Standard/target grp programmes                           |                             |
| Basic programmes   | •                           |
| Programmes for the hotel and catering industry           | •                           |
| Programmes for retirement and care homes                 | •                           |
| Programmes for facility management                       | •                           |
| Programmes for dry cleaners                              | •                           |
| Programmes for small businesses                          | •                           |
| Programmes for fire brigades and rescue services         | •                           |
| Programmes for studs, riding schools, and stables        | •                           |
| Programmes for hospitals                                 | •                           |
| Programmes for sports clubs                              | •                           |
| Programmes for beauty clinics, spas, and fitness studios | •                           |
| Dispensing   |                             |
| Detergent drawer   | 3 compartments              |
| Liquid dispensing module                                 | •                           |
| Maximum number of connections for liquid dispenser       | 12                          |
| pumps [number]   |                             |
| Empty sensor   | •                           |
| Standard electrical connection                           |                             |
| Heating type   | Electric                    |
| Electrical connection                                    | 3N AC 380-415V 50-60HZ      |
| Heater rating in kW                                      | 24.00                       |
| Total connected load in kW                               | 25.00                       |
| Fuse rating in A   | 50                          |
| Water connection/drainage                                |                             |
| Cold water [number]                                      | 3 x 1/2" hose w/ 3/4" union |
| Hot water [number]                                       | 1x 1/2" hose w/ 3/4" th.    |
|  | union                       |
| Dump valve   | DN 70                       |
| Dimensions and weight                                    |                             |
| External dimensions, height in mm                        | 1643                        |
| External dimensions, width in mm                         | 1089                        |
| External dimensions, depth in mm                         | 1250                        |
| External dimensions, gross height in mm                  | 1700                        |
| External dimensions, gross width in mm                   | 1336                        |
| External dimensions, gross depth in mm                   | 1530                        |
| Net weight in kg   | 640.0                       |
| Gross weight in kg                                       | 691                         |
| Maximum floor load in N/m <sup>2</sup>                   | 8853                        |
| Emissions data   |                             |
| Emission sound pressure level in the workplace           | 78 dB(A) re 20 μPa          |
| Heat dissipation into the room in MJ/h                   | 4.70                        |
| Features   |                             |
| Patented pre-spin  | •                           |
| Cloth reprocessing                                       | •                           |
| Imbalance monitoring                                     | •                           |
| Temperature monitoring                                   | •                           |
| Special heater element                                   | •                           |
|  |                             |



## PW 6241 [EL SOM WEK MF]

Washing machine, electrically heated

For marine requirements, powder detergent dispenser, liquid dispensing module.



EAN: 4002516447054 / Material number: 11813670 / Old Material Number: 51624105SOM

| Automatic load control+                              | •   |
|--|-----|
| Volumetric flow meter (optional)                     | •   |
| Communication slot                                   | •   |
| Emergency switch-off                                 | •   |
| Machine-independent accessories                      | •   |
| Efficiency and sustainability                        |     |
| Recycling rate in %                                  | 96  |
| Connection options                                   |     |
| Payment system (optional)                            | •   |
| Optical interface for service access                 | •   |
| Serial interface module RS 232 (optional)            | •   |
| Peak-load negotiation / energy management (optional) | •   |
| Operating data acquisition                           | •   |
| Water recovery (optional)                            | •   |
| Capacities   |     |
| Respirator masks [number]                            | 19  |
| Overalls [number]                                    | 4   |
| Over jackets [number]                                | 6   |
| Chemical protection suits [number]                   | 4   |
| Synthetic duvets [number]                            | 3   |
| Synthetic pillows [number]                           | 6   |
| Down duvets [number]                                 | 3   |
| Down pillows [number]                                | 6   |
| Cloths, 22 g [number]                                | 546 |
| Cotton mops, 40 cm / 190 g [number]                  | 126 |
| Cotton mops, 50 cm / 220 g [number]                  | 109 |
| Microfibre mops, 40 cm / 120 g [number]              | 200 |
| Microfibre mops, 50 cm / 170 g [number]              | 141 |
| Summer horse blankets [number]                       | 4   |
| Standards, test certificates and symbols             |     |
| CE   | •   |
| VDE-EMC  | •   |
| VDE  | •   |
| Splash-proof safety rating IPX4                      | •   |
| UKCA   | •   |
| WEEE   | •   |
| RCM  | •   |
| EAC  | •   |
| Complies with Machinery Directive 2006/42/EC         | •   |