#### Miele

#### PW 6241 [EL MF] Washing machine, electrically heated With liquid dispenser and individually programmable controls.



- Drum volume 240 I, load size 24.0 kg
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %, g-factor541

EAN: 4002516447092 / Material number: 11813750 / Old Material Number: 51624108NER

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:10
Load in kg	24.0
Drum volume in I	240
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	
Specific water consumption for cold water connection in I/	9.00
kg	9.00
Specific energy consumption for cold water connection in	0.26
kWh/kg	
Specific water consumption for hot water connection in I/kg	8.80
Specific energy consumption for hot water connection in kWh/kg	0.10
Water consumption with cold water connection in I	216.0
· · · · · · · · · · · · · · · · · · ·	
Energy consumption with cold water connection in kW	6.24
Programme duration in minutes with cold water connection	60
Water consumption with hot water connection in I	211.0
Energy consumption with hot water connection in kW	2.40
Programme duration in minutes with cold water and hot water connection	49
Water consumption in ECO programme with cold water	212.3
connection in I	2.2.0
Energy consumption in ECO programme with cold water	5.04
Programme duration in minutes with cold water connection	46
in ECO programme	
Water consumption in ECO programme with hot water connection in I	212.5
Energy consumption in ECO programme with hot water	1.44

<sup>\*</sup>Residual moisture specification relates to a hot rinse during the last rinse cycle.

### Míele

# PW 6241 [EL MF] Washing machine, electrically heated With liquid dispenser and individually programmable controls.



EAN: 4002516447092 / Material number: 11813750 / Old Material Number: 51624108NER

Programme duration in minutes with cold water and hot 36

Programme duration in minutes with cold water and hot water connection in ECO programme	36
Residual moisture with cold rinse in %	46
Residual moisture with hot rinse in %	43
Spin speed in rpm	1100
g factor	541
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
Basic programmes	•
Programmes for the hotel and catering industry	
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	
Programmes for small businesses	
Programmes for fire brigades and rescue services	
Programmes for studs, riding schools, and stables	- <del>-</del>
	•
Programmes for hospitals Programmes for sports clubs	- <del>-</del>
	- <del>-</del>
Programmes for beauty clinics, spas, and fitness studios	
Dispensing Determine drower	2 comportments
Detergent drawer	3 compartments
Liquid dispensing module	
Maximum number of connections for liquid dispenser	10
Maximum number of connections for liquid dispenser	12
pumps [number]	12 •
pumps [number] Empty sensor	12
pumps [number] Empty sensor Standard electrical connection	•
pumps [number]  Empty sensor  Standard electrical connection  Heating type	• Electric
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection	Electric 3N AC 380-415V 50-60HZ
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW	Electric 3N AC 380-415V 50-60HZ 24.00
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW	Electric 3N AC 380-415V 50-60HZ 24.00 25.00
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A	Electric 3N AC 380-415V 50-60HZ 24.00
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage	Electric 3N AC 380-415V 50-60HZ 24.00 25.00 50
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]	Electric 3N AC 380-415V 50-60HZ 24.00 25.00 50 3 x 1/2" hose w/ 3/4" union
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage	Electric 3N AC 380-415V 50-60HZ 24.00 25.00 50
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th.
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th. union
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th. union
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve  Dimensions and weight	Electric 3N AC 380-415V 50-60HZ 24.00 25.00 50  3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve  Dimensions and weight  External dimensions, height in mm	Electric 3N AC 380-415V 50-60HZ 24.00 25.00 50  3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union DN 70  1643
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve  Dimensions and weight  External dimensions, height in mm  External dimensions, width in mm	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th. union  DN 70  1643  1089
pumps [number]  Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve  Dimensions and weight  External dimensions, height in mm  External dimensions, depth in mm	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th. union  DN 70  1643  1089  1250
Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve  Dimensions and weight  External dimensions, height in mm  External dimensions, depth in mm  External dimensions, gross height in mm	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th. union  DN 70  1643  1089  1250  1700
Empty sensor  Standard electrical connection  Heating type  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Water connection/drainage  Cold water [number]  Hot water [number]  Dump valve  Dimensions and weight  External dimensions, height in mm  External dimensions, depth in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross width in mm	Electric  3N AC 380-415V 50-60HZ  24.00  25.00  50  3 x 1/2" hose w/ 3/4" union  1x 1/2" hose w/ 3/4" th. union  DN 70  1643  1089  1250  1700  1336

### **M**íele

# PW 6241 [EL MF] Washing machine, electrically heated With liquid dispenser and individually programmable controls.



EAN: 4002516447092 / Material number: 11813750 / Old Material Number: 51624108NER

Gross weight in kg	691
Maximum floor load in N/m <sup>2</sup>	8853
Emissions data	
Emission sound pressure level in the workplace	78 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	4.70
Features	
Patented pre-spin	•
Cloth reprocessing	•
Imbalance monitoring	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Communication slot	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	96
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak-load negotiation / energy management (optional)	•
Operating data acquisition	•
Water recovery (optional)	•
Capacities	
Respirator masks [number]	19
Overalls [number]	4
Over jackets [number]	6
Chemical protection suits [number]	4
Synthetic duvets [number]	3
Synthetic pillows [number]	6
Down duvets [number]	3
Down pillows [number]	6
Cloths, 22 g [number]	546
Cotton mops, 40 cm / 190 g [number]	126
Cotton mops, 50 cm / 220 g [number]	109
Microfibre mops, 40 cm / 120 g [number]	200
Microfibre mops, 50 cm / 170 g [number]	141
Summer horse blankets [number]	4
Standards, test certificates and symbols	
CE	
VDE-EMC	•
VDE	
Splash-proof safety rating IPX4	•
UKCA	
WEEE	
Complies with Machinery Directive 2006/42/EC	•