

PW 6241 [D dir.] Washing machine, steam heated (direct) With individually programmable controls for the maximum in flexibility.



- Drum volume 240 l, load size 24.0 kg
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 43 %^{*}, g-factor541

* Residual moisture specification relates to a hot rinse during the last rinse cycle.

EAN: 4002516447382 / Material number: 11813880 / Old Material Number: 51624147NER

Construction type and version	
Construction type	Front loader
Range	Professional
Front	Stainless steel
Control panel colour	Stainless steel
Load ratio	1:10
Load in kg	24.0
Drum volume in I	240
Door opening [Ø] in mm	430
Door opening angle in degrees	180
Door hinge	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Performance data	•
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	9.00
kg	9.00
Specific water consumption for hot water connection in I/kg	8.80
Water consumption with cold water connection in I	216.0
Water consumption with hot water connection in I	211.0
Water consumption in ECO programme with cold water connection in I	212.3
Water consumption in ECO programme with hot water	212.5
connection in I	
Residual moisture with cold rinse in %	46
Residual moisture with hot rinse in %	43
Spin speed in rpm	1100
g factor	541
Tested operating hours	30000
Control system	
Control system	Profitronic M
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Standard/target grp programmes	
	•
Basic programmes	-



PW 6241 [D dir.] Washing machine, steam heated (direct) With individually programmable controls for the maximum in flexibility.



EAN: 4002516447382 / Material number: 11813880 / Old Material Number: 51624147NER

Programmes for relation and care homes • Programmes for facility management • Programmes for facility management • Programmes for facility management • Programmes for fire brigades and rescue services • Programmes for sports dubs • Programmes for beauty clinics, spas, and fitness studios • Dispensing • Detergent drawer 2 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser • Standard electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in A 16 Water connection/drainage • Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam onnection 1x 3/4" Dimensions and weight • External dimensions, gross height in mm 1643		
Programmes for facility management • Programmes for synal businesses • Programmes for smal businesses • Programmes for fire brigades and rescue services • Programmes for sports clubs • Programmes for sports clubs • Programmes for sports clubs • Programmes for beauty clinics, spas, and fitness studios • Dispensing • Detergent drawer 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser 12 pumps [number] Empty sensor Standard electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in kW 66.00 Total connected load in kW 6.10 Fuse rating in A 16 Water connection/drainage V Cold water [number] X 1/2* hose w/ 3/4* th. union 10 × 1/2* hose w/ 3/4* th. union DN 70 Steam connection 1 × 3/4* Dimensions and weight External dimensions, depth in mm External dimensions, gross depth in mm 1250	Programmes for the hotel and catering industry	•
Programmes for dry cleaners • Programmes for small businesses • Programmes for studs, riding schools, and stables • Programmes for bospitals • Programmes for beauty clinics, spas, and fitness studios • Detergent drawer 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser • pumps [number] 12 Empty sensor • Standard electrical connection 3N AC 380-415V 50-60HZ Stam and electrical connection 3N AC 380-415V 50-60HZ Stam and electrical connection 3N AC 380-415V 50-60HZ Stam heater rating in kW 66.00 Total connection load in kW 6.10 Fuse rating in A 16 Water connection 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam onnection 1x 3/4" Dimensions and weight 1250 External dimensions, keight in mm 1643 External dimensions, gross height in mm 1336 External dimensions, gross height in mm 1530 External dimensions, gross height in mm	Programmes for retirement and care homes	
Programmes for small businesses • Programmes for fire brigades and rescue services • Programmes for studs, riding schools, and stables • Programmes for bospitals • Programmes for sports clubs • Programmes for bospitals • Dispensing • Detergent drawer 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser • Empty sensor • Standard electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in kW 86.00 Total connection/Crainage • Cold water [number] 2x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam connection/ 1 x 3/4" Dimensions and weight • External dimensions, keight in mm 1643 External dimensions, gross weight in mm 1320 External dimensions, gross weight in mm 1530 External dimensions, gross weight in mm 1530 External dimensions, gross weight in mm 1530	Programmes for facility management	
Programmes for fire brigades and rescue services • Programmes for studs, riding schools, and stables • Programmes for sports clubs • Programmes for beauty clinics, spas, and fitness studios • Dispensing 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser 12 pumps [number] • Empty sensor • Standard electrical connection 12 Heating type Direct steam Electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in RW 86.00 Total connected load in kW 6.10 Fuse rating in A 16 Water connection/drainage Col water [number] Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 3/4" Dimensions and weight External dimensions, height in mm External dimensions, depth in mm 1250 External dimensions, gross width in mm 1330 External dimensions, gross depth in mm 1330 External dimensions, gross depth in mm 1330 External	Programmes for dry cleaners	
Programmes for studs, riding schools, and stables • Programmes for hospitals • Programmes for pospits clubs • Programmes for beauty clinics, spas, and fitness studios • Detergent drawer 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in RW 86.00 Total connected load in KW 6.10 Fuse rating in A 16 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam connection 1 × 3/4" Dimensions and weight 1250 External dimensions, width in mm 1280 External dimensions, gross height in mm 1330 External dimensions, gross height in mm 1530 Net weight in kg 693 Maximum floor load in N/m ² 8873 Emtend intensions, gross height in mm 1530 Net weight in kg	Programmes for small businesses	
Programmes for hospitals • Programmes for sports clubs • Programmes for beauty clinics, spas, and fitness studios • Dispensing • Detergent drawer 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser 12 empty sensor • Standard electrical connection 3N AC 380-415V 50-60HZ Betaring type Direct steam Electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in KW 6.10 Fuse rating in A 16 Water connection/drainage 2x 1/2* hose w/ 3/4* th. Cold water [number] 1x 1/2* hose w/ 3/4* th. union DN 70 Steam connection 1 x 3/4* Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm 1250 External dimensions, gross depth in mm 1336 External dimensions, gross depth in mm 1530 Net weight in kg 693 Maximum flor loa in N/m ² 8873 Emission sound pressure level in the workplace 78 dB	Programmes for fire brigades and rescue services	
Programmes for sports clubs • Programmes for beauty clinics, spas, and fitness studios • Dispensing 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in kW 86.00 Total connected load in kW 6.10 Fuse rating in A 16 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam connection 1 x 3/4" Dimensions and weight 1 External dimensions, height in mm 1643 External dimensions, depth in mm 1290 External dimensions, depth in mm 1336 External dimensions, gross width in mm 1336 External dimensions, gross beight in mm 1530 Net weight in kg 693 Maximum floor load in N/m² 8873 Emission sound pressure level in the workplace 78 dB(A) re 20 µPa Heat dissipatio	Programmes for studs, riding schools, and stables	
Programmes for beauty clinics, spas, and fitness studios • Dispensing 3 compartments Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection 3N AC 380-415V 50-60HZ Beter rating in KW 86.00 Total connected load in kW 6.10 Fuse rating in A 16 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Cold water [number] 2x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam connection 1x 3/4" Dimensions and weight 1250 External dimensions, height in mm 1643 External dimensions, digth in mm 1280 External dimensions, gross height in mm 1200 External dimensions, gross height in mm 1530 Net weight in kg 642.0 Gross weight in kg 643.0 External dimensions, gross height in mm 1530 Net weight in kg 642.0 Gross weight in kg 642.0 Gross weight in kg 642.0	Programmes for hospitals	•
Dispensing3 compartmentsLiquid dispensing module (optional)•Maximum number of connections for liquid dispenser12pumps [number]12Empty sensor•Standard electrical connection3N AC 380-415V 50-60HZBeterrical connection3N AC 380-415V 50-60HZSteam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]2x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1 x 3/4"Dimensions and weight1External dimensions, height in mm1643External dimensions, gross width in mm1336External dimensions, gross width in mm1336External dimensions, gross width in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spinOloh reprocessing•Imalance monitoring•Special heater element•Automatic load control+•	Programmes for sports clubs	
Detergent drawer3 compartmentsLiquid dispensing module (optional)•Maximum number of connections for liquid dispenser pumps [number]12Empty sensor•Standard electrical connection3N AC 380-415V 50-60HZBetarding typeDirect steamElectrical connected load in kW6.10Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]1x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1 x 3/4"Dimensions and weight1643External dimensions, height in mm1250External dimensions, gerss height in mm1336External dimensions, gross width in mm1336External dimensions, gross width in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features1Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Special heater element•Automatic load control+•	Programmes for beauty clinics, spas, and fitness studios	•
Liquid dispensing module (optional) • Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection IN AC 380-415V 50-60HZ Beam heater rating in kW 86.00 Total connected load in kW 6.10 Fuse rating in A 16 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam connection 1 x 3/4" Dimensions and weight External dimensions, height in mm External dimensions, height in mm 1643 External dimensions, keight in mm 1250 External dimensions, gross weight in mm 1530 External dimensions, gross weight in mm 1530 Net weight in kg 642.0 Gross weight in kg 693 Maximum floor load in N/m ² 8873 Emission sound pressure level in the workplace 78 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 4.70 Features 9 Patented pre-spin • Cloth reprocessing <t< td=""><td>Dispensing</td><td></td></t<>	Dispensing	
Maximum number of connections for liquid dispenser pumps [number] 12 Empty sensor • Standard electrical connection Interstate Heating type Direct steam Electrical connection 3N AC 380-415V 50-60HZ Steam heater rating in kW 86.00 Total connected load in kW 6.10 Fuse rating in A 16 Water connection/drainage 2x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Steam connection 1 x 3/4" Dimensions and weight External dimensions, height in mm External dimensions, keight in mm 1633 External dimensions, gross weight in mm 1643 External dimensions, gross weight in mm 1643 External dimensions, gross weight in mm 1250 External dimensions, gross weight in mm 1336 External dimensions, gross weight in mm 1530 Net weight in kg 693 Maximum floor load in N/m ² 8873 Emission sound pressure level in the workplace 78 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 4.70	Detergent drawer	3 compartments
pumps [number]Empty sensor•Standard electrical connectionDirect steamHeating typeDirect steamElectrical connection3N AC 380-415V 50-60HZSteam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]2x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connectionNNEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weight1643External dimensions, height in mm1643External dimensions, gross height in mm1250External dimensions, gross beight in mm1336External dimensions, gross beight in mm1530Net weight in kg642.0Gross weight in kg643Heat dissipation into the room in MJ/h4.70Heat dissipation into the room in MJ/h4.70FeaturesPatented pre-spinPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Temperature monitoring•Special heater element•Automatic load control+•	Liquid dispensing module (optional)	•
Empty sensor•Standard electrical connectionDirect steamElectrical connection3N AC 380-415V 50-60HZSteam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]1x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, depth in mm1250External dimensions, gross height in mm1336External dimensions, gross beight in mm1530External dimensions, gross beight in mm1530Net weight in kg693Maximum floor load in N/m28873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spinPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Temperature monitoring•Temperature monitoring•Automatic load control+•		12
Standard electrical connectionHeating typeDirect steamElectrical connection3N AC 380-415V 50-60HZSteam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]1x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1 x 3/4"Dimensions and weight1089External dimensions, height in mm1643External dimensions, depth in mm1250External dimensions, gross height in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spinPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•		•
Heating typeDirect steamElectrical connection3N AC 380-415V 50-60HZSteam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]1x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1Dimensions and weight1External dimensions, height in mm1643External dimensions, depth in mm1250External dimensions, gross height in mm1336External dimensions, gross width in mm1336External dimensions, gross width in mm1530Net weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 μPaHeat dissipation into the room in MJ/h4.70Features9Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•		
Electrical connection3N AC 380-415V 50-60HZSteam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]1x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1 x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, width in mm1643External dimensions, gross height in mm1250External dimensions, gross weight in mm1336External dimensions, gross weight in mm1530Net weight in kg693Maximum floor load in N/m28873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spinPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Special heater element•Automatic load control+•		Direct steam
Steam heater rating in kW86.00Total connected load in kW6.10Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]2x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1 x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm1643External dimensions, depth in mm1250External dimensions, gross height in mm1336External dimensions, gross weight in mm1530External dimensions, gross weight in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features•Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•		3N AC 380-415V 50-60HZ
Fuse rating in A16Water connection/drainage2x 1/2" hose w/ 3/4" th. unionCold water [number]2x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connectionNEMA Plug: Twist Lock L6-30NEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, width in mm1643External dimensions, of pots height in mm1250External dimensions, gross height in mm1336External dimensions, gross beight in mm1336External dimensions, gross beight in mm1530Net weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 μPaHeat dissipation into the room in MJ/h4.70Features•Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•		86.00
Water connection/drainageCold water [number]2x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1NEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm1643External dimensions, depth in mm1250External dimensions, gross height in mm1336External dimensions, gross height in mm1336External dimensions, gross beight in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•	Total connected load in kW	6.10
Water connection/drainageCold water [number]2x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connection1 x 3/4"NEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm1643External dimensions, depth in mm1250External dimensions, gross height in mm1336External dimensions, gross height in mm1336External dimensions, gross beight in mm1530Net weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features•Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•		
unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Steam connectionImage: Steam connectionNEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weightImage: Steam connectionExternal dimensions, height in mm1643External dimensions, width in mm1089External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross height in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesImage: Steam content floorPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•		
LunionDump valveDN 70Steam connectionNEMA Plug: Twist Lock L6-30NEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weightExternal dimensions, height in mmExternal dimensions, width in mm1643External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross height in mm1336External dimensions, gross width in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplacePatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	,	
Steam connection1 x 3/4"NEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weight1643External dimensions, height in mm1089External dimensions, width in mm1250External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross width in mm1336External dimensions, gross width in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features•Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	Hot water [number]	
NEMA Plug: Twist Lock L6-301 x 3/4"Dimensions and weight1643External dimensions, height in mm1089External dimensions, width in mm1089External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross height in mm1336External dimensions, gross width in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplacePatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	Dump valve	DN 70
Dimensions and weight1643External dimensions, height in mm1643External dimensions, width in mm1089External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross width in mm1336External dimensions, gross width in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplacePatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•	Steam connection	
External dimensions, height in mm1643External dimensions, width in mm1089External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross width in mm1336External dimensions, gross width in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features•Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	NEMA Plug: Twist Lock L6-30	1 x 3/4"
External dimensions, width in mm1089External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross width in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Automatic load control+•	Dimensions and weight	
External dimensions, depth in mm1250External dimensions, gross height in mm1700External dimensions, gross width in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions data1000Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features1000Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	External dimensions, height in mm	1643
External dimensions, gross height in mm1700External dimensions, gross width in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	External dimensions, width in mm	1089
External dimensions, gross width in mm1336External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions dataEmission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	External dimensions, depth in mm	1250
External dimensions, gross depth in mm1530Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions data8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features9Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Special heater element•Automatic load control+•	External dimensions, gross height in mm	1700
Net weight in kg642.0Gross weight in kg693Maximum floor load in N/m²8873Emissions data8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features9Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	External dimensions, gross width in mm	1336
Gross weight in kg693Maximum floor load in N/m²8873Emissions data8873Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features9Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	External dimensions, gross depth in mm	1530
Maximum floor load in N/m² 8873 Emissions data 8873 Emission sound pressure level in the workplace 78 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 4.70 Features 9 Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Special heater element • Automatic load control+ •	Net weight in kg	642.0
Emissions dataEmission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70FeaturesPatented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	Gross weight in kg	693
Emission sound pressure level in the workplace78 dB(A) re 20 µPaHeat dissipation into the room in MJ/h4.70Features•Patented pre-spin•Cloth reprocessing•Imbalance monitoring•Temperature monitoring•Special heater element•Automatic load control+•	Maximum floor load in N/m ²	8873
Heat dissipation into the room in MJ/h 4.70 Features - Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Special heater element • Automatic load control+ •	Emissions data	
FeaturesPatented pre-spinCloth reprocessingImbalance monitoringTemperature monitoringSpecial heater elementAutomatic load control+	Emission sound pressure level in the workplace	78 dB(A) re 20 µPa
Patented pre-spin • Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Special heater element • Automatic load control+ •	Heat dissipation into the room in MJ/h	4.70
Cloth reprocessing • Imbalance monitoring • Temperature monitoring • Special heater element • Automatic load control+ •	Features	
Imbalance monitoring • Temperature monitoring • Special heater element • Automatic load control+ •	Patented pre-spin	•
Temperature monitoring • Special heater element • Automatic load control+ •	Cloth reprocessing	•
Special heater element • Automatic load control+ •	Imbalance monitoring	•
Automatic load control+	Temperature monitoring	•
	Special heater element	•
Volumetric flow meter (optional)	Automatic load control+	•
	Volumetric flow meter (optional)	•



PW 6241 [D dir.] Washing machine, steam heated (direct) With individually programmable controls for the maximum in flexibility.



Communication slot Emergency switch-off • Machine-independent accessories • Efficiency and sustainability Recycling rate in % 96 **Connection options** Payment system (optional) • Optical interface for service access • Serial interface module RS 232 (optional) • Peak-load negotiation / energy management (optional) • Operating data acquisition • Water recovery (optional) • Capacities Respirator masks [number] 19 Overalls [number] 4 6 Over jackets [number] Chemical protection suits [number] 4 З Synthetic duvets [number] Synthetic pillows [number] 6 Down duvets [number] 3 Down pillows [number] 6 Cloths, 22 g [number] 546 Cotton mops, 40 cm / 190 g [number] 126 Cotton mops, 50 cm / 220 g [number] 109 Microfibre mops, 40 cm / 120 g [number] 200 Microfibre mops, 50 cm / 170 g [number] 141 Summer horse blankets [number] 4 Standards, test certificates and symbols CE • VDE-EMC • VDE • Splash-proof safety rating IPX4 • UKCA • WEEE • •

EAN: 4002516447382 / Material number: 11813880 / Old Material Number: 51624147NER

Complies with Machinery Directive 2006/42/EC