

PT 8203 SL WP [PTB Plus]

Heat-pump dryers

SlimLine, low energy consumption without complicated exhaust ducting installat.



- Drum volume 200.00 l, load size 8.5 kg–10.0 kg
- Very easy installation – only 711 mm wide
- Easy to move – direct access underneath
- Shortest cycles thanks to diagonal air flow
- Simple handling – Two-step filter system

EAN: 4002516475088 / Material number: 11905230 / Old Material Number: 52820460D

Construction type and version	
Construction type	SlimLine
Range	Professional
Front	Iron grey
Load size with a load ratio of 1:23	8.5
Load size with a load ratio of 1:20	10.0
Drum volume in l	200.00
Drying system	Heat pump
Door opening [Ø] in mm	520
Door opening angle in degrees	180
Door hinge	left
Stainless steel drum	•
Stainless steel honeycomb drum	No
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for residential homes and apartments	•
Suitable for commercial laundries	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Performance data	
Maximum evaporation capacity in l/hour	4.60
Specific energy consumption in kWh/kg	0.24
Programme duration in min.	63
Control system	
Control system	Profitronic B Plus
Programmability	Setting of defined parameters
User interface	Residual moisture controlled
Time left display	•
Programme sequence indicator	•
Fascia panel with plain text	•
Standard/target grp programmes	
Basic programmes	•
Standard electrical connection	
Heating type	Heat pump with CleanStream
Electrical connection	3N AC 400V 50HZ
Electric heater rating in kW	0.00
Heater rating, heat pump in kW	6.40
Total connected load in kW	2.60
Fuse rating in A	16
Dimensions and weight	
External dimensions, height in mm	1800
External dimensions, width in mm	711
External dimensions, depth in mm	1075
External dimensions, gross height in mm	1810

PT 8203 SL WP [PTB Plus]

Heat-pump dryers

SlimLine, low energy consumption without complicated exhaust ducting installat.



EAN: 4002516475088 / Material number: 11905230 / Old Material Number: 52820460D

External dimensions, gross width in mm	800
External dimensions, gross depth in mm	1180
Net weight in kg	202.0
Gross weight in kg	213
Maximum floor loading in N	2220
Emissions data	
Emission sound pressure level in the workplace	57 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	2.30
Features	
Intelligent drum reversal	•
Large-surface fluff filter	•
Two-stage filtration	•
PerfectDry	•
SoftLift drum ribs	•
Retractable plinth	•
Machine-independent accessories	•
Efficiency and sustainability	
Contains fluorinated greenhouse gases	•
Hermetically sealed system	•
Coolant	R450a
Refrigerant quantity in kg	1.35
Refrigerant global warming potential in kg CO ₂ e	605
Appliance global warming potential in kg CO ₂ e	877
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Standards, test certificates and symbols	
CE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•