

## PTD 901 [ECO] Throughfeed dishwasher

With heat recovery from exhaust air and waste water for efficient wash results.



- Max. cleaning performance<sup>\*</sup>: 1296 plates/h
- 15 % less energy consumption\* thanks to energy recuperation
- Optimum room atmosphere vapour extraction inclusive
- Always the right programme itemspecific solutions
- Simple and flexible operation full-touch display

EAN: 4002516485711 / Material number: 11917930 / Old Material Number: 61090111D

construction type lange lodel lash system lumber of levels cont lank volume in I lipplication luitable for retirement and care homes luitable for hospitals luitable for hospitality industry luitable for guesthouses luitable for canteens luitable for child care facilities luitable for universities and schools luitable for fast food restaurants luitable for sports clubs	Passthrough dishwasher Professional Performanceeco Tank passthrough 1 Stainless steel 35.0
odel  /ash system  umber of levels  ont  ank volume in I  pplication  uitable for retirement and care homes  uitable for small restaurants/bars  uitable for hospitality industry  uitable for guesthouses  uitable for canteens  uitable for universities and schools  uitable for fast food restaurants  uitable for sports clubs  erformance data  ested virucidal efficacy	Performanceeco Tank passthrough  1 Stainless steel 35.0  • • • • • • • • • • • • • • • • • •
Vash system  umber of levels  cont  ank volume in I  pplication  uitable for retirement and care homes  uitable for small restaurants/bars  uitable for hospitality industry  uitable for guesthouses  uitable for canteens  uitable for canteens  uitable for universities and schools  uitable for fast food restaurants  uitable for sports clubs  erformance data  ested virucidal efficacy	Tank passthrough  1 Stainless steel 35.0  • • • • • • • • • • • • • • • • • •
umber of levels  ront  ank volume in I  pplication  uitable for retirement and care homes  uitable for hospitals  uitable for hospitality industry  uitable for guesthouses  uitable for canteens  uitable for child care facilities  uitable for thiory sites and schools  uitable for fast food restaurants  uitable for sports clubs  erformance data  ested virucidal efficacy	1 Stainless steel 35.0  • • • • • • • • • • • • • • • • • •
pplication uitable for retirement and care homes uitable for hospitals uitable for hospitals uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for thiodocare facilities uitable for syorts clubs erformance data ested virucidal efficacy	Stainless steel 35.0  • • • • • • • • • • • • • • • • • •
pplication uitable for retirement and care homes uitable for hospitals uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for thiod care facilities uitable for syorts clubs erformance data ested virucidal efficacy	35.0 • • • • • • • • • • • • • • • • • • •
pplication uitable for retirement and care homes uitable for hospitals uitable for small restaurants/bars uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for thiod care facilities uitable for sports clubs	• • • • • • • • • • • • • • • • • • •
uitable for retirement and care homes uitable for hospitals uitable for small restaurants/bars uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for hospitals uitable for small restaurants/bars uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for small restaurants/bars uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for hospitality industry uitable for guesthouses uitable for canteens uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for guesthouses uitable for canteens uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for canteens uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for child care facilities uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for universities and schools uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for fast food restaurants uitable for sports clubs erformance data ested virucidal efficacy	•
uitable for sports clubs erformance data ested virucidal efficacy	• 300
erformance data ested virucidal efficacy	• 300
ested virucidal efficacy	• 300
•	300
'roulation numn Omay in I/m'r	300
irculation pump Qmax in I/min.	
nortest programme duration in sec.	50
aximum final rinse temperature in °C	90
leaning performance, plates/h	1296
leaning performance, glasses/h	3773
leaning performance, baskets/h	72
ervice life in wash cycles	438000
ontrol system	
ontrol system	Electronic controls
rogramme selection	Full-touch display
utomatic On/Off standby switch	•
rogrammes [number]	4
oloured programme sequence indicator	•
hoice of display language	•
tandard electrical connection	
ectrical connection	3N AC 380-415V 50HZ
eater rating in kW	6.90
ank heater rating in kW	2.50
oiler heater rating in kW	6.40
otal connected load in kW	7.90
use rating in A	16
ength of mains connection cable in m	3.50
ossible voltage variant 1	3.00
ectrical connection	3N AC 380-415V 50HZ
eater rating in kW	6.90
otal connected load in kW	
use rating in A	10.20 25
	ZU
ossible voltage variant 2 ectrical connection	AC 230V 50HZ

Depending on site conditions (temperature of incoming water / power connection) values given may vary.

<sup>&</sup>quot; Applies to all ECO models, compared to models without an energy recuperation system.



## PTD 901 [ECO] Throughfeed dishwasher With heat recovery from exhaust air and waste water for efficient wash results.



EAN: 4002516485711 / Material number: 11917930 / Old Material Number: 61090111D

Heater rating in kW	6.40
Total connected load in kW	6.90
Fuse rating in A	32
Water connection/drainage	
Cold water [number]	1
Required flow pressure in bar	1.50-6.00
Drain pump [DN]	19
Drain pump head height from floor level, max. in c	65
Booster pump	•
Maximum water hardness in mmol/l	0.54
Water consumption per wash cycle in I	2.20
Length of water inlet hose in cm	150
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions with closed hood, height	2175
External dimensions with opened hood, height	2175
External dimensions, net width in mm	635
External dimensions, net depth in mm	750
External dimensions, gross height in mm	1910
External dimensions, gross width in mm	770
External dimensions, gross depth in mm	880
Usable space in wash cabinet, height in mm	440
Usable space in wash cabinet, width in mm	540
Usable space in wash cabinet, depth of lower basket in mm	500
Usable space in wash cabinet, depth in mm	550
In-feed height above floor in mm	850
Net weight [kg]	156
Gross weight in kg	172
Maximum floor load in N/m <sup>2</sup>	2220
Emissions data	
Emissions – sound pressure at workplace	62 dB(A) re 20 μPa
Programmes	
Programme for light soiling	•
Programme for normal soiling	•
Programme for heavy soiling	•
Additional programme options	•
Wash ware specific	•
Soak	•
Self-cleaning	•
Descaling	•
Basic cleaning	•
Basket design	
Without baskets	•
Features	
Integrated dispensing pump/dispensing module for rinsing	•
agent	
Wash cabinet made from high-quality stai	•
Spray arm monitor for all spray arms	•
Manual hood operation	•
Automatic programme start once hood is closed	•
Adjustable final rinse temperature	•
Adjustable wash temperature	•



PTD 901 [ECO]
Throughfeed dishwasher
With heat recovery from exhaust air and waste water for efficient wash results.