# Miele

#### PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



- Drum volume 110 I, maximum load size 12.0 kg
- Top cleaning & consumption values – innovative Miele technology
- Ideal operation thanks to colour touch display M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

O controller to a controller	
Construction type and version	Frankling de
Construction type	Front loader
Range	Performance Plus
Front Control panel colour	Stainless steel
Control panel colour  Maximum load with a load ratio of 1:0 in kg	Stainless steel 12.0
Maximum load with a load ratio of 1:9 in kg	·
Load ratio	1:9
Load in kg  Drum volume in I	110
	415
Door opening [Ø] in mm  Door opening angle in degrees	180
Door hinge	
	right
Automatic door lock Innovative suds container	
	<u> </u>
Maintenance-free motor with frequency converter	<u> </u>
Patented honeycomb drum 2.0	
Application Suitable for offshore use	•
Suitable for marine use	
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	6.20
kg	
Specific energy consumption for cold water connection in kWh/kg	0.14
Specific water consumption for hot water connection in I/kg	5.90
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in I	74.4
Water consumption for cold water connection in Mops standard 60 °C programme in I	142.2
Energy consumption with cold water connection in kW	1.68
Energy consumption for cold water connection in Mops standard 60 °C programme in kWh	2.50
Programme duration in minutes with cold water connection	49
Water consumption with hot water connection in I	70.8
Water consumption for hot water connection in Mops standard 60 °C programme in I	139.9
Energy consumption with hot water connection in kW	0.72
Energy consumption for hot water connection in Mops standard 60 °C programme in kWh	1.00
Programme duration in minutes with cold water and hot water connection	42
Water consumption in ECO programme with cold water connection in I	69.6
Energy consumption in ECO programme with cold water	1.20
Programme duration in minutes with cold water connection in ECO programme	34
Water consumption in ECO programme with hot water connection in I	68.4
Energy consumption in ECO programme with hot water	0.36
	·



### PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



Programme duration in minutes with cold water and hot water connection in ECO programme	31
Programme running time in minutes for Mops standard 60 °C programme with cold water connection	54
Programme running time in minutes for Mops standard 60 °C programme with hot water connection	47
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	44
Residual moisture when processing cleaning cloths in %	25
Spin speed in rpm	- 1150 - 458
g factor	
Tested operating hours	30000
Control system	M.T. d. D. Dl.
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Freely selectable
Time left display	
Programme sequence indicator	•
Selectable display languages	-
Option to enter weight prior to start of programme	•
Standard/target grp programmes	
Basic programmes	•
Dispensing	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser pumps [number]	12
Empty sensor	•
Standard electrical connection	
Heating type	Electric
Electrical connection	3 AC 230V 50HZ
Heater rating in kW	9.00
Total connected load in kW	9.60
Fuse rating in A	35
Possible voltage variant 1	
Electrical connection	3 AC 230V 60HZ
Heater rating in kW	9.00
Total connected load in kW	9.60
Fuse rating in A	35
Water connection/drainage	
Cold water [number]	3 x 1/2" hose w/ 3/4" union
Hot water [number]	1x 1/2" hose w/ 3/4" th.
Tiot Water [Harrisor]	union
Hard water (optional) [number]	2 x 1/2" w/ 3/4" union
Dump valve	DN 70
Dimensions and weight	
External dimensions, height in mm	1350
External dimensions, width in mm	799
External dimensions, depth in mm	924
External dimensions, geost height in mm	1475
External dimensions, gross rieignt in mm	1090
External dimensions, gross width in mm	1130
Net weight in kg	287.0
THE WEIGHT IT NO	201.0



### PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.

Gross weight in kg	306
Maximum floor load in N/m <sup>2</sup>	4483
Emissions data	
Emission sound pressure level in the workplace	65 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	6.48
Features	
Patented pre-spin	•
Cloth reprocessing	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Volumetric flow meter (optional)	•
Weighing plinth (optional)	•
	•
Add laundry  Programme collection via collect frame	•
Programme selection via colour frame	
Emergency switch-off	<u> </u>
Machine-independent accessories	•
Efficiency and sustainability	04
Recycling rate in %	91
Connection options	
Payment system (optional)	<u> </u>
Optical interface for service access	<u> </u>
Peak load cut-out/energy management (optional)	<u> </u>
Water recovery (optional)	<u> </u>
LAN	
WiFi	<u> </u>
Connector Box	•
Capacities	
Respirator masks [number]	10
Helmets [number]	3
Overalls [number]	2
Over jackets [number]	3
Chemical protection suits [number]	1
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Down duvets [number]	1
Down pillows [number]	2
Cloths, 22 g [number]	289
Cotton mops, 40 cm / 190 g [number]	64
Cotton mops, 50 cm / 220 g [number]	56
Microfibre mops, 40 cm / 120 g [number]	100
Microfibre mops, 50 cm / 170 g [number]	72
Mops, office, 100 g [quantity]	120
Mops, stairway, 150 g [quantity]	80
Summer horse blankets [number]	2
Tarrier trained blankets [Harrison]	_



## PWM 912 [EL DV DD SOM]

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/FC	•