

PDR 508 [EL] Professional vented dryer, Little Giants, electrically heated with extremely short programme running times. Performance 8.0 kg in 54 min.



- Drum volume 130.00 l, load size
 8.0 kg
- Tested for intensive use unparalleled Miele quality
- Language-neutral fascia panel with rotary control M Select
- Precision drying of all fabrics PerfectDry

EAN: 4002516527992 / Material number: 11945030 / Old Material Number: 52508354GB

| Construction type and version | |
|---|---------------------------------|
| Construction type | Front-loader, stackable |
| Range | Performance |
| Front | Lotus white |
| Fascia color | Stainless steel |
| Load in kg | 8.0 |
| Drum volume in I | 130.00 |
| | Exhaust air |
| Drying system Door opening [Ø] in mm | 370 |
| | |
| Door opening angle in degrees | <u>167</u> |
| Door hinge | left |
| Stainless steel honeycomb drum | Yes |
| Application | |
| Suitable for the hotel and catering industry | • |
| Suitable for retirement and care homes | • |
| Suitable for facility management | • |
| Suitable for residential homes and apartments | |
| Suitable for dry cleaners | • |
| Suitable for commercial laundries | • |
| Suitable for small businesses | • |
| Suitable for universities, nurseries, and schools | • |
| Suitable for hospitals | • |
| Suitable for camp sites | • |
| Suitable for sports clubs | • |
| Suitable for beauty salons, spas, and fitness centres | • |
| Suitable for doctors' and dentists' practices | • |
| Suitable for the petrochemicals industry | • |
| Suitable for the food-processing industry | • |
| Suitable for amusement parks & holiday complexes | • |
| Suitable for state/community care facilities | • |
| Performance data | |
| Maximum evaporation capacity in I/hour | 4.30 |
| Specific energy consumption in kWh/kg | 0.53 |
| Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW | 0.53 |
| Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture a | 0.42 |
| Programme duration in min. | 54 |
| Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes | 54 |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in | 45 |
| Control system | |
| Control system | M Select |
| Programmability | programmable |
| User interface | Residual moisture controlled |
| Max. delay start in h | 24 |
| Time left display | • |
| Programme sequence indicator | • |
| Control panel with easy-to-understand symbols | • |
| | |



PDR 508 [EL] Professional vented dryer, Little Giants, electrically heated with extremely short programme running times. Performance 8.0 kg in 54 min.



| Language can be selected easily at any time | • |
|---|---------------------|
| Standard electrical connection | |
| Heating type | Electric |
| Electrical connection | 230V~ 50/60HZ |
| Electric heater rating in kW | 5.22 |
| Total connected load in kW | 5.47 |
| Fuse rating in A | 25 |
| Dimensions and weight of dryer | |
| External dimensions, height in mm | 850 |
| External dimensions, width in mm | 596 |
| External dimensions, depth in mm | 717 |
| External dimensions, gross height in mm | 940 |
| External dimensions, gross width in mm | 660 |
| External dimensions, gross depth in mm | 820 |
| Net weight in kg | 49.0 |
| Gross weight in kg | 55 |
| Maximum floor load in N/m ² | 920 |
| Emissions data | |
| Emission sound pressure level in the workplace | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 0.76 |
| Features | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Large-surface filter | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| Low temperature function | • |
| Communication slot | • |
| Drying basket (optional) | • |
| Drum lighting | • |
| Machine-independent accessories | • |
| Efficiency and sustainability | |
| Energy efficiency class | С |
| Annual energy consumption in kWh | 581 |
| Noise in dB(a) in the Cottons Normal dry standard | 66 |
| programme with a full load | 00 |
| Duration in minutes in the standard programme | 128 |
| How it works | Vented |
| Load in kg | 8.0 |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Peak load cut-out/energy management (optional) | • |
| LAN/WiFi module (optional) | • |
| WiFiConn@ct | • |
| Standards, test certificates and symbols | |
| CE | • |
| VDE | • |
| VDE-EMC | • |
| Splash-proof safety rating IPX4 | • |
| WEEE | • |
| ¥¥∟∟∟ | |

EAN: 4002516527992 / Material number: 11945030 / Old Material Number: 52508354GB



PDR 508 [EL] Professional vented dryer, Little Giants, electrically heated with extremely short programme running times. Performance 8.0 kg in 54 min.



EAN: 4002516527992 / Material number: 11945030 / Old Material Number: 52508354GB

•

•

UKCA

Complies with Machinery Directive 2006/42/EC