

## PUR 98 D

### Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



- Timeless design – stainless steel canopy 898 mm wide
- Powerful – 650 m<sup>3</sup>/h in Booster level
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean – Miele CleanCover
- Suitable for every home – for extraction or recirculation

**A**

EAN: 4002516585794 / Material number: 12050650 / Old Material Number: 28410858GB

| <b>Construction type</b>  |                    |
|---|--------------------|
| Island cooker hood  | •                  |
| <b>Operating modes</b>  |                    |
| Type of air guide   | Can be retrofitted |
| <b>Design</b>   |                    |
| Colour  | Stainless steel    |
| <b>User convenience</b>   |                    |
| Electronic controls   | •                  |
| <b>Efficiency and sustainability</b>  |                    |
| Energy efficiency class (A+++ – D)  | A                  |
| Annual energy consumption in kWh/year                                       | 51.8               |
| Fluid dynamic efficiency class  | A                  |
| Lighting efficiency class   | A                  |
| Grease filtering efficiency class   | A                  |
| <b>Filter system</b>  |                    |
| Number of dishwasher-safe stainless steel grease filters (10-ply)           | 3                  |
| <b>Lighting</b>   |                    |
| Number x W  | 4 x 3 W            |
| Light intensity in lx   | 500 lx             |
| Colour temperature in K   | 3000 Kelvin        |
| <b>Fan</b>  |                    |
| Dual-action fan   | •                  |
| AC motor  | •                  |
| <b>Exhaust air</b>  |                    |
| Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591         | 280                |
| Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591         | 330                |
| Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591         | 400                |
| Air throughput in Booster level (m <sup>3</sup> /h) according to EN 61591   | 650                |
| Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3              | 48.0               |
| Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3              | 53.0               |
| Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3              | 57.0               |
| Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3             | 69.0               |
| Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13      | 31.0               |
| Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13      | 35.0               |
| Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13      | 39.0               |
| Sound pressure in Booster level (dB(A) re 20 µPa) acc. to EN 60704-2-13     | 51.0               |
| <b>Recirculation</b>  |                    |
| Air throughput in Level 1 (m <sup>3</sup> /h) according to EN 61591         | 190                |
| Air throughput in Level 2 (m <sup>3</sup> /h) according to EN 61591         | 270                |
| Air throughput in Level 3 (m <sup>3</sup> /h) according to EN 61591         | 330                |
| Air throughput in Booster level 1 (m <sup>3</sup> /h) according to EN 61591 | 460                |

## PUR 98 D

### Island cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516585794 / Material number: 12050650 / Old Material Number: 28410858GB

|   |      |
|---|------|
| Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3                  | 57.0 |
| Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3                  | 62.0 |
| Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3                  | 66.0 |
| Sound power in Booster level 1 (dB(A) re 1 pW) acc. to EN 60704-3               | 73.0 |
| Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13          | 40.0 |
| Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13          | 45.0 |
| Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13          | 49.0 |
| Sound pressure in Booster level 1 (dB(A) re 20 µPa) acc. to EN 60704-2-13       | 56.0 |
| <b>Safety</b>   |      |
| Safety switch-off   | •    |
| <b>Technical data</b>   |      |
| Overall height for vented and external in in. (mm)                              | 690  |
| Canopy width in mm  | 898  |
| Overall height for extraction mode and external mode cooker hoods in mm         | 990  |
| Canopy height in mm   | 70   |
| Overall height for recirculation in in. (mm)                                    | 750  |
| Canopy depth in mm  | 598  |
| Overall height for recirculation mode cooker hoods in mm                        | 1060 |
| Minimum height above electric hobs in mm  | 450  |
| Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm | 650  |
| Net weight in kg  | 34.0 |
| Length of supply lead in m  | 0.0  |
| Hard-wired connection   | •    |
| Total rated load in kW  | 0.23 |
| Voltage in V  | 230  |
| Fuse rating in A  | 10   |
| Number of phases  | 1    |
| Frequency in Hz   | 50   |
| <b>Installation notes</b>   |      |
| Extraction ducting connection at top  | •    |
| Diameter of exhaust duct in mm  | 150  |
| Telescopic chimney  | •    |
| <b>Accessories included</b>   |      |
| Non-return flap   | •    |
| <b>Optional accessories</b>   |      |
| Active charcoal filter  | Nein |