

PFD 405 [WB HygieneAir]
Freestanding fresh water dishwasher
With baskets, for all locations with high hygiene requirements.



- Max. cleaning performance\*: 456 plates/h or 24 baskets/h
- Perfect drying results thanks to DryPlus drying
- Extremely hygienic results final rinse temperature of 85 °C
- Maximum convenience with M
   Touch Flex full-touch colour display
- First-class results thanks to freshwater wash system

EAN: 4002516577027 / Material number: 12066250 / Old Material Number: 61040515GB

0	
Construction type and version	
Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Hygieneair
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised
Application	
Suitable for retirement and care homes	•
Suitable for hospitals	•
Suitable for child care facilities	•
Suitable for universities and schools	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in I/min.	390
Shortest programme duration in min.	5
Maximum final rinse temperature in °C	85
Cleaning performance, plates/h	456
Cleaning performance, plates/h with Dry+	104
Cleaning performance, baskets/h	24
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000
Miele MOVE	
Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	<u> </u>
Self-help function	•
Installation of remote updates and software updates	•
Control system	
Control system	M Touch Flex
Max. delay start in h	24
Time left display	•
Programmes [number]	12
Programme sequence indicator	<u> </u>
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	8.50
Total connected load in kW	8.90

<sup>\*</sup> Depending on site conditions (temperature of incoming water / power connection) values given may vary.



## PFD 405 [WB HygieneAir] Freestanding fresh water dishwasher With baskets, for all locations with high hygiene requirements.



EAN: 4002516577027 / Material number: 12066250 / Old Material Number: 61040515GB

Length of mains connection cable in m   1.90	Fuse rating in A	15-16
Possible voltage variant 1   Electrical connection	Length of mains connection cable in m	1.90
Electrical connection	5	
Heater rating in kW   3.00   3.40   Total connected load in kW   3.40   15-16		AC 230V 50HZ
Fuse rating in A  Water connection/drainage Cold water [number] 1 Hot water [number] 1 Required flow pressure in bar 0.40-10.00 Drain pump [DN] 22 Drain pump [DN] 22 Drain pump head height from floor level, max. in c 100 Integrated water softener • • Maximum water hardness in mmol/l 10.70 Water protection system Waterproof system Water consumption per wash cycle in I 8.00 Length of water inlet hose in cm 170 Length of water drain hose in cm 170 Length of water drain hose in cm 150  Dimensions and weight External dimensions, height in mm 820 External dimensions, height in mm 598 External dimensions, net width in mm 598 External dimensions, gross width in mm 920 External dimensions, gross width in mm 920 External dimensions, gross width in mm 559 External dimensions, gross width in mm 740 Usable space in wash cabinet, height in mm 536 Usable space in wash cabinet, depth of upper baske 474 Usable space in wash cabinet, depth of lower basket in mm 516 In-feed height above floor in mm 600 Net weight [kg] 78 Gross weight in kg 88 Maximum floor load in N/m² 1200  Emissions data  Emissions – sound pressure at workplace 47 dB(A) re 20 μPa Sound power (LwA) in dB(A) re 1 pW 59.0 Heat dissipation into the room in MJ/h 1.44  Programmes Universal • • • • • • • • • • • • • • • • • • •	Heater rating in kW	
Fuse rating in A  Water connection/drainage Cold water [number] 1 Hot water [number] 1 Required flow pressure in bar 0.40-10.00 Drain pump [DN] 22 Drain pump [DN] 22 Drain pump head height from floor level, max. in c 100 Integrated water softener • • Maximum water hardness in mmol/l 10.70 Water protection system Waterproof system Water consumption per wash cycle in I 8.00 Length of water inlet hose in cm 170 Length of water drain hose in cm 170 Length of water drain hose in cm 150  Dimensions and weight External dimensions, height in mm 820 External dimensions, height in mm 598 External dimensions, net width in mm 598 External dimensions, gross width in mm 920 External dimensions, gross width in mm 920 External dimensions, gross width in mm 559 External dimensions, gross width in mm 740 Usable space in wash cabinet, height in mm 536 Usable space in wash cabinet, depth of upper baske 474 Usable space in wash cabinet, depth of lower basket in mm 516 In-feed height above floor in mm 600 Net weight [kg] 78 Gross weight in kg 88 Maximum floor load in N/m² 1200  Emissions data  Emissions – sound pressure at workplace 47 dB(A) re 20 μPa Sound power (LwA) in dB(A) re 1 pW 59.0 Heat dissipation into the room in MJ/h 1.44  Programmes Universal • • • • • • • • • • • • • • • • • • •	Total connected load in kW	3.40
Water connection/drainage       1         Cold water [number]       1         Hed water [number]       1         Required flow pressure in bar       0.40-10.00         Drain pump (DN)       22         Drain pump head height from floor level, max. in c       100         Integrated water softener       •         Maximum water hardness in mmol/l       10.70         Water protection system       Waterproof system         Water consumption per wash cycle in I       8.00         Length of water drain hose in cm       170         Length of water drain hose in cm       150         Dimensions and weight         External dimensions, height in mm       820         External dimensions, set dipth in mm       598         External dimensions, net width in mm       598         External dimensions, gross height in mm       920         External dimensions, gross width in mm       670         External dimensions, gross depth in mm       740         Usable space in wash cabinet, keight in mm       559         Usable space in wash cabinet, width in mm       569         Usable space in wash cabinet, depth of lower basket in mm       16         In-feed height above floor in mm       216         Required niche		
Cold water [number]		
Hot water [number]	-	1
Required flow pressure in bar Drain pump [DN] Drain pump [DN] Drain pump head height from floor level, max. in c Integrated water softener Maximum water hardness in mmol/l Water protection system Water protection system Water consumption per wash cycle in l Length of water drain hose in cm Length of water drain hose in cm IT00 Length of water drain hose in cm It00 Dimensions and weight External dimensions, height in mm External dimensions, net width in mm External dimensions, net width in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions with lid, height in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions with cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm External dimensions date Emissions – sound pressure at workplace Emissions – sound pressure at workplace Emissions data Emissions – sound pressure at workplace Emissions data Emissions – sound pressure at workplace Sound power (LwA) in dB(A) re 1 pW Sound power (LwA) in dB(A) re 20 μPa Sound power (LwA) in dB(A) re 1 pW Sound p		1
Drain pump [DN]         22           Drain pump head height from floor level, max. in c         100           Integrated water softener         •           Maximum water hardness in mmol/l         10.70           Water protection system         Waterproof system           Water consumption per wash cycle in l         8.00           Length of water inlet hose in cm         170           Length of water drain hose in cm         150           Dimensions and weight         820           External dimensions, height in mm         820           External dimensions, height in mm         835           External dimensions, et width in mm         598           External dimensions, gross height in mm         598           External dimensions, gross height in mm         920           External dimensions, gross width in mm         740           Usable space in wash cabinet, height in mm         559           Usable space in wash cabinet, width in mm         536           Usable space in wash cabinet, depth of lower basket in mm         516           In-feed height above floor in mm         216           Required niche width in mm         600           Net weight [kg]         78           Gross weight in kg         88           Maximum floor load		0.40-10.00
Drain pump head height from floor level, max. in c       100         Integrated water softener       •         Maximum water hardness in mmol/l       10.70         Water protection system       Waterproof system         Water consumption per wash cycle in I       8.00         Length of water inlet hose in cm       170         Length of water drain hose in cm       150         Dimensions and weight       820         External dimensions, height in mm       835         External dimensions with lid, height in mm       598         External dimensions, net width in mm       598         External dimensions, gross height in mm       920         External dimensions, gross depth in mm       670         External dimensions, gross depth in mm       740         Usable space in wash cabinet, height in mm       559         Usable space in wash cabinet, width in mm       559         Usable space in wash cabinet, depth of upper baske       474         Usable space in wash cabinet, depth of lower basket in mm       516         In-feed height above floor in mm       600         Net weight [kg]       78         Gross weight in kg       88         Maximum floor load in N/m²       1200         Emissions – sound pressure at workplace <t< td=""><td></td><td></td></t<>		
Integrated water softener  Maximum water hardness in mmol/l  Water protection system  Water consumption per wash cycle in l Length of water drain hose in cm  Length of water drain hose in cm  Integrated dimensions, height in mm  External dimensions, height in mm  External dimensions, net width in mm  External dimensions, net depth in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross depth in mm  559  Usable space in wash cabinet, height in mm  536  Usable space in wash cabinet, depth of upper baske  Usable space in wash cabinet, depth of lower basket in mm  Infeed height above floor in mm  600  Net weight [kg]  78  Gross weight in kg  Maximum floor load in N/m²  Emissions – sound pressure at workplace  Emissions – sound pressure at workplace  Sound power (LwA) in dB(A) re 1 pW  59.0  Heat dissipation into the room in MJ/h  Programmes  Universal  Universal  Super short  Short  - Hygiene  Hygiene plus  Cold/Pre-wash  Glasses  Beer glasses  - Cutlery  •		100
Maximum water hardness in mmol/I       10.70         Water protection system       Waterproof system         Water consumption per wash cycle in I       8.00         Length of water inlet hose in cm       170         Length of water drain hose in cm       150         Dimensions and weight       ***         External dimensions, height in mm       820         External dimensions with lid, height in mm       835         External dimensions, et width in mm       598         External dimensions, gross height in mm       920         External dimensions, gross width in mm       670         External dimensions, gross depth in mm       740         Usable space in wash cabinet, height in mm       559         Usable space in wash cabinet, width in mm       536         Usable space in wash cabinet, depth of lower basket in mm       516         In-feed height above floor in mm       216         Required niche width in mm       600         Net weight [kg]       78         Gross weight in kg       88         Maximum floor load in N/m²       1200         Emissions – sound pressure at workplace       47 dB(A) re 20 μPa         Sound power (LwA) in dB(A) re 1 pW       59.0         Heat dissipation into the room in MJ/h       1.44 <td></td> <td>•</td>		•
Water consumption per wash cycle in I Length of water inlet hose in cm Length of water drain hose in cm Length of water drain hose in cm Inspect of the water drain hose in cm External dimensions, height in mm External dimensions with lid, height in mm External dimensions with lid, height in mm External dimensions, net width in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm		10.70
Water consumption per wash cycle in I Length of water inlet hose in cm Length of water drain hose in cm Length of water drain hose in cm Inspect of the water drain hose in cm External dimensions, height in mm External dimensions with lid, height in mm External dimensions with lid, height in mm External dimensions, net width in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm	Water protection system	Waterproof system
Length of water inlet hose in cm     170       Length of water drain hose in cm     150       Dimensions and weight     820       External dimensions, height in mm     835       External dimensions, net width in mm     598       External dimensions, net depth in mm     598       External dimensions, gross height in mm     920       External dimensions, gross width in mm     670       External dimensions, gross depth in mm     740       Usable space in wash cabinet, height in mm     559       Usable space in wash cabinet, width in mm     536       Usable space in wash cabinet, depth of lower basket in mm     516       In-feed height above floor in mm     216       Required niche width in mm     600       Net weight [kg]     78       Gross weight in kg     88       Maximum floor load in N/m²     1200       Emissions data     1200       Emissions data     47 dB(A) re 20 μPa       Sound power (LwA) in dB(A) re 1 pW     59.0       Heat dissipation into the room in MJ/h     1.44       Programmes     1.44       Universal     •       Short     •       Hygiene     •       Hygiene plus     •       Coll/Pre-wash     •       Glasses     •       Cuttery </td <td></td> <td></td>		
Length of water drain hose in cm  Dimensions and weight  External dimensions, height in mm  External dimensions with lid, height in mm  External dimensions, net width in mm  External dimensions, net depth in mm  External dimensions, pross height in mm  External dimensions, gross height in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross depth in mm  External dimensions, gross width in mm  External dimensions, gross depth in mm  External dimensions, gross width in mm  External dimensions, gross widt		
Dimensions and weight       External dimensions, height in mm       820         External dimensions with lid, height in mm       835         External dimensions, net width in mm       598         External dimensions, gross height in mm       598         External dimensions, gross height in mm       598         External dimensions, gross height in mm       670         External dimensions, gross depth in mm       740         Usable space in wash cabinet, height in mm       559         Usable space in wash cabinet, width in mm       536         Usable space in wash cabinet, depth of upper baske       474         Usable space in wash cabinet, depth of lower basket in mm       516         In-feed height above floor in mm       216         Required niche width in mm       600         Net weight [kg]       78         Gross weight in kg       88         Maximum floor load in N/m²       1200         Emissions data       1200         Emissions Journal pressure at workplace       47 dB(A) re 20 μPa         Sound power (LwA) in dB(A) re 1 pW       59.0         Heat dissipation into the room in MJ/h       1.44         Programmes       1         Universal       •         Super short       •		
External dimensions, height in mm External dimensions with lid, height in mm External dimensions, net width in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross weight in mm External dimensions, gross weig	-	
External dimensions with lid, height in mm  External dimensions, net width in mm  External dimensions, net depth in mm  External dimensions, gross height in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross depth in mm  External dimensions, gross depth in mm  External dimensions, gross depth in mm  External dimensions, gross width in mm  Exte	-	820
External dimensions, net width in mm  External dimensions, net depth in mm  External dimensions, gross height in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross depth in mm  External dimensions, gross width in mm  External dimensions, gross height in mm  External dimensions, gross height in mm  External dimensions, gross height in mm  External dimensions, gross width in mm  External dimensions, gross defer in mm  External dimensions, gross width in mm  External dimensions, gross width in mm  External dimensions, gross defer in mm  Exter		
External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm T40 Usable space in wash cabinet, height in mm Usable space in wash cabinet, width in mm S36 Usable space in wash cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm Equired niche width in mm Equired niche width in mm Equired niche width in kg Emissions data Emissions data Emissions – sound pressure at workplace Emissions – sound pressure at workplace Sound power (LwA) in dB(A) re 1 pW Engrammes Universal Universal Universal Universal Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Eeer glasses Cuttery	, 0	
External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm T40 Usable space in wash cabinet, height in mm Usable space in wash cabinet, width in mm Usable space in wash cabinet, width in mm Usable space in wash cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm Required niche width in mm Sab Required niche width in		
External dimensions, gross width in mm External dimensions, gross depth in mm 740 Usable space in wash cabinet, height in mm 559 Usable space in wash cabinet, width in mm 536 Usable space in wash cabinet, depth of upper baske 474 Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm 816 Required niche width in mm 800 Net weight [kg] 78 Gross weight in kg 88 Maximum floor load in N/m² 1200 Emissions data Emissions – sound pressure at workplace Sound power (LwA) in dB(A) re 1 pW 59.0 Heat dissipation into the room in MJ/h 1.44 Programmes Universal Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cuttlery  •	·	
External dimensions, gross depth in mm  Usable space in wash cabinet, height in mm  Usable space in wash cabinet, width in mm  Usable space in wash cabinet, width in mm  Usable space in wash cabinet, depth of upper baske  Usable space in wash cabinet, depth of lower basket in mm  In-feed height above floor in mm  Required niche width in		
Usable space in wash cabinet, height in mm Usable space in wash cabinet, width in mm Usable space in wash cabinet, width in mm Usable space in wash cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm Required niche width in mm 600 Net weight [kg] 78 Gross weight in kg 88 Maximum floor load in N/m² 1200 Emissions data Emissions – sound pressure at workplace Sound power (LwA) in dB(A) re 1 pW 59.0 Heat dissipation into the room in MJ/h 1.44 Programmes Universal Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cuttlery •		
Usable space in wash cabinet, width in mm Usable space in wash cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm Required niche width in kg Required niche width in k		
Usable space in wash cabinet, depth of upper baske Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm 216 Required niche width in mm 600 Net weight [kg] 78 Gross weight in kg 88 Maximum floor load in N/m² 1200 Emissions data Emissions – sound pressure at workplace Sound power (LwA) in dB(A) re 1 pW 59.0 Heat dissipation into the room in MJ/h 1.44 Programmes Universal Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cutlery		
Usable space in wash cabinet, depth of lower basket in mm In-feed height above floor in mm Required niche width in mm Required ni		
In-feed height above floor in mm  Required niche width in mm  Net weight [kg]  Gross weight in kg  Maximum floor load in N/m²  Emissions data  Emissions – sound pressure at workplace  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in MJ/h  Programmes  Universal  Super short  Short  Hygiene  Hygiene plus  Cold/Pre-wash  Glasses  Beer glasses  Cutlery  28  600  78  88  88  47  78  89  89  89  80  80  80  80  80  80  8		
Required niche width in mm       600         Net weight [kg]       78         Gross weight in kg       88         Maximum floor load in N/m²       1200         Emissions data       1200         Emissions – sound pressure at workplace       47 dB(A) re 20 μPa         Sound power (LwA) in dB(A) re 1 pW       59.0         Heat dissipation into the room in MJ/h       1.44         Programmes       •         Universal       •         Super short       •         Short       •         Hygiene plus       •         Cold/Pre-wash       •         Glasses       •         Beer glasses       •         Cutlery       •	<del></del>	
Net weight [kg]       78         Gross weight in kg       88         Maximum floor load in N/m²       1200         Emissions data       1200         Emissions – sound pressure at workplace       47 dB(A) re 20 μPa         Sound power (LwA) in dB(A) re 1 pW       59.0         Heat dissipation into the room in MJ/h       1.44         Programmes       Universal         Super short       •         Short       •         Hygiene       •         Hygiene plus       •         Cold/Pre-wash       •         Glasses       •         Beer glasses       •         Cutlery       •		
Gross weight in kg       88         Maximum floor load in N/m²       1200         Emissions data       1200         Emissions – sound pressure at workplace       47 dB(A) re 20 μPa         Sound power (LwA) in dB(A) re 1 pW       59.0         Heat dissipation into the room in MJ/h       1.44         Programmes       Universal         Super short       •         Short       •         Hygiene       •         Hygiene plus       •         Cold/Pre-wash       •         Glasses       •         Beer glasses       •         Cutlery       •		
Maximum floor load in N/m²  Emissions data  Emissions – sound pressure at workplace 47 dB(A) re 20 μPa  Sound power (LwA) in dB(A) re 1 pW 59.0  Heat dissipation into the room in MJ/h 1.44  Programmes  Universal Super short Short Hygiene Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cutlery		
Emissions data  Emissions – sound pressure at workplace 47 dB(A) re 20 µPa  Sound power (LwA) in dB(A) re 1 pW 59.0  Heat dissipation into the room in MJ/h 1.44  Programmes  Universal • Super short • Short • Hygiene • Hygiene plus  Cold/Pre-wash Glasses • Beer glasses  Cutlery •		
Emissions – sound pressure at workplace  Sound power (LwA) in dB(A) re 1 pW  Heat dissipation into the room in MJ/h  Programmes  Universal  Super short  Short  Hygiene  Hygiene plus  Cold/Pre-wash  Glasses  Beer glasses  Cutlery  47 dB(A) re 20 µPa  59.0  1.44  Programmes  •  0  1.44  •  -  -  -  -  -  -  -  -  -  -  -  -		.250
Sound power (LwA) in dB(A) re 1 pW         59.0           Heat dissipation into the room in MJ/h         1.44           Programmes         •           Universal         •           Super short         •           Short         •           Hygiene         •           Hygiene plus         •           Cold/Pre-wash         •           Glasses         •           Beer glasses         •           Cutlery         •		47 dB(A) re 20 uPa
Heat dissipation into the room in MJ/h  Programmes  Universal  Super short  Short  Hygiene  Hygiene plus  Cold/Pre-wash  Glasses  Beer glasses  Cutlery  1.44  1.4		
Programmes Universal Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cutlery  •  Universal •  Super short •  -  -  -  -  -  -  -  -  -  -  -  -		
Universal Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cutlery  •		
Super short Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cutlery  •  Cold Cold Cold Cold Cold Cold Cold Cold		•
Short Hygiene Hygiene plus Cold/Pre-wash Glasses Beer glasses Cutlery  •  Cutlery •  -  -  -  -  -  -  -  -  -  -  -  -		
Hygiene Hygiene plus  Cold/Pre-wash Glasses Beer glasses Cutlery  •  Cutlery		
Hygiene plus  Cold/Pre-wash  Glasses  Beer glasses  Cutlery  •		
Cold/Pre-wash Glasses Beer glasses Cutlery  •		
Glasses Beer glasses Cutlery  •		- <u>-</u>
Beer glasses Cutlery  •		
Cutlery •		
1 1001100		
	1 Idotioo	·



## PFD 405 [WB HygieneAir] Freestanding fresh water dishwasher With baskets, for all locations with high hygiene requirements.



EAN: 4002516577027 / Material number: 12066250 / Old Material Number: 61040515GB

Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
1 x APFD 215 upper basket	•
1 x APFD 220 lower basket for inserts	•
2 x APFD 420 insert for cutlery	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•
Features	
Drying	AutoOpen assisted drying, Dry+ drying
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
AutoClose	•
Perfect GlassCare	•
Door lock, protected by code	•
Adjustable temperature holding time	•
Drying time can be altered	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, test certificates and symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•