

H 2861 B Oven

in a mix and match design with networking, PerfectClean and FlexiClip runners.



- Clear text display with rotary controls – EasyControl Plus
- Particularly easy to clean PerfectClean finish
- Network-enabled WiFi appliance Miele@home
- Achieve perfect results with ease automatic programmes



EAN: 4002516642565 / Material number: 12143950 / Old Material Number: 22286144GB

| Construction type and design | |
|---|-----------------------------|
| Built-in oven | • |
| PureLine | • |
| Appliance Colour | Stainless steel/Clean Steel |
| Convenience features | |
| Rapid heat-up | • |
| Operating modes | |
| AirFry | • |
| Automatic programmes | • |
| Eco fan heat | • |
| Grill operating modes | • |
| Grill | • |
| Fan plus | • |
| Intensive bake | • |
| Conventional heat | • |
| Bottom heat | • |
| Fan grill | • |
| User convenience | |
| Networking with Miele@home | • |
| Display | EasyControl Plus |
| SoftOpen | • |
| SoftClose | • |
| MultiLingua | • |
| Time of day display | • |
| Minute minder | • |
| Programmable start of cooking duration | • |
| Programmable end of cooking duration | • |
| Programmable cooking duration | • |
| Actual temperature display | • |
| Target temperature display | • |
| Buzzer when desired temperature is reached | • |
| Recommended temperature | • |
| Individual settings | • |
| Efficiency and sustainability | |
| Energy efficiency class (A+++ - D) | A+ |
| Power rating in off mode in W | 0.5 |
| Power rating in standby mode in W | 1.0 |
| Power rating in networked standby in W | 2.0 |
| Time until automatic switch to standby in min | 20 |
| Time until automatic switch to networked standby in min | 20 |
| Time until automatic switch to off mode in min | 20 |
| Cleaning and care | |
| Stainless steel/CleanSteel finish | • |
| Oven compartment with PerfectClean and catalytically enamelled liners | • |
| CleanGlass door | • |
| Safety | |
| Appliance cooling system and touch-cool front | • |
| Safety switch-off | • |
| System lock | • |



H 2861 B Oven in a mix and match design with networking, PerfectClean and FlexiClip runners.




EAN: 4002516642565 / Material number: 12143950 / Old Material Number: 22286144GB

| Technical data | |
|--|----------------|
| Oven compartment volume in I | 76 |
| No. of shelf levels | 5 |
| Number of shelf levels oven compartment 1 | 5 |
| Number of shelf levels oven compartment 2 | 5 |
| Numbered shelf levels | • |
| Oven light | 1 halogen spot |
| Temperatures in °C | 30–300 |
| Electronic temperature regulation min. in °C | 30 |
| Electronic temperature regulation max. in °C | 300 |
| Niche width min. in mm | 560 |
| Niche width max. in mm | 568 |
| Niche height min. in mm | 590 |
| Niche height max. in mm | 595 |
| Niche depth in mm | 550 |
| Appliance width in mm | 595 |
| Appliance height in mm | 596 |
| Appliance depth in mm | 569 |
| Weight in kg | 42.0 |
| Total rated load in kW | 3.50 |
| Voltage in V | 220-240 |
| Frequency in Hz | 50 |
| Fuse rating in A | 16 |
| Number of phases | 1 |
| Length of supply lead in m | 1.50 |
| Replacing lamps | Customer |
| Accessories included | |
| Baking tray with PerfectClean | 1 |
| Universal tray with PerfectClean | 1 |
| Baking and roasting rack without PerfectClean | 1 |
| FlexiClip runners with PerfectClean | 1 |
| Removable side runners (pair) | 1 |
| Grilling and roasting insert with PerfectClean | 1 |

Míele


H 2861 B Oven

in a mix and match design with networking, PerfectClean and FlexiClip runners.




installation H7000 XL, installation drawing, GB, AU

1) Netzanschlussleitung, L=1500 mm, 2) In diesem Bereich kein Anschluss, 3) Lüftungsausschnitt min. 150 cm²




side view H7000 XL, installation drawings, GB, AU

22 mm - glass, 23.3 mm - metal




built-in H7000 XL, installation drawing






H226x-1B/BP/E/EP/I/IP, H2x6xB/BP, H7x6xB/BP/BPX, installation drawings

If the oven is to be installed under a hob, follow the instructions for installing the hob and the height of the hob.



DG2840, DG7x40, DGC7x4x, DG7x6x, DGC7x6x, DGD7635, DGM7x4x, DO7, H28B/BP, H7x4xB/BM/BP, H7x6xB/BP, installation drawing

1) 400 mm, 2) 360 mm, 3) 47 mm, 4) 24 mm, 5) 32.5 mm



side view H7000 XL build-under, installation drawing, GB, AU

22 mm - glass, 23.3 mm - metal