

PLW 7111 [Safety S-1011]

Washer-disinfector for the reprocessing of breathing apparatus

- SlimLine, electric heating, drying, drain pump and condenser.





- Performance/cycle 8 breathing masks and 8 air regulators
- Alternative performance/cycle 2 compressed air bottles
- Alternative performance/cycle 2 compressed air unit carrier frames
- Flexible for loading with a usable capacity of 241 I litres
- Intuitive operation and programmable controls
- High-performance system and specific programmes

Construction type and version	
Construction type	Freestanding, 1 glazed
	hinged door
Type of heating	Electricity
Front/back	Stainless Steel
Side panels	Stainless steel
Single/multiple installations	•
Slimline construction type	•
Number of wash levels	2
Loading and unloading with telescopic runners	•
Electric door lock	•
Buzzer, acoustic signal at end of programme	•
Service-friendly design	•
Application	
Suitable for fire brigades and rescue services	•
Capacity	
Breathing masks [number]	16
Compressed air bottles [number]	2
Compressed air unit carrier frames with compressed air bottle [number]	1
Compressed air unit carrier frames [number]	2
Performance data	
Circulation pump, Qmax in I/min	750
Wash cabinet usable capacity in I	241
Control system	
Control type	TouchControl
Programme selection	Full-touch colour display
Programmability	Freely programmable
Programmes [number]	5
Free programme positions [number]	20
Automatic programme restart	•
Programme sequence display	•
Selectable display languages	•
Standard electrical connection	
Electrical connection	3N AC 380-415V 50HZ
Heater rating in kW	8.40
Total rated load in kW	10.10
Fuse rating in A	16
Length of mains connection cable in m	4.00
Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
DI water [number]	1
Required flow pressure in kPa	100-600
Maximum water hardness (cold water/hot water) in mmol/l	0.70
Drain pump [DN]	25
Drain valve [DN]	38
Water protection system	Waterproof system
Drying unit	
Di ying dine	



PLW 7111 [Safety S-1011]

Washer-disinfector for the reprocessing of breathing apparatus

- SlimLine, electric heating, drying, drain pump and condenser.



EAN: 4002516669326 / Material number: 12278760 / Old Material Number: 62711134GB

Air throughput in m ³ /h	130
Time setting in 1-minute increments	0-60
HEPA filter class	H14
HEPA filter filtration efficiency (DIN EN 1822) in %	99.99
Electric heater rating in kW	4.00
Dimensions and weight	
External dimensions, net height in mm	702
External dimensions, net width in mm	650
External dimensions, net depth in mm	1965
External dimensions, gross height in mm	2110
External dimensions, gross width in mm	945
External dimensions, gross depth in mm	840
Wash cabinet, height in mm	717
Wash cabinet, width in mm	570
Wash cabinet, depth in mm	590
Rack height above floor in mm	850
Net weight in kg	251
Gross weight in kg	260
Maximum floor load in N/m ²	680
Emissions data	
Sound pressure LpA in cleaning and drying according to	68 dB(A) re 20 µPa
DIN EN ISO 11201	31 31 4 7 1 3 1 pr
Heat dissipation into the room in MJ/h	0.80
Programmes	
Breathing apparatus	•
Vario FB Special	•
Vario FB Special Vario FB Special Plus	•
·	- -
Vario FB Special Plus	•
Vario FB Special Plus Vario FB Chem	•
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus	•
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB	•
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features	•
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media	•
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps	• • • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional)	• • • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control	• • • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l)	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished SlimLine mobile plinth	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished SlimLine mobile plinth Variable-speed pump	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished SlimLine mobile plinth Variable-speed pump Multi-coloured chamber lighting	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished SlimLine mobile plinth Variable-speed pump Multi-coloured chamber lighting Modular basket design	• • • • • • • • • • • • • • • • • • •
Vario FB Special Plus Vario FB Chem Vario FB Chem Plus Drying FB Features 2 integrated diaphragm dispenser pumps for liquid media Additional integrated dispenser pumps Steam condenser (optional) Volume flow control Interface for process documentation Multi-component filter system Load carrier – direct coupling Integrated hot air drying Miele Cloud Service Setting options for process chemicals (3 x 5 l) Wash cabinet made of high-quality stainless steel (1.4404/316L), electropolished SlimLine mobile plinth Variable-speed pump Multi-coloured chamber lighting Modular basket design Connection options	• • • • • • • • • • • • • • • • • • •



PLW 7111 [Safety S-1011]

Washer-disinfector for the reprocessing of breathing apparatus

- SlimLine, electric heating, drying, drain pump and condenser.





Standards, test certificates and symbols	
CE	•
EN 61010-1	•
EN 61010-2-040	•
RoHS guideline 2011/65/EU	•
Machinery Directive 2006/42/EC	•