

G 7380 SCVi FF Fully integrated dishwasher XXL for perfect gaps and joints in the kitchen thanks to FrontFit



- Innovative design and maximum convenience – 3D MultiFlex Tray
- Versatile and secure ExtraComfort basket design
- Everything completely dry AutoOpen drying
- Fresh water dishwashers from ?? litres in the Automatic programme d
- Very easy door opening and closing – ComfortClose



Fully integrated dishwasher 60 cm dishwasher Control panel colour Stainless Steel. Control panel version Fully integrated fascia Control type Programme selector button Display 1-line text display Display colour White MultiLingua Convenience ComfortClose Door closing aid Time left display Delay start up to 24 hours In-operation indicator light optical and acoustic Display language selection Efficiency and sustainability Energy efficiency class (A-G) Water consumption in the Automatic programme in I from 6.0 Water consumption of the ECO programme in litres per 8.4 programme cycle Electricity consumption in the ECO programme in kWh 0.54 Energy consumption of the ECO programme in kWh after 54 100 programme cycles Consumption value in kWh in the ECO programme with hot 0.29 water connection Duration of ECO programme in minutes 230 Noise emission class В Noise emissions in dB(A) 43 EcoFeedback EcoPower Technology Proven hygiene Hot water connection Half load Quality of results Fresh water dishwasher SensorDry Recirculation Turbothermic drying Active condensation drying BrilliantGlassCare Wash programmes QuickPowerWash ECO Automatic Intensive 75 °C PowerWash Gentle

EAN: 4002516738404 / Material number: 12423920 / Old Material Number: 21738062GB

ExtraQuiet 40 dB(A)
Appliance care
Dishwashing options

Express



G 7380 SCVi FF Fully integrated dishwasher XXL for perfect gaps and joints in the kitchen thanks to FrontFit



EAN: 4002516738404 / Material number: 12423920 / Old Material Number: 21738062GB

Extra dry Basket design Cutlery loading	3D MultiFlex tray
	3D MultiFlex tray
Cutlery loading	3D MultiFlex tray
FlexCare glass holder	2
FlexCare cup rack	1
Basket design	ExtraComfort
Number of place settings	14
Safety	
Waterproof system	•
Filter indicator light	•
Safety lock	•
Technical data	
Niche width minimal in mm	600
Niche width max in mm	600
Niche height minimal in mm	805
Niche height maximal in mm	870
Niche depth in mm	550
Appliance width in mm	598
Appliance height in mm	805
Appliance depth in mm	550
Depth with door open in cm	116.5
Net weight in kg	48.0
Total rated load in kW	2.00
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Electrical frequency standard	50
Length of water inlet hose in m	1.50
Length of water drain hose in m	1.50
Length of supply lead in m	1.80
Min. front panel weight in kg	4.0
Max. front panel weight in kg	10.0
[can be retrofitted by Service to min.]	8.0
[can be retrofitted by Service to max.]	16.0
Available display languages	
Available display languages via MultiLingua	bahasa malaysia, deutsch, english (AU), english (GB),
Accessories included	· · · · · · · · · · · · · · · · · · ·