

ProCare Tex 10 B+ - 20 I Booster, liquid concentrate, neutral, 20 I for effective removal of grease stains.



- For use in Miele Professional washing machines
- Gentle degreaser for any type of laundry
- Particularly gentle on fabrics and colours
- Full washing power even at 30 °C
- Can also be used as an emulsifier and wetting agent

EAN: 4002516776208 / Material number: 12495150 / Old Material Number: 59709301V1

Dreduct actorian	
Product category	
Washing machines	•
Wash performance	
Dirt dissolving power	Very good
Protein dissolving power	Very good
Grease dissolving power	Very good
Degree of whiteness	Very good
Dispensing	
Suitable for automatic dispensing	•
Manual dispensing	•
Can be used with all degrees of water hardness	•
Dispensing recommendation	
pH value at 20 °C	7,5
How to use	
Launderettes	•
Hotels, catering	•
Cleaning sportswear	•
Cleaning outerwear	•
Cleaning workwear	•
Product properties	
Minimum storage temperature in °C	0
Maximum storage temperature in °C	40
Dimensions and weight	
External dimensions, gross depth in mm	288.00
Product properties	
Medium type	Booster
Alkalinity	pH-neutral
Aggregate form	Liquid concentrate
Composition	Surfactants
Biodegradable	•
Phosphate-free	•
Effective at temperatures from 30–90 °C	•
Particularly effective at low temperatures	•
Highly effective, even at 40 °C	•
Short activation time	•
Foam sensing	•
High-level detergency combined with sparing use	•
Density (at 20 °C) in g/cm ³	1.00
Free from micro-plastics	
Simple handling	•
Ideal additive for all detergents	
-	-
Storage information	0
Minimum storage temperature in °C	0
Maximum storage temperature in °C	40
Store in a dry location that is free of frost	•
Containers should always be re-sealed immediately once	•
the required amount of product has been removed	
	• 36



ProCare Tex 10 B+ - 20 I Booster, liquid concentrate, neutral, 20 I for effective removal of grease stains.



EAN: 4002516776208 / Material number: 12495150 / Old Material Number: 59709301V1

Dimensions and weight	
External dimensions, net height in mm	385
External dimensions, net width in mm	258
External dimensions, net depth in mm	294
Compliance, test certificates, and symbols	
GHS/CLP compliant	•

GHS/CLP compliant