

WWB360 WCS PWash&8kg W1 front-loader washing machine:

A -20 %* I 8 kg I 1400 rpm I QuickPowerWash I Miele@home I CapDosing



- Tested for 20 years of perfect laundry care
- Save even more energy with A -20 %*
- QuickPowerWash ensures fast, efficient results in just 49 minutes
- Complete app control of your washing machine with Miele@ home
- ExclusiveCapDosing range for different textiles and stains
- ^{*} 20 % more economical than the threshold value (52) for energy efficiency class A.
- "Additional digital offer from Miele & Cie. KG. All smart applications are made possible with the Miele@home system. The range of functions can vary depending on the model and the country.



EAN: 4002516867371 / Material number: 12721170 / Old Material Number: 11WB3601GB

Construction type	
Suitable for stacking	
Side-by-side	•
Slot-in	
Door hinge	right
Model	
Product brand	W1 White Edition
Front-loader	•
Spinning	
Max. spin speed	1400
Rinse hold	
Without spin function	•
Design	
Appliance colour	Lotus white
Control panel colour	Lotus white
Door design	Obsidian black with white
Detay coloctor colour	ring
Rotary selector colour	Lotus White 5° inclined
Control panel version	
Control type	Rotary control
Display	DirectSensor white, 7 segment
Cleaning performance	7 segment
Innovative PowerWash technology	•
CapDosing portioned dispensing	-
Gentle laundry care	
Honeycomb drum	•
Load in kg	8.0
User convenience	6.0
Networking with Miele@home	•
Delay start up to 24 hours	•
Time left display	•
AutoClean detergent drawer	•
AddLoad	•
Efficiency and sustainability	
Energy efficiency class (A-G)	A
More economical than the threshold value (52) for energy	20%
efficiency class A	
Weighted energy consumption per 100 operating cycles for	38
the wash cycle in kWh	
Weighted water consumption per cycle in I	48
Spin efficiency class	В
Acoustic airborne noise emission class (spin cycle)	Α
Sound emissions during spin cycle in dB(A) re 1 pW	72
Duration of the "ECO 40–60" programme at nominal capacity	219
Power rating in off mode in W	0.30
Power rating in networked standby in W	0.60
Low temperature wash "Cold" and "20 °C"	•
Automatic load control	•
Flow meter	•
	-



WWB360 WCS PWash&8kg W1 front-loader washing machine:

A -20 %* I 8 kg I 1400 rpm I QuickPowerWash I Miele@home I CapDosing



EAN: 4002516867371 / Material number: 12721170 / Old Material Number: 11WB3601GB


ProfiEco motor Wash programmes QuickPowerWash Cottons (coloureds) Minimum iron Delicates Shirts Woollens (hand-washable) Express 20 Dark garments / Denim Proofing Proofing Proofing Proofing Figure 1 EXPRESS 20 Bark garments / Denim Proofing Proofing Proofing Proofing Pround EXPRESS 20 Bark garments / Denim Proofing Proofing Proofing Proofing Pround EXPRESS 20 Bark garments / Denim Proofing Proofing Proofing Proofing Pre-wash Pre-wash Pre-wash Pre-wash Pre-wash Pre-ironing with steam Pageor Bafety Water protection system Water protection system Safety lock PIN-Code Optical interface Pre-ironical data Dimensions in mm (width) Dimensions in mm (width) Dimensions in mm (height) Baso Dimensions in mm (depth) Appliance depth in mm with opened door Potal rated load in kW Potal rating in A Prequency in Hz Prequency in	Foam sensing	•
QuickPowerWash • Cottons (coloureds) • Minimum iron • Delicates • Shirts • Woollens (hand-washable) • Express 20 • Dark garments / Denim • Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water protection system Safety lock • PIN-Code • Optical interface • Technical data • Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated l	ProfiEco motor	•
Cottons (coloureds) • Minimum iron • Delicates • Shirts • Woollens (hand-washable) • Express 20 • Dark garments / Denim • Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety • Water protection system Watercontrol-System Safety lock • PIN-Code • Optical interface • Technical data • Dimensions in mm (width) 596 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Volta	Wash programmes	
Minimum iron • Delicates • Shirts • Woollens (hand-washable) • Express 20 • Dark garments / Denim • Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water protection system Water protection system Watercontrol-System Safety lock • PIN-Code • Optical interface • Technical data - Dimensions in mm (width) 596 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 <	QuickPowerWash	•
Delicates	Cottons (coloureds)	•
Shirts • Woollens (hand-washable) • Express 20 • Dark garments / Denim • Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water control-System Safety lock • PIN-Code • Optical interface • Technical data • Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Minimum iron	•
Woollens (hand-washable) • Express 20 • Dark garments / Denim • Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water control-System Safety lock • PIN-Code • Optical interface • Technical data * Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Delicates	•
Express 20 Dark garments / Denim Proofing Drain / Spin ECO 40-60 Washing extras Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V ECO 40-60 • Optical interface • PIN-Code • Optical interface Technical data Dimensions in mm (height) Baso Baso Total rated load in kW Voltage in V PIN-Code	Shirts	•
Dark garments / Denim • Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water control-System Safety lock • PIN-Code • Optical interface • Technical data - Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A	Woollens (hand-washable)	•
Proofing • Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water protection system Water protection system Watercontrol-System Safety lock • PIN-Code • Optical interface • Technical data Dimensions in mm (width) Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Express 20	•
Drain / Spin • ECO 40-60 • Washing extras • Short • Pre-wash • Water plus • Additional rinse cycle • Pre-ironing with steam • Buzzer • Safety Water protection system Water protection system Watercontrol-System Safety lock • PIN-Code • Optical interface • Technical data Dimensions in mm (width) Dimensions in mm (height) 850 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Dark garments / Denim	•
ECO 40-60 Washing extras Short -	Proofing	•
Washing extrasShort•Pre-wash•Water plus•Additional rinse cycle•Pre-ironing with steam•Buzzer•SafetyWater protection systemWater protection systemWatercontrol-SystemSafety lock•PIN-Code•Optical interface•Technical dataDimensions in mm (width)Dimensions in mm (height)850Dimensions in mm (depth)643Appliance depth in mm with opened door1077Weight in kg80Total rated load in kW2.10-2.40Voltage in V220-240Fuse rating in A13	Drain / Spin	•
Short Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Water control-System Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Valditional e •	ECO 40-60	•
Pre-wash Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Water control-System Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Pre-ironing with steam • Water protection system Watercontrol-System • Other control-System • Fuse rating in A	Washing extras	
Water plus Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Vatercontrol-System Vatercontrol-System Safety lock • Optical interface • Technical data Dimensions in mm (width) S96 Dimensions in mm (height) B80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A	Short	•
Additional rinse cycle Pre-ironing with steam Buzzer Safety Water protection system Watercontrol-System Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Pre-ironing with steam Watercontrol-System • • ### Watercontrol-System ### Option	Pre-wash	•
Pre-ironing with steam Buzzer Safety Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V 220-240 Fuse rating in A	Water plus	•
Buzzer Safety Water protection system Watercontrol-System Safety lock • PIN-Code • Optical interface • Technical data Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Additional rinse cycle	•
SafetyWater protection systemWatercontrol-SystemSafety lock•PIN-Code•Optical interface•Technical data	Pre-ironing with steam	•
Water protection system Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Euse rating in A Weight in kg Matercontrol-System Watercontrol-System 80 1077 850 850 1077 80 80 210-2.40 220-240 Fuse rating in A	Buzzer	<u>•</u>
Safety lock PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Exercise See See See See See See See See See S	Safety	
PIN-Code Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Experimental Substituting 13 13	Water protection system	Watercontrol-System
Optical interface Technical data Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (depth) Appliance depth in mm with opened door Weight in kg Total rated load in kW Voltage in V Euse rating in A Pole See See See See See See See	Safety lock	<u> </u>
Technical data Dimensions in mm (width) 596 Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	PIN-Code	•
Dimensions in mm (width) Dimensions in mm (height) Dimensions in mm (height) Even Dimensions in mm (height) Even Dimensions in mm (depth) Even Dimensions in mm (depth) Even Dimensions in mm (depth) Even Dimensions in mm (height) Even Dimensions in mm (width) Even Dimensions in mm (height) Even Dimensions in mm (hei	Optical interface	<u>•</u>
Dimensions in mm (height) 850 Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Technical data	
Dimensions in mm (depth) 643 Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Dimensions in mm (width)	596
Appliance depth in mm with opened door 1077 Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Dimensions in mm (height)	850
Weight in kg 80 Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Dimensions in mm (depth)	643
Total rated load in kW 2.10-2.40 Voltage in V 220-240 Fuse rating in A 13	Appliance depth in mm with opened door	1077
Voltage in V220-240Fuse rating in A13	Weight in kg	80
Fuse rating in A 13	Total rated load in kW	2.10-2.40
	Voltage in V	220-240
Frequency in Hz 50	Fuse rating in A	13
	Frequency in Hz	50
Length of supply lead in m 2	Length of supply lead in m	2

Míele


WWB360 WCS PWash&8kg

W1 front-loader washing machine:


A -20 %* I 8 kg I 1400 rpm I QuickPowerWash I Miele@home I CapDosing




W1 drawing, facia 5 degree, measures in mm



W1 drawing, facia 5 degree, measures in mm



W1 drawing, facia 5 degree, measures in mm



W1 drawing, facia 5 degree, measures in mm