

PDR 908 ROP [EL]

Professional vented dryer, Little Giants, electrically heated with extremely short programme running times. Performance 8.0 kg in 52 min.



- Drum volume 130.00 l, load size 8.0 kg
- Tested for intensive use unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics PerfectDry
- Future-proof connectivity via WiFi

EAN: 4002516870869 / Material number: 12752520 / Old Material Number: 52908364GB

Old Material Number: 52908364GB	
Construction type and version	
Construction type	Front-loader, stackable
Range	Performance Plus
Front	Lotus white
Fascia color	Stainless steel
Load in kg	8.0
Drum volume in l	130.00
Drying system	Exhaust air
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Performance data	
Maximum evaporation capacity in I/hour	51
Specific energy consumption in kWh/kg	0.50
Specific energy consumption for Cottons/Normal drying	0.50
programme with residual moisture at 48 % in kW	0.00
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture a	0.42
Programme duration in min.	52
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	52
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in	57
Control system	
Control system	M Touch Flex
Programmability	programmable
User interface	Residual moisture
	controlled
Max. delay start in h	24
Time left display	•
Programme sequence indicator	•



EAN: 4002516870869 / Material number: 12752520 /

PDR 908 ROP [EL]

Professional vented dryer, Little Giants, electrically heated with extremely short programme running times. Performance 8.0 kg in 52 min.



Old Material Number: 52908364GB	
Language can be selected easily at any time	•
Standard electrical connection	Ele etrie
Heating type	
Electrical connection	230V~ 50/60HZ
Electric heater rating in kW	5.22
Total connected load in kW	5.47
Fuse rating in A	25
Dimensions and weight of dryer	95.0
External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	717
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	<u>820</u>
Net weight in kg	51.5
Gross weight in kg	57
Maximum floor load in N	920
Emissions data	-70 JD(A) - 20 D
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	0.76
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface filter	•
PerfectDry	•
SoftLift drum ribs	•
Low temperature function	•
Communication slot	•
Drum lighting	•
Machine-independent accessories	•
Efficiency and sustainability	
How it works	Vented
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	*
WiFi	*
LAN module (optional)	*
WiFiConn@ct	•
Standards, test certificates and symbols	
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•