

KFMC 3834 L MasterCool fridge-freezer MasterFresh Pro | FoodView | AirClean System | IceMaker | BrilliantLight Pro



- Food stays fresh for up to 5 times longer — MasterFresh Pro
- Everything in full view at all times FoodView
- Fresh supplies without unpleasant odours #Longlife AirClean system
- Ice cubes for cold drinks IceMaker
- Practical illumination with elegant LEDs #BrilliantLight Pro



| ppliance category | |
|--|---|
| MasterCool (refrigeration unit XXL) | • |
| Construction type | |
| Built-in appliance | <u> </u> |
| Integrated appliance | • |
| Door hinge | Left |
| Convertible door hinging | • |
| Side-by-side enabled | • |
| Design | |
| Lighting | BrilliantLight Pro |
| SmartLight | • |
| User convenience | |
| Networking with Miele@home | • |
| FoodView (cameras) | 3 |
| Freshness system | MasterFresh Pro + DailyFresh ExtraCool |
| Longlife AirClean system | • |
| DynaCool | • |
| NoFrost | • |
| DuplexCool Pro | • |
| SoftClose | • |
| SelfClose | • |
| Number of IceMakers with mains water connection | 1 |
| ceMaker with mains water connection | • |
| Push2open | • |
| FullAccess | • |
| EasyClean | • |
| MaxLoad hinge | • |
| Control system | |
| Operating concept | M Touch Pro |
| Precise adjustment | Fridge and freezer temperature |
| Fridge compartment can be switched off | No |
| Independent temperature regulation of fridge and freezer zones | Yes |
| SuperCool&AirClean | • |
| SuperFreeze | • |
| No. of temperature zones | 3 |
| Sabbath mode | • |
| Holiday mode | • |
| Eco mode | • |
| Quicklce | • |
| Fridge/Fridge section | |
| Height-adjustable, full-width tempered glass shelves | 2 |
| Number of VeggieBoxes | 1 |
| No. of crisper drawers | 1 |
| vo. or enaper drawers | |

Míele

KFMC 3834 L MasterCool fridge-freezer MasterFresh Pro | FoodView | AirClean System | IceMaker | BrilliantLight Pro

Ice scoop




EAN: 4002516914440 / Material number: 12866570 /

| EAN: 4002516914440 / Material number: 12866570 | / | |
|--|------------|---|
| Old Material Number: 38383410GB | | |
| Freezer/Freezer section | | |
| Number of freezer baskets | 3 | _ |
| of which on telescopic runners | 2 | |
| Efficiency and sustainability | | |
| Energy efficiency class (A–G) | D | |
| Annual energy consumption in kWh | 254.00 | |
| Energy consumption in 24 h in kWh | 0.69 | |
| Safety | | |
| Spill-proof glass shelves | <u> </u> | |
| Acoustic door alarm | • | |
| Acoustic temperature alarm | • | |
| Technical data | | |
| Niche width in mm min. | 762 | |
| Niche width in mm max. | 762 | |
| Niche height in mm min. | 2134 | |
| Niche height in mm max. | 2134 | |
| Niche depth in mm | 610 | |
| Appliance width in mm | 756 | |
| Appliance height in mm | 2123 | |
| Appliance depth in mm | 608 | |
| Weight in kg | 236.5 | |
| Door hinge technology | Fixed door | _ |
| Max. door front weight — refrigerator, in kg | 60 | _ |
| Max. door front weight – freezer, in kg | 17 | _ |
| Climate class | SN-T | |
| Refrigerator compartment in I | 316 | |
| including PerfectFresh zone in I | 51 | |
| 4* freezer compartment in I | 160 | |
| Total usable capacity in I | 476 | |
| Storage time in case of fault in h | 19 | |
| Freezer capacity in kg/24 h | 14.00 | |
| Acoustic airborne noise emission class (A–D) | С | |
| Sound emissions in dB(A) re 1 pW | 39 | |
| Current consumption (mA) | 3000 | |
| Voltage in V | 220-240 | |
| Fuse rating in A | 10 | _ |
| Number of phases | 1 | |
| Frequency in Hz | 50-60 | |
| Length of supply lead in m | 3.0 | |
| Replacing lamps | Service | _ |
| Accessories included | | |
| | | |

Miele


KFMC 3834 L MasterCool fridge-freezer

MasterFresh Pro | FoodView | AirClean System | IceMaker | BrilliantLight Pro




KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, PACS, stainless steel front, installation (*Footnote) (drawing)

Information for KFMC 3632 L + R, KFMC 3836 L + R (US/CD) only, *View from the front, 1. Mains connection cable, L = 3000 mm (118 inch), 2. Water connection L = 1800 mm (70 inch), Information for KFMC 3834 L + R (EU), 1. Mains connection cable, L = 3000 mm , 2. Water connection L = 1800 mm




KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, integration, panel ready (installation drawing) (US)




KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, installation, panel ready (*Footnote) (drawing) (US)

Information for KFMC 3632 L + R, KFMC 3836 L + R (US/CD) only, *View from the front, 1. Mains connection cable, L = 3000 mm (118 inch), 2. Water connection L = 1800 mm (70 inch), Information for KFMC 3834 L + R (EU), 1. Mains connection cable, L = 3000 mm , 2. Water connection L = 18mm mm




KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, PACS, with stainless steel front, integration (drawing)



KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, front view, installation (*Footnote) (drawing)


*1. 60 kg, 2. 17 kg




KFMC3632R+L, KFMC3642R+L, KFMC3836R+L, KFMC3834R+L, KFMC3858FD, MasterCool III, frame neutral, installation (drawing)

Míele


KFMC 3834 L MasterCool fridge-freezer MasterFresh Pro | FoodView | AirClean System | IceMaker | BrilliantLight Pro




KFMC3632R+L, KFMC3642R+L, KFMC3836R+L, KFMC3834R+L, KFMC3858FD, MasterCool III, hinge clearance, installation (drawing)



KFMC3632R+L, KFMC3642R+L, KFMC3836R+L, KFMC3834R+L, KFMC3858FD, MasterCool III, Sideview bottom, installation (drawing)



KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, PACS, with stainless steel front, top view (drawing) (US)



KFMC3632R+L, KFMC3836R+L, KFMC3834R+L, MasterCool III, panel ready, top view (drawing) (US)