

DAR 1135 Extractor unit for perfectly combining with Range Cookers or Range Tops.



- Customised kitchen design fully integrated in 850 mm
- Powerful fan up to 650 m3/h
- Perfect illumination LED ClearView lighting
- Dishwasher-proof 3 high-quality stainless steel grease filters
- Safe and easy to clean Miele CleanCover

B

Osselvation by	
Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	Exhaust air
User convenience	
Rotary knob	
Electronic controls	
Power levels (number without Booster level)	3
Temperature sensor	•
Easy-to-clean canopy interior – CleanCover	•
Efficiency and sustainability	
Energy efficiency class (A+++ - D)	B
Annual energy consumption in kWh/year	68.4
Fluid dynamic efficiency class	В
Lighting efficiency class	A
Grease filtering efficiency class	С
Cleaning and care	
Dishwasher-safe grease collection channel	•
Filter system	
Number of dishwasher-safe stainless steel filters	3
Lighting	
LED	•
Number x W	3 x 3 W
Fan	
Dual-action fan	•
	-
	•
AC motor	•
AC motor Exhaust air	•
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591	200
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591	300
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591	300 400
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591	300
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN	300 400
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN	300 400 650
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN	300 400 650 39.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN	300 400 650 39.0 48.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 µPa) according to	300 400 650 39.0 48.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	300 400 650 39.0 48.0 54.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13	300 400 650 39.0 48.0 54.0 67.0 25.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13	300 400 650 39.0 48.0 54.0 67.0 25.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13	300 400 650 39.0 48.0 54.0 67.0 25.0 34.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13	300 400 650 39.0 48.0 54.0 67.0 25.0 34.0
AC motor Exhaust air Air throughput in Level 1 (m³/h) according to EN 61591 Air throughput in Level 2 (m³/h) according to EN 61591 Air throughput in Level 3 (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Air throughput in Booster level (m³/h) according to EN 61591 Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3 Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3 Sound pressure in Level 1 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 2 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Level 3 (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) according to EN 60704-2-13 Sound pressure in Booster level (dB(A) re 20 μPa) acc. to EN 60704-2-13	300 400 650 39.0 48.0 54.0 67.0 25.0 34.0

850

EAN: 4002515815748 / Material number: 10598370 / Old Material Number: 28113550GB

Canopy width in mm



DAR 1135 Extractor unit for perfectly combining with Range Cookers or Range Tops.




EAN: 4002515815748 / Material number: 10598370 / Old Material Number: 28113550GB

Canopy height in mm	449
Canopy depth in mm	579
Minimum height above electric hobs in mm	450
Net weight in kg	22.0
Length of supply lead in m	1.5
Standard plug fitted	•
Minimum safety distance above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Total rated load in kW	0.20
Voltage in V	230
Fuse rating in A	15
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction ducting connection at rear	•
Extraction ducting connection on side	•
Extraction ducting connection at top, rear, and si	•
Diameter of exhaust duct in mm	150
Accessories included	
Non-return flap	•



DAR 1135 Extractor unit for perfectly combining with Range Cookers or Range Tops.



DAR1135 (installation drawing)