Miele

PWM 908 [EL DV]

Professional washing machine, Little Giants, EL heated, with drain valve and target group specific programmes. Capacity 8.0 kg in 49 min.



- Drum volume 73 I, load capacity 8.0 kg
- Tested for intensive use unparalleled Miele quality
- Max. user convenience w. fulltouch colour display –M Touch Flex
- 22 % less water consumption and 28 % less energy consumption*
- Future-proof networking via WiFi

EAN: 4002516197157 / Material number: 11168820 / Old Material Number: 51908451IRL

Construction type and version Construction type Performance Plus Front Stainless steel Control panel colour Load in kg Dour opening [0] in mm Door opening angle in degrees 167 Door hinge Maintenance-free synchronous motor Honeycomb drum with perforated drum rear panel Application Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for residential homes and apartments Suitable for small businesses Suitable for small businesses Suitable for numerial alundries Suitable for numerial sundries Suitable for pospitals Suitable for supports clubs Suitable for sports clubs Suitable for sports clubs Suitable for the petrochemicals industry Suitable for subsement parks & holiday complexes Suitable for subsemption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Sp	O	
Range Front Stainless steel Control panel colour Load in kg Drum volume in I Door opening [0] in mm Door opening [0] in mm Door opening [0] in imm Door opening angle in degrees Informance-free synchronous motor Honeycomb drum with perforated drum rear panel Application Suitable for the hotel and catering industry Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for launderettes Suitable for launderettes Suitable for roummerial laundries Suitable for nommerical laundries Suitable for nommerical laundries Suitable for hospitals Suitable for commercial sundries Suitable for hospitals Suitable for beauty salons, spas, and fitness centres Suitable for sports clubs Suitable for the petrochemicals industry Suitable for state/community care facilities Performance dat Tested virucidal efficacy Proven hygiene Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption with cold water connection in l/kg Water consumption with cold water connection in l/kg Programme duration in minutes with cold water and hot water consumption with hot water connection in l/kg Programme duration in minutes with cold water and hot water consumption with hot water connection in l/kg Programme duration in minutes with cold water and hot water consumption with hot water connection in l/kg Programme duration in minutes with cold water and hot water consumption with hot water connection in l/kg Programme duration in minutes with cold water and hot water consumption with hot water connection in l/kg Spin speed in rpm Specific water water with hot finse in % 48 Spin speed in rpm	Construction type and version	En el la ede caladada
Front Stainless steel Control panel colour Load in kg Dourn volume in I 73 Door opening [Ø] in mm 300 Door opening angle in degrees 167 Door hinge right Maintenance-free synchronous motor • Honeycomb drum with perforated drum rear panel Application Suitable for the hotel and catering industry • Suitable for retirement and care homes • Suitable for retirement and care homes • Suitable for launderettes • Suitable for residential homes and apartments • Suitable for small businesses • Suitable for small businesses • Suitable for ownersial laundries • Suitable for nonversities, nurseries, and schools Suitable for phospitals • Suitable for sports clubs Suitable for phospitals • Suitable for broatly salons, spas, and fitness centres • Suitable for the petrochemicals industry • Suitable for the pod-processing industry • Suitable for subsement parks & holiday complexes • Performance data Ferformance data Ferside water consumption for cold water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption with cold water connection in l/kg Programme duration in minutes with cold water connection in l/kg Programme duration in minutes with cold water connection in l/kg Programme duration in minutes with cold water connection in l/kg Residual moisture with hot frinse in % 48 Res		
Control panel colour Load in kg B.0 Drum volume in I Door opening [0] in mm Boor opening [0] in mm Boor opening log lin degrees Boor opening angle in degree		
Load in kg 8.0 Puru volume in 73 300 Door opening [Ø] in mm 300		
Drum volume in I 73 Door opening [Ø] in mm 300 Door opening angle in degrees 167 Door hinge right Maintenance-free synchronous motor • Noneycomb drum with perforated drum rear panel • Application 175 Suitable for the hotel and catering industry • Suitable for retirement and care homes 175 Suitable for retirement and care homes 175 Suitable for residential homes and apartments 175 Suitable for dry cleaners 175 Suitable for commercial laundries 175 Suitable for commercial laundries 175 Suitable for nonerial laundries 175 Suitable for beamy sites 175 Suitable for camp sites 175 Suitable for camp sites 175 Suitable for camp sites 175 Suitable for beauty salons, spas, and fitness centres 175 Suitable for the petrochemicals industry 175 Suitable for the petrochemicals industry 175 Suitable for the food-processing industry 175 Suitable for the food-processing industry 175 Suitable for amusement parks & holiday complexes 175 Suitable for sumusement parks & holiday complexes 175 Suitable for state/community care facilities 175 Specific water consumption for cold water connection in I/kg 175 Specific water consumption for hot water connection in I/kg 175 Specific energy consumption for hot water connection in I/kg 175 Specific energy consumptio		
Door opening [0] in mm Door opening angle in degrees 167 Door hinge right Maintenance-free synchronous motor Honeycomb drum with perforated drum rear panel Application Suitable for the hotel and catering industry Suitable for the hotel and care homes Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for or small businesses Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for camp sites Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Perven hygiene Specific energy consumption for cold water connection in l/kg Specific water consumption for hot water connection in l/kg Specific energy consumption for hot water connection in kWhr/kg Water consumption with cold water connection in kW Programme duration in minutes with cold water connection Energy consumption with hot water connection in kW Programme duration in minutes with cold water and hot water consumption minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW and so consumption with hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot water connection in kW Programme duration in minutes with cold water and hot wat	·	
Door opening angle in degrees Door hinge Maintenance-free synchronous motor Maintenance-free synchronous motor Application Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for or dry cleaners Suitable for commercial laundries Suitable for omy cleaners Suitable for universities, nurseries, and schools Suitable for universities, nurseries, and schools Suitable for sports clubs Suitable for camp sites Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for musement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific water consumption with cold water connection in I/kg Specific wa		73
Door hinge Maintenance-free synchronous motor Honeycomb drum with perforated drum rear panel Application Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for launderettes Suitable for caresidential homes and apartments Suitable for cry cleaners Suitable for commercial laundries Suitable for small businesses Suitable for commercial laundries Suitable for camp sites Suitable for camp sites Suitable for camp sites Suitable for beauty salons, spas, and fitness centres Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for smale parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I/kg Water consumption with cold water connection in I/kg Programme duration in minutes with cold water and hot water consumption for Specific in kW Programme duration in minutes with cold water and hot water connection in I/kg Residual moisture with cold rinse in % Residual moisture with hot rinse in %	Door opening [Ø] in mm	300
Maintenance-free synchronous motor Honeycomb drum with perforated drum rear panel Application Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for launderettes Suitable for camerate and surfaments Suitable for commercial laundries Suitable for commercial laundries Suitable for small businesses Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for nomercial laundries Suitable for nomercial laundries Suitable for small businesses Suitable for nomercial laundries Suitable for small businesses Suitable for small businesses Suitable for small businesses Suitable for soprits clubs Suitable for sports clubs Suitable for sports clubs Suitable for sports clubs Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for the petrochemicals industry Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I/kg Water consumption with cold water connection in I/kg Water consumption with cold water connection in I/kg Frogramme duration in minutes with cold water connection in I/kg Frogramme duration in minutes with cold water connection in I/kg Frogramme duration in minutes with cold water and hot water connection in I/kg Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm	Door opening angle in degrees	167
Application Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for commercial laundries Suitable for commercial laundries Suitable for universities, nurseries, and schools Suitable for universities, nurseries, and schools Suitable for nospitals Suitable for camp sites Suitable for camp sites Suitable for doctors' and dentists' practices Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for amusement parks & holiday complexes Suitable for amusement parks & holiday complexes Suitable for suntided efficacy Proven hygiene Specific water consumption for cold water connection in I/kg Specific water consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg Specific energy consumption with cold water connection in I/kg	Door hinge	right
Application Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for dry cleaners Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for universities, nurseries, and schools Suitable for camp sites Suitable for sports clubs Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for the petrochemicals industry Suitable for the pot-processing industry Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in IV kg Specific water consumption for hot water connection in IV Specific water consumption with cold water connection in IV Why/kg Water consumption with cold water connection in IV Programme duration in winutes with cold water connection in IV Programme duration with cold water connection in IV Programme duration in minutes with cold water connection in IV Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Piss publication in since in Specific and in Ivaliance in Ival	Maintenance-free synchronous motor	•
Suitable for the hotel and catering industry Suitable for retirement and care homes Suitable for launderettes Suitable for launderettes Suitable for devidential homes and apartments Suitable for dry cleaners Suitable for commercial laundries Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for universities, nurseries, and schools Suitable for nospitals Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/k kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Water consumption with cold water connection in I/kg Water consumption with cold water connection in I/kg Programme duration in minutes with cold water connection Water consumption with hot water connection in I/kg Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm Suitable for the petrochemicals and schools Spin speed in rpm Suitable for state/commentines Suitable for state/commentines Suitable for sports clubs Suitable for sports clubs Suitable for doctors' and dentists' practices Suitable for doctors' and dentists' practices Suitable for sports clubs Suitable for sports clubs Suitable for proventies Suitable for sports clubs Suitable for sp	Honeycomb drum with perforated drum rear panel	•
Suitable for retirement and care homes Suitable for launderettes Suitable for residential homes and apartments Suitable for residential homes and apartments Suitable for commercial laundries Suitable for commercial laundries Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for camp sites Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in l/kg Specific energy consumption for cold water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Water consumption with cold water connection in l Energy consumption with cold water connection in l Programme duration in minutes with cold water connection in l Energy consumption with hot water connection in l Energy consumption with hot water connection in lW Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % 48 Residual moisture with hot rinse in % 45 Spin speed in rpm	Application	
Suitable for launderettes Suitable for residential homes and apartments Suitable for dry cleaners Suitable for commercial laundries Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for sports clubs Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Water consumption with cold water connection in I/kg Programme duration in minutes with cold water and hot water connection in I/kg Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm Suitable for size in security is and schools	Suitable for the hotel and catering industry	•
Suitable for residential homes and apartments Suitable for dry cleaners Suitable for commercial laundries Suitable for small businesses Suitable for miversities, nurseries, and schools Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for small sparks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for hot water connection in I/ kWh/kg Specific energy consumption for hot water connection in I/ kWh/kg Specific energy consumption for hot water connection in I/ Specific energy consumption with cold water connection in I/ Water consumption with hot water connection in I/ Water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 45 Spin speed in rpm	Suitable for retirement and care homes	•
Suitable for dry cleaners Suitable for commercial laundries Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in l/kg Specific water consumption for hot water connection in l/kWh/kg Specific energy consumption for hot water connection in l/kg Water consumption with cold water connection in kW Programme duration in minutes with cold water connection in l/specific energy consumption with cold water connection in kW Programme duration in minutes with cold water connection in kW Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm Suitable for sate/specific send specific send specific	Suitable for launderettes	•
Suitable for dry cleaners Suitable for commercial laundries Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in l/kg Specific water consumption for hot water connection in l/kWh/kg Specific energy consumption for hot water connection in l/kg Water consumption with cold water connection in kW Programme duration in minutes with cold water connection in l/specific energy consumption with cold water connection in kW Programme duration in minutes with cold water connection in kW Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm Suitable for sate/specific send specific send specific	Suitable for residential homes and apartments	•
Suitable for commercial laundries Suitable for small businesses Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in l/kg Specific water consumption for hot water connection in l/kg/ Specific energy consumption for hot water connection in l/kg Water consumption with cold water connection in l/kg Water consumption with cold water connection in l/kg Programme duration in minutes with cold water connection in l/kg Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm Suitable for camp stees. Spin speed in rpm Suitable for camp stees. Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for beauty salons, spas, and fitness centres Suitable for deal stees. Suitable for deal stees centres Suitable for deal stees Suitable for deal stees Suitable f		•
Suitable for universities, nurseries, and schools Suitable for hospitals Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific energy consumption for cold water connection in l/kg Specific water consumption for hot water connection in l/kg Specific water consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption with cold water connection in l/kg Specific energy consumption with cold water connection in l/kg Specific energy consumption with cold water connection in l Energy consumption with cold water connection in l Energy consumption with hot water connection in l Water consumption with hot water connection in l Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm		•
Suitable for hospitals Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kWh/kg Water consumption with cold water connection in I/k Water consumption with cold water connection in I/k Energy consumption with cold water connection in I/k Programme duration in minutes with cold water connection Water consumption with hot water connection in I/k Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Suitable for the contents Postation of the content of the	Suitable for small businesses	•
Suitable for hospitals Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kWh/kg Water consumption with cold water connection in I/k Water consumption with cold water connection in I/k Energy consumption with cold water connection in I/k Programme duration in minutes with cold water connection Water consumption with hot water connection in I/k Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Suitable for the contents Postation of the content of the		•
Suitable for camp sites Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kWh/kg Specific energy consumption for hot water connection in I/kWh/kg Water consumption with cold water connection in I/S Programme duration in minutes with cold water connection Water consumption with hot water connection in I/S Programme duration in minutes with cold water and hot water connection Residual moisture with hot rinse in % Residual moisture with hot rinse in % Spin speed in rpm		•
Suitable for sports clubs Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in I Energy consumption with hot water connection in I Specific energy consumption with hot water connection in I Energy consumption with hot wat	·	•
Suitable for beauty salons, spas, and fitness centres Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific vater consumption for hot water connection in I/kg Specific vater consumption for hot water connection in I/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in I Specific energy consumption with hot water connection in I Energy consumption with hot water connection in I Specific energy consumption with hot water connection in I Energy consumption with hot water connection in I As 0 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 45		•
Suitable for doctors' and dentists' practices Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with tot water connection in I Specific energy consumption with tot water connection in I Specific energy consumption with tot water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with total water connection in I Specific energy consumption with total water connection in I Specific energy consumption with total water connection in I Specific energy consumption with total water connection in I Specific energy consumption in I/kg Specific		•
Suitable for the petrochemicals industry Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection Specific energy consumption with hot water connection in I Energy consumption with hot water connection in I Since Specific energy consumption with hot water connection in I Also Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm Suitable for the food-processing industry Belliand to the food-processing industry Bel	·	· <u> </u>
Suitable for the food-processing industry Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in I Specific energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection in I Energy consumption with hot water connection in kW O.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 59 1600	·	
Suitable for amusement parks & holiday complexes Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Specific energy consumption with hot water connection in W 1.05 Programme duration in minutes with cold water connection in I Energy consumption with hot water connection in I Energy consumption with hot water connection in kW Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 59 Kasidual moisture with hot rinse in % 48 Residual in rpm	·	<u>. </u>
Suitable for state/community care facilities Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption with cold water connection in I Energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in kW 0.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 59 Spin speed in rpm 1600		<u>. </u>
Performance data Tested virucidal efficacy Proven hygiene Specific water consumption for cold water connection in I/ kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in I Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 1600		•
Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for cold water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in I Energy consumption with hot water connection in W 48.0 Energy consumption in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 59 Spin speed in rpm 1600	·	•
Proven hygiene Specific water consumption for cold water connection in I/kg Specific energy consumption for cold water connection in I/kg Specific water consumption for hot water connection in I/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Water consumption with cold water connection in I/kg Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I/kg Energy consumption with hot water connection in I/kg Energy consumption with hot water connection in I/kg Energy consumption with hot water connection in I/kg 48.0 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % Spin speed in rpm 1600		
Specific water consumption for cold water connection in I/kg Specific energy consumption for cold water connection in kWh/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in kW Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in kW Displayed Frogramme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Spin speed in rpm 6.40		•
kg Specific energy consumption for cold water connection in kWh/kg Specific water consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption for hot water connection in l/kg Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption with cold water connection in l Specific energy consumption in hinter energy consumption in l Specific energy		•
kWh/kg Specific water consumption for hot water connection in I/kg Specific energy consumption for hot water connection in I/kg Specific energy consumption for hot water connection in RWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in kW 0.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 500 Spin speed in rpm 1600	, i	6.40
Specific energy consumption for hot water connection in kWh/kg Water consumption with cold water connection in I Energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in I Energy consumption with hot water connection in kW 0.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 59 48 Spin speed in rpm 1600	· · · · · · · · · · · · · · · · · · ·	0.13
kWh/kg Water consumption with cold water connection in I 51.0 Energy consumption with cold water connection in kW 1.05 Programme duration in minutes with cold water connection 59 Water consumption with hot water connection in I 48.0 Energy consumption with hot water connection in kW 0.50 Programme duration in minutes with cold water and hot water connection 49 water connection 48 Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 45 Spin speed in rpm 1600	Specific water consumption for hot water connection in I/kg	6.00
Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in kW O.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 100 100 100 100 100 100 100 1		0.06
Energy consumption with cold water connection in kW Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in kW O.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 100 100 100 100 100 100 100 1		51.0
Programme duration in minutes with cold water connection Water consumption with hot water connection in I Energy consumption with hot water connection in kW O.50 Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 59 48.0 48 45 50 50 60 60 60 60 60 60 60 6		
Water consumption with hot water connection in I Energy consumption with hot water connection in kW Double Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 48.0 49 49 48 48 60 60 60 60 60 60 60 60 60 6		
Energy consumption with hot water connection in kW Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 0.50 49 48 Residual moisture with cold rinse in % 45 Spin speed in rpm		
Programme duration in minutes with cold water and hot water connection Residual moisture with cold rinse in % Residual moisture with hot rinse in % Spin speed in rpm 49 48 48 1600		
water connection Residual moisture with cold rinse in % 48 Residual moisture with hot rinse in % 45 Spin speed in rpm 1600		
Residual moisture with hot rinse in % 45 Spin speed in rpm 1600	water connection	
Spin speed in rpm 1600		
g factor 704		
	g factor	704

Based on the Coloured items 60 °C programme with a warm water connection, compared to predecessor.



PWM 908 [EL DV]

Professional washing machine, Little Giants, EL heated, with drain valve and target group specific programmes. Capacity 8.0 kg in 49 min.



EAN: 4002516197157 / Material number: 11168820 / Old Material Number: 51908451IRL

Control system Control system Control system Control system M Touch Flex Programmability programmabile Max. delay start in h Time left display Programme sequence indicator Language can be selected easily at any time Dispensing Detergent drawer CapDosing Detergent drawer CapDosing Flexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating in kW 5.30 Total connected load in kW Fuse rating in A 13 Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 7use rating in A 13 Possible voltage variant 1 Electrical connection Hot water [number] Cold water [number] Ty 1/2" hose w/ 3/4" th. union Dump valve Dimensions and weight External dimensions, height in mm External dimensions, gross depth in mm External dimensions, gross beight in mm External dimensions, gross beight in mm External dimensions, gross beight in mm External dimensions, gross depth in mm External dimensions, gross beight in mm Fatemal dimensions gross depth in mm Fate	Tested operating hours	30000
Programmability Max. delay start in h 96 Time left display Programme sequence indicator Language can be selected easily at any time Dispensing Detergent drawer CapDosing Flexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connection 10	Control system	
Max. delay start in h Time left display Programme sequence indicator Language can be selected easily at any time Dispensing Detergent drawer CapDosing Plexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection Hot water [number] Cold water [number] Dump valve Dimensions and weight External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross well her workplace Emission sound pressure level in the workplace Endard very position in the common of the	Control system	M Touch Flex
Max. delay start in h Time left display Programme sequence indicator Language can be selected easily at any time Dispensing Detergent drawer CapDosing Plexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection Hot water [number] Cold water [number] Dump valve Dimensions and weight External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross well her workplace Emission sound pressure level in the workplace Endard very position in the common of the	Programmability	programmable
Time left display Programme sequence indicator Language can be selected easily at any time Dispensing Detergent drawer CapDosing Heakible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW 5.50 Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Tuse rating in kW Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 3 Supplementation of the variation of t	Max. delay start in h	
Programme sequence indicator Language can be selected easily at any time Dispensing Detergent drawer CapDosing Flexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connection Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 2.85 Fuse rating in A 13 Water connected load in kW 5.30 Total connected load in kW 13 Water lonnected load in kW 13 Water lonnected load in kW 13 Water lonnected load in kW 2.85 Fuse rating in A 13 Water connection/drainage Cold water [number] 1x 1/2* hose w/ 3/4* th. union Dump valve Dimensions and weight External dimensions, height in mm 850 External dimensions, sheight in mm 605 External dimensions, gross height in mm 605 External dimensions, gross height in mm 606 External dimensions, gross height in mm 607 External dimensions, gross height in mm 608 External dimensions, gross height in mm 609 External dimensions, gross height in mm 600 External dimensions data 600 External dimensions data 700 External dimensions data 700 Emission sound pressure level in the workplace 70 dB(A) re 20 µPa 600 Heat dissipation into the room in MJ/h 700 Features 700 Figure standard dispenser 7		•
Language can be selected easily at any time Dispensing Detergent drawer CapDosing • Rexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heating type Electrical connected load in kW 5.30 Total connected load in kW 5.50 Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A National Maximum flow and a selection and a selectical connection Heater rating in kW 2.85 Cold water [number] Lix 1/2" hose w/ 3/4" th. union Dump valve Dimensions and weight External dimensions, height in mm 850 External dimensions, syoss height in mm 940 External dimensions, gross height in mm 660 External dimensions, gross depth in mm 714 External dimensions, gross depth in mm 768 Net weight in kg 107 Maximum floor load in N/m² Emission sound pressure level in the workplace Emission sound imbalance monitoring - Commercial shock absorbers - Hard-wearing stainless-steel flange Disinfection rinse		•
Dispensing 3 compartments CapDosing • Hexible dispensing adapter (optional) • Maximum number of connections for liquid dispenser pumps [number] 6 Empty sensor • Standard electrical connection Electric Heating type Electric Electrical connection 2N~ 400V 50HZ Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 Electrical connection Electrical connection 230V~ Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage 13 Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 850 External dimensions, gepth in mm 605 External dimensions, gross height in mm 714 Externa		•
Detergent drawer CapDosing Plexible dispensing adapter (optional) Plexible dispensing adapter (optional) Plexible dispensing adapter (optional) Plexible dispensing adapter of connections for liquid dispenser pumps [number] Plexible systems or Plexible systems or Pleating type Plectrical connection Pleating type Plectrical connection Pleater rating in kW Pleater rating in kW Possible voltage variant 1 Plectrical connection Pleater rating in kW Possible voltage variant 1 Plectrical connection Pleater rating in kW Pleater rating i		
CapDosing Plexible dispensing adapter (optional) Plexible dispensing adapter (optional) Plexible dispensing adapter (optional) Plexible dispensing adapter (optional) Plexible dispension	. •	3 compartments
Flexible dispensing adapter (optional) Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electric Electrical connection Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve Dimensions and weight External dimensions, height in mm 850 External dimensions, depth in mm 714 External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm 605 External dimensions, gross depth in mm 744 External dimensions, gross depth in mm 660 External dimensions, gross depth in mm 678 Net weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace 470 dB(A) re 20 μPa Heat dissipation into the room in MJ/h Peatures 3-dimensional imbalance monitoring Commercial shock absorbers 4-dimensions insee		
Maximum number of connections for liquid dispenser pumps [number] 6 Empty sensor • Standard electrical connection Electric Heating type Electric Electrical connection 2N~ 400V 50HZ Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 230V~ Electrical connection 230V~ Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage 1x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, width in mm External dimensions, width in mm 850 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 <td< td=""><td></td><td>•</td></td<>		•
Standard electrical connection Heating type Electric Electrical connection 2N~ 400V 50HZ Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 Electrical connection Electrical connection 230V~ Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage 13 Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight 850 External dimensions, height in mm 850 External dimensions, width in mm 605 External dimensions, gross height in mm 940 External dimensions, gross width in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Maximum number of connections for liquid dispenser	6
Heating type Electric Electrical connection 2N~ 400V 50HZ Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 230V~ Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage 1x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 605 External dimensions, width in mm 605 External dimensions, gross height in mm 940 External dimensions, gross depth in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Empty sensor	•
Electrical connection 2N~ 400V 50HZ Heater rating in kW 5.30 Total connected load in kW 5.50 Fuse rating in A 13 Possible voltage variant 1 Electrical connection 230V~ Heater rating in kW 2.65 Total connected load in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" th. union Hot water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 850 External dimensions, width in mm 605 External dimensions, gross height in mm 714 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emission sound pressure level in the workplace <70 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring • Commercial shock absorbers • Hard-wearing stainless-steel flange • Disinfection rinse	Standard electrical connection	
Heater rating in kW Total connected load in kW 5.50 Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm 850 External dimensions, width in mm 605 External dimensions, gross height in mm 714 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross width in mm 660 External dimensions, gross width in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	Heating type	Electric
Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Z.65 Total connected load in kW Z.85 Total connected load in kW Z.85 Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm Faternal dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm Faternal dimensions, gross width in	Electrical connection	2N~ 400V 50HZ
Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Cotal connected load in kW Euse rating in A Water connection/drainage Cold water [number] In x 1/2" hose w/ 3/4" th. union Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Formal dime	Heater rating in kW	5.30
Possible voltage variant 1 Electrical connection 230V~ Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage 1x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight 25 External dimensions, height in mm 850 External dimensions, width in mm 605 External dimensions, gross height in mm 714 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data 2 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Total connected load in kW	5.50
Electrical connection 230V~ Heater rating in kW 2.65 Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage 1x 1/2" hose w/ 3/4" th. union Cold water [number] 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 605 External dimensions, gross height in mm 714 External dimensions, gross width in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Fuse rating in A	13
Heater rating in kW Total connected load in kW 2.85 Fuse rating in A 13 Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Faternal dimensions, gross depth in mm External dimensions, gross depth in mm Faternal dimensions, gross depth in mm Tofa Net weight in kg Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	Possible voltage variant 1	
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Ix 1/2" hose w/ 3/4" th. union Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Faternal dimensions, gross depth in mm External dimensions, gross depth in mm Faternal dimensions, gross depth in mm Tofa Net weight in kg Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	Electrical connection	230V~
Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Ix 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm Faternal dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm Faternal dimensions, gross depth in mm Faternal dimensions, gross depth in mm Total External dimensions, gross depth in mm Total External dimensions, gross depth in mm Total External dimensions depth in mm Total Externa	Heater rating in kW	2.65
Water connection/drainage1x 1/2" hose w/ 3/4" th. unionCold water [number]1x 1/2" hose w/ 3/4" th. unionHot water [number]1x 1/2" hose w/ 3/4" th. unionDump valveDN 70Dimensions and weightExternal dimensions, height in mm850External dimensions, width in mm605External dimensions, depth in mm714External dimensions, gross height in mm940External dimensions, gross width in mm660External dimensions, gross depth in mm768Net weight in kg103.0Gross weight in kg107Maximum floor load in N/m²2820Emissions data2820Emissions data2820Heat dissipation into the room in MJ/h1.00Features3-dimensional imbalance monitoring•Commercial shock absorbers•Hard-wearing stainless-steel flange•Disinfection rinse•	Total connected load in kW	2.85
Cold water [number]	Fuse rating in A	13
Hot water [number] union 1x 1/2" hose w/ 3/4" th. union Dump valve DN 70 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 850 External dimensions, width in mm 605 External dimensions, gross height in mm 714 External dimensions, gross width in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Water connection/drainage	
Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Fass Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² Existing at 107 Maximum floor load in N/m² External dimensions data Emission sound pressure level in the workplace Freatures 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	Cold water [number]	1x 1/2" hose w/ 3/4" th.
Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Faternal dimensions, gross depth in mm Tall External dimensions, gross width in mm Tall		union
Dump valve DN 70 Dimensions and weight 850 External dimensions, height in mm 605 External dimensions, depth in mm 714 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data 2820 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring • Commercial shock absorbers • Hard-wearing stainless-steel flange • Disinfection rinse •	Hot water [number]	1x 1/2" hose w/ 3/4" th.
Dimensions and weight 850 External dimensions, height in mm 605 External dimensions, depth in mm 714 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa		union
External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	Dump valve	DN 70
External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	Dimensions and weight	
External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	External dimensions, height in mm	850
External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	External dimensions, width in mm	605
External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	External dimensions, depth in mm	714
External dimensions, gross depth in mm 768 Net weight in kg Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse	External dimensions, gross height in mm	940
Net weight in kg 103.0 Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data -70 dB(A) re 20 μPa Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	External dimensions, gross width in mm	660
Gross weight in kg 107 Maximum floor load in N/m² 2820 Emissions data 2820 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	External dimensions, gross depth in mm	768
Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Net weight in kg	103.0
Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Gross weight in kg	107
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse < <70 dB(A) re 20 μPa 1.00 • • • • • • • • • • • • • • • • • •	Maximum floor load in N/m ²	2820
Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse 1.00 • 0	Emissions data	
Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse •	Emission sound pressure level in the workplace	<70 dB(A) re 20 μPa
3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse •	Heat dissipation into the room in MJ/h	1.00
Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse •	Features	
Hard-wearing stainless-steel flange Disinfection rinse •	3-dimensional imbalance monitoring	•
Disinfection rinse •	Commercial shock absorbers	•
	Hard-wearing stainless-steel flange	•
EcoSpeed •	Disinfection rinse	•
	EcoSpeed	•



PWM 908 [EL DV]

Professional washing machine, Little Giants, EL heated, with drain valve and target group specific programmes. Capacity 8.0 kg in 49 min.



EAN: 4002516197157 / Material number: 11168820 / Old Material Number: 51908451IRL

Pre-ironing	•
Efficient drum rib technology	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Flow meter	•
LED drum lighting, class 1	•
Communication slot	•
Add laundry	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system (optional)	•
Optical interface for service access	<u> </u>
Peak load cut-out/energy management (optional)	•
LAN/WiFi module (optional)	•
WiFiConn@ct	•
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•