

PWM 906 [EL DP MAR 2 AC 208-240V 60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 6.0 kg.



- Drum volume 57 I, load capacity 6.0 kg
- Tested for intensive use unparalleled Miele quality
- Max. user convenience w. fulltouch colour display –M Touch Flex
- 22 % less water consumption and 28 % less energy consumption*
- Thorough cleaning with professional wash programmes

EAN: 4002516279372 / Material number: 11251400 / Old Material Number: 51906389MAR

Construction type and version	
Construction type	Front loader
Range	Performance Plus
Front	Stainless steel
Control panel colour	Stainless steel
Load in kg	6.0
Drum volume in I	57
Door opening [Ø] in mm	300
Door opening angle in degrees	167
Door hinge	right
Maintenance-free synchronous motor	•
Honeycomb drum with perforated drum rear panel	•
Application	
Suitable for offshore use	•
Suitable for marine use	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/	7.50
kg	
Specific energy consumption for cold water connection in kWh/kg	0.16
Specific water consumption for hot water connection in I/kg	7.00
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in I	45.0
Energy consumption with cold water connection in kW	0.95
Programme duration in minutes with cold water connection	59
Water consumption with hot water connection in I	42.0
Energy consumption with hot water connection in kW	0.38
Programme duration in minutes with cold water and hot water connection	49
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	45
	1600
Spin speed in rpm	
g factor	704
Tested operating hours	30000
Control system	M. Taviala Clavi
Control system	M Touch Flex
Programmability Name and the last in the	programmable
Max. delay start in h	96
Time left display	•
Programme sequence indicator	•
Language can be selected easily at any time	•
Dispensing	
Detergent drawer	3 compartments
CapDosing	•
Flexible dispensing adapter (optional)	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•

^{*} Based on the Coloured items 60 °C programme with a warm water connection, compared to predecessor.



PWM 906 [EL DP MAR 2 AC 208-240V 60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 6.0 kg.



EAN: 4002516279372 / Material number: 11251400 / Old Material Number: 51906389MAR

Heating type	Standard electrical connection	
Electrical connection	Heating type	Electric
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] In x 1/2" hose w/ 3/4" th. union Drain pump Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm Father weight in kg Industrial dimensions, gross depth in mm For 88 External dimensions, gross depth in mm For 80 External dimensions, gross depth in mm For 80 External dimensions, gross depth in mm For 80 External dimensions, gross de		2~208-240V 60HZ
Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Drain pump DN 22 Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Formal dimensions depth in kg Industrial dimensions depth depth in kg Industrial di	Heater rating in kW	3.80-5.00
Fuse rating in A Water connection/drainage Cold water [number] Ix 1/2" hose w/ 3/4" th. union Hot water [number] Drain pump DN 22 Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Formal dimensions depth in kg Industrial dimensions depth depth in kg Industrial di	Total connected load in kW	4.00-5.20
Cold water [number]		
Cold water [number]	Water connection/drainage	
Hot water [number] union 1x 1/2" hose w/ 3/4" th. union Drain pump DN 22 Dimensions and weight 850 External dimensions, height in mm 605 External dimensions, gross height in mm 714 External dimensions, gross height in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 100.0 Gross weight in kg 100.0 Maximum floor load in N/m² 2820 Emissions data 2820 Emissions ound pressure level in the workplace <70 dB(A) re 20 μPa		1x 1/2" hose w/ 3/4" th.
Drain pump Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, width in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Foral dimensions, gross depth in mm Tofa Net weight in kg 100.0 Gross weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² Examission sound pressure level in the workplace Emissions ound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace Emission sound pressure level in the workplace -70 dB(A) re 20 μPa 1.00 Features 3-dimensional imbalance monitoring - Commercial shock absorbers 4-Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed - Pre-ironing - Efficient drum rib technology - Temperature monitoring - Special heater element - Automatic load control - Flow meter - LED drum lighting, class 1 Communication slot Add laundry - Add laundry - Machine-independent accessories - Efficiency and sustainability - Recycling rate in % - 95 Connection options Payment system (optional) - LAN/WiFi module (optional) - LAN/WiFi module (optional) - ViFiConn@ct - Standards, test certificates and symbols		union
Dimensions and weight External dimensions, height in mm 850 External dimensions, width in mm 605 External dimensions, gross height in mm 714 External dimensions, gross width in mm 940 External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² 2820 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Hot water [number]	17 17 2 11000 117 07 1 1111
External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm 660 External dimensions, gross depth in mm 768 Net weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² Emissions data Emissions sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring • Commercial shock absorbers I-ard-wearing stainless-steel flange Disinfection rinse EcoSpeed • Pre-ironing Efficient drum rib technology Temperature monitoring • Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry • Machine-independent accessories Efficiency and sustainability Recycling rate in % 95 Connection options Payment system (optional) • LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols	Drain pump	DN 22
External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm To88 Net weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² Exissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols	Dimensions and weight	
External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth External dimensions, gross depth External dimensions External dimens	External dimensions, height in mm	850
External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Total Net weight in kg Total Net weight in kg Total Maximum floor load in N/m² Eas20 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Teatures 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) UkiFiConn@ct Standards, test certificates and symbols	External dimensions, width in mm	605
External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols	External dimensions, depth in mm	714
External dimensions, gross width in mm External dimensions, gross depth in mm 768 Net weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols	External dimensions, gross height in mm	940
External dimensions, gross depth in mm Net weight in kg 100.0 Gross weight in kg 104 Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Net weight in kg Gross weight in kg Haximum floor load in N/m² Zes20 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Heat dissipation into the room in MJ/h Heat dissipation limbalance monitoring Gommercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFiConn@ct Standards, test certificates and symbols		768
Gross weight in kg Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFiConn@ct Standards, test certificates and symbols		
Maximum floor load in N/m² 2820 Emissions data Emission sound pressure level in the workplace <70 dB(A) re 20 μPa		
Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFiConn@ct Standards, test certificates and symbols		
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 1.00 Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFiConn@ct Standards, test certificates and symbols		2020
Heat dissipation into the room in MJ/h Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LANWiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		<70 dB(A) re 20 uPa
Features 3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LANWiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
3-dimensional imbalance monitoring Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) UKIFICOnn@ct Standards, test certificates and symbols		1.00
Commercial shock absorbers Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LANWiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		•
Hard-wearing stainless-steel flange Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LANWiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		<u> </u>
Disinfection rinse EcoSpeed Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LANWiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
EcoSpeed Pre-ironing Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Pre-ironing Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Efficient drum rib technology Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) WiFiConn@ct Standards, test certificates and symbols		
Temperature monitoring Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		<u></u>
Special heater element Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Automatic load control Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Flow meter LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
LED drum lighting, class 1 Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Communication slot Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Add laundry Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Machine-independent accessories Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		<u>•</u>
Efficiency and sustainability Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		<u>•</u>
Recycling rate in % Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols	·	•
Connection options Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		0.5
Payment system (optional) Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		95
Optical interface for service access Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
Peak load cut-out/energy management (optional) LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols		
LAN/WiFi module (optional) WiFiConn@ct Standards, test certificates and symbols	_ ·	
WiFiConn@ct Standards, test certificates and symbols		•
Standards, test certificates and symbols		•
		•
WEEE •	Standards, test certificates and symbols	
	WEEE	•



PWM 906 [EL DP MAR 2 AC 208-240V 60Hz]

Professional washing machine, Little Giants, electric heating, drain pump Lloyd's Register approved, load size 6.0 kg.



EAN: 4002516279372 / Material number: 11251400 / Old Material Number: 51906389MAR

Lloyd's Register

Complies with Machinery Directive 2006/42/EC