

## PRI 421 [EL LAM] Rotary ironer, electrically heated With spring padding for optimum finishing results.



- Capacity113.0 kg/h<sup>\*</sup>, roller diameter 365 mm, roller width 2040 mm
- Outstanding finish results thanks to HPC heater plate
- State-of-the-art controls Touch display
- Selection of the most important settings favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

With 25% residual moisture – performance data according to DIN 11 902:<br/>br>The achievable ironing capacity depends on overall conditions such as, for example, the type of laundry and the experience of the operator. EAN: 4002516365990 / Material number: 11606800 / Old Material Number: 53421102EU

Construction type   Laundry infeed at the front, laundry outfeed at the back laundry outfeed at the back     Range   Professional     Outer casing   Iron grey     Roller diameter in mm   365     Working width in mm   2040     Heater plate material   Aluminium     Padding   Leaf-spring padding     Ironer cover   ARAMID needle-felt cloth     Application   •     Suitable for the hotel and catering industry   •     Suitable for commercial laundries   •     Suitable for hospitals   •     Suitable for forspitals   •     Suitable for offshore use   •     Performance data   Max.     Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Touch display (optional)   Touch-Display PRI     Programme setting   programme parameters     Minimum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   SN AC 400V 50-60HZ     Electrice   Electric	Construction type and version	
laundry outfeed at the back       Range     Professional       Outer casing     Iron grey       Roller diameter in mm     365       Working width in mm     2040       Heater plate material     Aluminium       Padding     Leaf-spring padding       Ironer cover     ARAMID needle-felt cloth       Application     •       Suitable for retirement and care homes     •       Suitable for commercial laundries     •       Suitable for offshore use     •       Performance data     •       Max. inoning performance at 25 % residual moisture in kg/h     113.0       Tested operating hours     20000       Control system     Touch display       Control system     Touch display       Programme setting     Setting of defined programme parameters       Minimum ironing speed, controlled in m/min     1.5       Maximum ironing speed, controlled in m/min     5.4       Adjustable temperature     Infinitely variable       Stating type     Electric       Electrical connection     3N AC 400V 50-60HZ       Electrical connection RIM     22.90		Laundry infeed at the front.
Outer casing     Iron grey       Roller clameter in mm     365       Working width in mm     2040       Heater plate material     Aluminium       Padding     Leaf-spring padding       Ironer cover     ARAMID needle-feit cloth       Application     •       Suitable for the hotel and catering industry     •       Suitable for commercial laundries     •       Suitable for obspitals     •       Suitable for offshore use     •       Performance data     max. ironing performance at 25 % residual moisture in kg/h       Max. ironing performance at 25 % residual moisture in kg/h     113.0       Toseted operating hours     200000       Control system     Touch display       Touch display (optional)     Touch display       Programme setting     Setting of defined programme parameters       Minimum ironing speed, controlled in m/min     1.5       Mazimum ironing speed, controlled in m/min     5.4       Adjustable temperature     Infinitely variable       Stating type     Electric       Electric connection     3N AC 400V 50-60HZ       Electric heater rating in kW		
Roller diameter in mm   365     Working width in mm   2040     Heater plate material   Aluminium     Padding   Leaf-spring padding     Ironer cover   ARAMID needle-felt cloth     Application   •     Suitable for the hotel and catering industry   •     Suitable for commercial laundries   •     Suitable for nospitals   •     Suitable for offshore use   •     Performance data   113.0     Max. ironing performance at 25 % residual moisture in kg/h   113.0     Touch display (optional)   Touch-display     Control system   Touch display     Touch display (optional)   Touch-display PRI     Programme setting   programme parameters     Minimum ironing speed, controlled in m/min   1.5     Maximum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electric heater rating in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   External dimensions, depth in mm	Range	Professional
Working width in mm 2040   Heater plate material Alurninium   Padding Leaf-spring padding   Ironer cover ARAMID needle-felt cloth   Application •   Suitable for the hotel and catering industry •   Suitable for rommercial laundries •   Suitable for commercial laundries •   Suitable for offshore use •   Performance data •   Max. ironing performance at 25 % residual moisture in kg/h 113.0   Tested operating hours 20000   Control system Touch display   Touch display (optional) Touch -Display PRI   Programme setting Setting of defined programme parameters   Minimum ironing speed, controlled in m/min 1.5   Maximum ironing speed, controlled in m/min 5.4   Adjustable temperature Infinitely variable   Standard electrical connection 3N AC 400V 50-60HZ   Electric Electric   Electric heater rating in kW 23.50   Total dimensions, width in mm 2759   External dimensions, keight in mm 1110   External dimensions, gross height in mm 1388   External dimensions, gross width in mm 2866   External dimensions, gross weight in mm 1388	Outer casing	Iron grey
Working width in mm 2040   Heater plate material Alurninium   Padding Leaf-spring padding   Ironer cover ARAMID needle-felt cloth   Application •   Suitable for the hotel and catering industry •   Suitable for rommercial laundries •   Suitable for commercial laundries •   Suitable for offshore use •   Performance data •   Max. ironing performance at 25 % residual moisture in kg/h 113.0   Tested operating hours 20000   Control system Touch display   Touch display (optional) Touch -Display PRI   Programme setting Setting of defined programme parameters   Minimum ironing speed, controlled in m/min 1.5   Maximum ironing speed, controlled in m/min 5.4   Adjustable temperature Infinitely variable   Standard electrical connection 3N AC 400V 50-60HZ   Electric Electric   Electric heater rating in kW 23.50   Total dimensions, width in mm 2759   External dimensions, keight in mm 1110   External dimensions, gross height in mm 1388   External dimensions, gross width in mm 2866   External dimensions, gross weight in mm 1388	Roller diameter in mm	365
Heater plate material   Aluminium     Padding   Leaf-spring padding     Ironer cover   ARAMID needle-felt cloth     Application   Suitable for the hotel and catering industry   •     Suitable for nomercial laundries   •     Suitable for onspitals   •     Suitable for onspitals   •     Suitable for offshore use   •     Performance data   113.0     Tested operating hours   20000     Control system   Touch display     Touch display (optional)   Touch display     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   1.5     Maximum ironing speed, controlled in m/min   5.4     Acjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electrical connection   3N AC 400V 50-60HZ     Electrica load in KW   22.90     Total connectod load in KW   22.90     Total connecton newight   External dimensions, height in mm     External dimensions, gross height in mm   1110     External dimensions, gross height in mm   1388 <tr< td=""><td></td><td>2040</td></tr<>		2040
Ironer cover     ARAMID needle-feit cloth       Application     Suitable for the hotel and catering industry     •       Suitable for retirement and care homes     •       Suitable for commercial laundries     •       Suitable for offshore use     •       Performance data     Max. ironing performance at 25 % residual moisture in kg/h     113.0       Tested operating hours     20000     Control system       Control system     Touch display (optional)     Touch-Display PRI       Programme setting     Setting of defined programme parameters       Minimum ironing speed, controlled in m/min     1.5       Maxinum ironing speed, controlled in m/min     5.4       Adjustable temperature     Infinitely variable       Standard electrical connection     3N AC 400V 50-60HZ       Electrical connection     3N AC 400V 50-60HZ       Electrica loan in KW     22.90       Total connected load in kW     23.50       Fuse rating in A     50       Dimensions and weight     External dimensions, width in mm       External dimensions, gross height in mm     1188       External dimensions, gross depth in mm     1388 <t< td=""><td>Heater plate material</td><td>Aluminium</td></t<>	Heater plate material	Aluminium
ApplicationSuitable for the hotel and catering industrySuitable for retirement and care homesSuitable for commercial laundriesSuitable for hospitalsSuitable for hospitalsSuitable for offshore usePerformance dataMax. ironing performance at 25 % residual moisture in kg/hTested operating hoursControl systemControl systemControlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionHeating typeElectricElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in ADimensions and weightExternal dimensions, height in mmSteternal dimensions, gross beight in mm1388External dimensions, gross beight in mm1388External dimensions, gross beight in mm1388External dimensions, gross beight in mm1096Net weight in kgGross weight in kgArison sound pre	Padding	Leaf-spring padding
Suitable for the hotel and catering industry   •     Suitable for retirement and care homes   •     Suitable for offshore use   •     Performance data   •     Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Control system   Touch display (optional)     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   1.5     Maxinum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electric   Electric     Electric heater rating in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   1110     External dimensions, keight in mm   11411     External dimensions, gross height in mm   1388     External dimensions, gross beight in mm   1388     External dimensions, gross depth in mm   1096     Net weight in kg   377     Gross weight in k	Ironer cover	ARAMID needle-felt cloth
Suitable for retirement and care homes   •     Suitable for orommercial laundries   •     Suitable for offshore use   •     Performance data   •     Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Touch display (optional)   Touch-Display PRI     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   1.5     Maximum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electric   Electric     Electric heater rating in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   External dimensions, keight in mm     External dimensions, gross height in mm   1110     External dimensions, gross beight in mm   1388     External dimensions, gross depth in mm   1388     External dimensions, gross depth in mm   1096     Net weight in kg   377	Application	
Suitable for retirement and care homes   •     Suitable for orommercial laundries   •     Suitable for offshore use   •     Performance data   •     Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Touch display (optional)   Touch-Display PRI     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   1.5     Maximum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electric   Electric     Electric heater rating in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   External dimensions, keight in mm     External dimensions, gross height in mm   1110     External dimensions, gross beight in mm   1388     External dimensions, gross depth in mm   1388     External dimensions, gross depth in mm   1096     Net weight in kg   377	Suitable for the hotel and catering industry	•
Suitable for hospitals   •     Suitable for offshore use   •     Performance data   •     Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Touch display (optional)   Touch-Display PRI     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   1.5     Maximum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electrical connection   3N AC 400V 50-60HZ     Electrical connected load in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   1110     External dimensions, height in mm   1110     External dimensions, gross width in mm   1388     External dimensions, gross width in mm   1388     External dimensions, gross depth in mm   1096     Net weight in kg   377     Gross weight in kg   377     Maximum floor load in N/m <sup>2</sup> <td></td> <td>•</td>		•
Suitable for offshore use   •     Performance data   Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Control system   Touch display     Touch display (optional)   Touch-Display PRI     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electric heater rating in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   External dimensions, height in mm     External dimensions, depth in mm   1110     External dimensions, gross height in mm   1388     External dimensions, gross weight in mm   1096     Net weight in kg   377     Gross weight in kg   377     Gross weight in kg   456     Maximum floor load in N/m²   3698     Entension sound pressure level in the workplace   56 dB(A) re 20 µPa     Heat dissipation into the room in MJ/h	Suitable for commercial laundries	•
Suitable for offshore use   •     Performance data   Max. ironing performance at 25 % residual moisture in kg/h   113.0     Tested operating hours   20000     Control system   Touch display     Control system   Touch display     Touch display (optional)   Touch-Display PRI     Programme setting   Setting of defined programme parameters     Minimum ironing speed, controlled in m/min   5.4     Adjustable temperature   Infinitely variable     Standard electrical connection   3N AC 400V 50-60HZ     Electric heater rating in kW   22.90     Total connected load in kW   23.50     Fuse rating in A   50     Dimensions and weight   External dimensions, height in mm     External dimensions, depth in mm   1110     External dimensions, gross height in mm   1388     External dimensions, gross weight in mm   1096     Net weight in kg   377     Gross weight in kg   377     Gross weight in kg   456     Maximum floor load in N/m²   3698     Entension sound pressure level in the workplace   56 dB(A) re 20 µPa     Heat dissipation into the room in MJ/h	Suitable for hospitals	•
Max. ironing performance at 25 % residual moisture in kg/h113.0Tested operating hours20000Control systemTouch displayControl systemTouch display (PRIProgramme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionBelectricElectricElectricElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightExternal dimensions, height in mmExternal dimensions, gross height in mm1388External dimensions, gross width in mm2759External dimensions, gross weight in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tablePatented EasyFold out-feed table•Outfeed table extension (optional)•		•
Tested operating hours20000Control systemTouch displayTouch display (optional)Touch-Display PRIProgramme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connection3N AC 400V 50-60HZElectric cal connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightEternal dimensions, height in mmExternal dimensions, depth in mm1110External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross width in mm1096Net weight in kg377Gross weight in kg3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tablePatented EasyFold out-feed table•Outfeed table extension (optional)•	Performance data	
Tested operating hours20000Control systemTouch displayTouch display (optional)Touch-Display PRIProgramme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connection3N AC 400V 50-60HZElectric cal connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightEternal dimensions, height in mmExternal dimensions, depth in mm1110External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross width in mm1096Net weight in kg377Gross weight in kg3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tablePatented EasyFold out-feed table•Outfeed table extension (optional)•	Max. ironing performance at 25 % residual moisture in kg/h	113.0
Control systemTouch displayTouch display (optional)Touch-Display PRIProgramme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionElectricElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightExternal dimensions, height in mmExternal dimensions, beight in mm1110External dimensions, gross width in mm2759External dimensions, gross width in mm2866External dimensions, gross width in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Tested operating hours	20000
Control systemTouch displayTouch display (optional)Touch-Display PRIProgramme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionElectricElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightExternal dimensions, height in mmExternal dimensions, beight in mm1110External dimensions, gross width in mm2759External dimensions, gross width in mm2866External dimensions, gross width in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Control system	
Programme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionInfinitely variableHeating typeElectricElectric connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, gross height in mm1388External dimensions, gross height in mm2866External dimensions, gross beight in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•		Touch display
Programme settingSetting of defined programme parametersMinimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionInfinitely variableHeating typeElectricElectric connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, gross height in mm1388External dimensions, gross height in mm2866External dimensions, gross beight in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•	Touch display (optional)	Touch-Display PRI
Minimum ironing speed, controlled in m/min1.5Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionInfinitely variableHeating typeElectricElectric connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•		Setting of defined
Maximum ironing speed, controlled in m/min5.4Adjustable temperatureInfinitely variableStandard electrical connectionElectricElectrical connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightEtectrical connectionExternal dimensions, height in mm1110External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	<b>. .</b>	programme parameters
Adjustable temperatureInfinitely variableStandard electrical connectionInfinitely variableHeating typeElectricElectric connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm1110External dimensions, width in mm2759External dimensions, gross height in mm1888External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceFeaturesFeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•	Minimum ironing speed, controlled in m/min	1.5
Standard electrical connectionElectricHeating typeElectricElectrical connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm1110External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm2866External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Maximum ironing speed, controlled in m/min	5.4
Heating typeElectricElectrical connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emission sound pressure level in the workplace56 dB(A) re 20 μPaHeat dissipation into the room in MJ/h13.70Features9Patented EasyFold out-feed table•Outfeed table extension (optional)•	Adjustable temperature	Infinitely variable
Electrical connection3N AC 400V 50-60HZElectric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross weight in mm1096Net weight in kg3777Gross weight in kg456Maximum floor load in N/m²3698Emissions data56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Standard electrical connection	
Electric heater rating in kW22.90Total connected load in kW23.50Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross weight in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEnd dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Heating type	Electric
Total connected load in kW23.50Fuse rating in A50Dimensions and weightExternal dimensions, height in mmExternal dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross weight in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEnd dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Electrical connection	3N AC 400V 50-60HZ
Fuse rating in A50Dimensions and weight1110External dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm2866External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Electric heater rating in kW	22.90
Dimensions and weight1110External dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Total connected load in kW	23.50
External dimensions, height in mm1110External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg3777Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceFeatures56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Fuse rating in A	50
External dimensions, width in mm2759External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•	Dimensions and weight	
External dimensions, depth in mm1441External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceFeatures56 dB(A) re 20 µPaPatented EasyFold out-feed table•Outfeed table extension (optional)•	External dimensions, height in mm	1110
External dimensions, gross height in mm1388External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	External dimensions, width in mm	2759
External dimensions, gross width in mm2866External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	External dimensions, depth in mm	1441
External dimensions, gross depth in mm1096Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	External dimensions, gross height in mm	1388
Net weight in kg377Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplaceEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	External dimensions, gross width in mm	2866
Gross weight in kg456Maximum floor load in N/m²3698Emissions dataEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•	External dimensions, gross depth in mm	1096
Maximum floor load in N/m²   3698     Emissions data   20 µPa     Emission sound pressure level in the workplace   56 dB(A) re 20 µPa     Heat dissipation into the room in MJ/h   13.70     Features   20 µPa     Patented EasyFold out-feed table   •     Outfeed table extension (optional)   •	Net weight in kg	377
Emissions dataEmissions dataEmission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed tableOutfeed table extension (optional)•	Gross weight in kg	456
Emission sound pressure level in the workplace56 dB(A) re 20 µPaHeat dissipation into the room in MJ/h13.70FeaturesPatented EasyFold out-feed table•Outfeed table extension (optional)•	Maximum floor load in N/m <sup>2</sup>	3698
Heat dissipation into the room in MJ/h   13.70     Features   -     Patented EasyFold out-feed table   -     Outfeed table extension (optional)   -	Emissions data	
Features   Patented EasyFold out-feed table   Outfeed table extension (optional)	Emission sound pressure level in the workplace	56 dB(A) re 20 µPa
Patented EasyFold out-feed table •   Outfeed table extension (optional) •	Heat dissipation into the room in MJ/h	13.70
Outfeed table extension (optional)	Features	
	Patented EasyFold out-feed table	•
HPC heater plate	Outfeed table extension (optional)	•
	HPC heater plate	•



## PRI 421 [EL LAM] Rotary ironer, electrically heated With spring padding for optimum finishing results.



EAN: 4002516365990 / Material number: 11606800 / Old Material Number: 53421102EU

Automatic finger guard	•
FlexControl footswitch	•
In-feed table	•
Pick-off bands	•
Laundry box	•
Laundry return feed (optional)	•
Cover (optional)	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Emergency switch-off	•
APRI 319 care set for the heater plate included in the scope of delivery	•
Machine-independent accessories	•
Connection options	
Peak load cut-out/energy management (optional)	•
Standards, test certificates and symbols	
VDE	•
CE	•
WEEE	•
VDE-EMC	•
Splash-proof IPX0	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•