

PRI 210 [EL SOM STW AB]

Rotary ironer, electrically heated

with the latest controls and flexible working height for marine applications.



- Capacity 30.0 kg/h*, roller diameter 210 mm, roller width 1000 mm
- Ideal ergonomics heightadjustable and optional plinth
- State-of-the-art controls Touch display
- Selection of the most important settings favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

'With 15% residual moisture – performance data according to DIN 11 902:
br>The achievable ironing capacity depends on overall conditions such as, for example, the type of laundry and the experience of the operator.

EAN: 4002516422303 / Material number: 11741300 / Old Material Number: 53210008SOM

Construction type Laundry infeed and outfeed at the front Can be set up against a wall • Range Professional Outer casing Iron grey Roller diameter in mm 210 Working width in mm 1000 Heater plate material Aluminium Padding Supple steel wool Ironer cover ARAMID needle-felt cloth Application • Suitable for offshore use • Suitable for marine use • Performance data Part of the steel operating hours Control system 20000 Control system 20000 Control system Touch display Touch display (optional) Touch display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Adjustable temperature Infinitely variable Standard electrical connection 3 AC 440V 50-60HZ Beating type Electric Electrical connected load in kW 5.40 Total connected load in kW		
Can be set up against a wall ● Range Professional Outer casing Iron grey Roller diameter in mm 210 Working width in mm 1000 Heater plate material Aluminium Padding Supple steel wool Ironer cover ARAMID needle-felt cloth Application • Suitable for offshore use • Suitable for marine use • Performance data * Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 20000 Control system 70 cuch display Control system 70 cuch display (potional) Touch display (potional) Touch-Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection 1.5 Heating type Electric Electric heater rating in kW	Construction type and version	
Range Outer casing Iron grey Roller diameter in mm 210 Working width in mm 1000 Heater plate material Aluminium Padding Supple steel wool Ironer cover ARAMID needle-felt cloth Application Suitable for offshore use • Suitable for marine use Performance data Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 20000 Control system Touch display Touch display (optional) Touch-Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Heating type Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm 1374 External dimensions, gross width in mm 1763 External dimensions gross width in mm 1763 External dimensions gross width in mm 1763 External dimensions data Emission sound pressure level in the workplace 170 dB(A) re 20 µPa 184 Heat dissipation into the room in MJ/h 185 Features Automatic finger guard 190 countries and residual monitor 190 countries and 190 countries 1	Construction type	3
Outer casing Roller diameter in mm 210 Working width in mm Heater plate material Padding Irone cover Application Suitable for offshore use Suitable for marine use Performance data Max. ironing performance at 15 % residual moisture in kg/h Touch display (optional) Programme setting Forgramme setting Maximum ironing speed, controlled in m/min Adjustable temperature Ifficiate onection Heating type Electrica connection Electrica connection Electrica locanection Electrica locanection Fuse rating in kW Total connected load in kW Fuse rating in kM External dimensions, height in mm External dimensions, gross belight in mm External dimensions, gross height in mm External dimensions External dimensions External dimensions External dimensions External dimensions E	Can be set up against a wall	•
Roller diameter in mm 210 Working width in mm 1000 Heater plate material Aluminium Supple steel wool Ironer cover ARAMID needle-felt cloth Application Suitable for offshore use • Suitable for offshore use • Suitable for marine use • Performance data Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 20000 Control system Touch display (optional) Touch-Display PRI Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Infinitely variable Ielectrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm 1374 External dimensions, gross height in mm 1763 External dimensions, gross width in mm 1763 External dimensions of 470 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 4,50 Features Automatic finger guard 1 FlexControl footswitch 4 Airing bar 4 Feed-in board	Range	Professional
Working width in mm 1000 Heater plate material Aluminium Padding Supple steel wool Ironer cover ARAMID needle-felt cloth Application • Suitable for marine use • Performance data *** Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 200000 Control system Touch display Control system Touch display (optional) Touch display (optional) Touch-Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection 4.0 Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight 1579 External dimensions, keight in mm 1579 External dimension	Outer casing	Iron grey
Heater plate material Padding Supple steel wool Ironer cover ARAMID needle-felt cloth Application Suitable for offshore use Suitable for marine use Performance data Max. ironing performance at 15 % residual moisture in kg/h Tested operating hours Control system Control system Touch display (optional) Programme setting Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min Adjustable temperature Standard electrical connection Heating type Electric cheater rating in kW Fuse rating in A Dimensions and weight External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross so depth in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External	Roller diameter in mm	210
Padding Supple steel wool Ironer cover ARAMID needle-felt cloth Application • Suitable for offshore use • Suitable for marine use • Performance data 30.0 Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 20000 Control system Touch display Control system Touch Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection 4.0 Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, width in mm 1579 External dimensions, depth in mm 1763 External dimensions, gross height in mm 1763 External dimensions, gross depth in mm	Working width in mm	1000
Ironer cover Application Suitable for offshore use Suitable for offshore use Performance data Max. ironing performance at 15 % residual moisture in kg/h Tested operating hours Control system Touch display (optional) Programme setting Touch display (optional) Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min Adjustable temperature Islandard electrical connection Heating type Electrical connection Heating type Electrical connection Sinensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions gross width in mm External dimensions gross depth in mm External dimensions gross depth in mm External dimensions gross depth in mm External dimensions gross width in mm External dimensions gross depth in mm External dimensions gross width in mm External dimensions gross depth in mm External dimensions gross depth in	Heater plate material	Aluminium
Application Suitable for offshore use Performance data Max. ironing performance at 15 % residual moisture in kg/h Tested operating hours Control system Control system Control display (optional) Programme setting Touch display (optional) Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min Adjustable temperature Standard electrical connection Heating type Electrical connection Blectric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, depth in mm 1579 External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions data Emission sound pressure level in the workplace FlexControl footswitch Alring bar Feed-in board • • • • • • • • • • • • •	Padding	Supple steel wool
Suitable for offshore use Performance data Max. ironing performance at 15 % residual moisture in kg/h Tested operating hours Control system Control system Control display (optional) Programme setting Maximum ironing speed, controlled in m/min Adjustable temperature Infinitely variable Electrical connection Heating type Electrical connection Electrical connected load in kW Touse dimensions, width in mm 16 Dimensions and weight External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions defined in kg Basission sound pressure level in the workplace Featines Automatic finger guard FlexControl footswitch Alring bar Feed-in board	Ironer cover	ARAMID needle-felt cloth
Suitable for marine use Performance data Max. ironing performance at 15 % residual moisture in kg/h Tested operating hours Control system Control system Touch display (optional) Programme setting Minimum ironing speed, controlled in m/min Adjustable temperature Standard electrical connection Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross depth in mm External dimensions, depth in kg 122 Emission sound pressure level in the workplace Features Automatic finger guard FleatControl footswitch Airing bar Feed-in board	Application	
Performance data Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 20000 Control system Touch display Touch Josplay (optional) Touch-Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection 3 AC 440V 50-60HZ Electrical connection 3 AC 440V 50-60HZ Electrical connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1579 External dimensions, gross height in mm 1579 External dimensions, gross height in mm 1763 External dimensions, gross depth in mm 1763 External dimensions, gross depth in mm 136 Maximum floor load in N/m² 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Suitable for offshore use	•
Max. ironing performance at 15 % residual moisture in kg/h 30.0 Tested operating hours 20000 Control system Touch display Touch display (optional) Touch-Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Infinitely variable Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1579 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 136 Maximum floor load in N/m² 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emission sound pressure level in the workplace <70	Suitable for marine use	•
Tested operating hours Control system Control system Touch display (optional) Programme setting Forgramme setting Minimum ironing speed, controlled in m/min Adjustable temperature Standard electrical connection Heating type Electrical connection Electric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, width in mm 1579 External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions gross height in mm External dimensions gross height in mm External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions gross beight in mm External dimensions gross width in mm External dimensions gross beight in mm External dimensions gross width in	Performance data	
Control system Control system Touch display (optional) Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min Adjustable temperature Infinitely variable Standard electrical connection Heating type Electrical connection Electrical connection 3 AC 440V 50-60HZ Electrical connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm 1579 External dimensions, depth in mm 476 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Max. ironing performance at 15 % residual moisture in kg/h	30.0
Control system Touch display Touch display (optional) Touch-Display PRI Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight 1032 External dimensions, height in mm 1579 External dimensions, width in mm 1579 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 136 Maximum floor load in N/m² 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	Tested operating hours	20000
Touch display (optional) Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min Adjustable temperature Infinitely variable Standard electrical connection Heating type Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A Dimensions and weight External dimensions, height in mm 1579 External dimensions, depth in mm 476 External dimensions, gross height in mm 1763 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1200 Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Control system	
Programme setting Setting of defined programme parameters Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Electric Heating type Electric Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight 16 External dimensions, height in mm 1579 External dimensions, width in mm 1579 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data 2 Emissions sound pressure level in the workplace <70 dB(A) re 20 μPa	Control system	Touch display
Minimum ironing speed, controlled in m/min Maximum ironing speed, controlled in m/min Adjustable temperature Standard electrical connection Heating type Electrical connection Biectric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross width in mm 1763 External dimensions, gross depth in mm External dimensions, gross depth in mm External dimensions, gross width in mm External dimensions, gross depth in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Touch display (optional)	Touch-Display PRI
Minimum ironing speed, controlled in m/min 1.5 Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Electric Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight 16 External dimensions, height in mm 1032 External dimensions, width in mm 1579 External dimensions, gross height in mm 476 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emissions data Emissions data 270 dB(A) re 20 μPa Heat dissipation into the room in MJ/h 4.50 Features 4 Automatic finger guard • Feed-in board<	Programme setting	Setting of defined
Maximum ironing speed, controlled in m/min 4.0 Adjustable temperature Infinitely variable Standard electrical connection Electric Heating type Electric Electric connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm External dimensions, width in mm 1579 External dimensions, depth in mm 476 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data 2 Emission sound pressure level in the workplace <70 dB(A) re 20 μPa		programme parameters
Adjustable temperature Standard electrical connection Heating type Electric Electric as AC 440V 50-60HZ Electric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, height in mm 1579 External dimensions, depth in mm 1579 External dimensions, gross height in mm 1374 External dimensions, gross height in mm 1763 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 1800 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Minimum ironing speed, controlled in m/min	1.5
Standard electrical connection Heating type Electric Electrical connection 3 AC 440V 50-60HZ Electric heater rating in kW 5.40 Total connected load in kW 5.80 Fuse rating in A 16 Dimensions and weight External dimensions, height in mm 1579 External dimensions, width in mm 1579 External dimensions, depth in mm 1374 External dimensions, gross height in mm 1763 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 1763 External dimensions, gross depth in mm 1763 External dimensions, gross depth in mm 1860 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.50 Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Maximum ironing speed, controlled in m/min	4.0
Heating typeElectricElectrical connection3 AC 440V 50-60HZElectric heater rating in kW5.40Total connected load in kW5.80Fuse rating in A16Dimensions and weight1032External dimensions, height in mm1579External dimensions, width in mm476External dimensions, gross height in mm1374External dimensions, gross width in mm1763External dimensions, gross depth in mm660Net weight in kg122Gross weight in kg136Maximum floor load in N/m²1220Emissions data20Emission sound pressure level in the workplace<70 dB(A) re 20 μPa	Adjustable temperature	Infinitely variable
Electrical connection Electric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Standard electrical connection	
Electric heater rating in kW Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, height in mm 1032 External dimensions, width in mm 1579 External dimensions, depth in mm 476 External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Heating type	Electric
Total connected load in kW Fuse rating in A Dimensions and weight External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board	Electrical connection	3 AC 440V 50-60HZ
Fuse rating in A Dimensions and weight External dimensions, height in mm 1032 External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board		5.40
Dimensions and weightExternal dimensions, height in mm1032External dimensions, width in mm1579External dimensions, depth in mm476External dimensions, gross height in mm1374External dimensions, gross width in mm1763External dimensions, gross depth in mm660Net weight in kg122Gross weight in kg136Maximum floor load in N/m²1220Emissions data20Emission sound pressure level in the workplace<70 dB(A) re 20 μPa	Total connected load in kW	5.80
External dimensions, height in mm External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 1579 476 476 476 476 476 477 478 478	Fuse rating in A	16
External dimensions, width in mm External dimensions, depth in mm External dimensions, gross height in mm External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 1374 476 1374 128 1290 122 122 124 125 126 127 128 1290 1290 1200 1200 121 121 1220 122	Dimensions and weight	
External dimensions, depth in mm External dimensions, gross height in mm 1374 External dimensions, gross width in mm 1763 External dimensions, gross width in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 476 1374 476 1374 1476 147	External dimensions, height in mm	1032
External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 1374 147 1763 1220 136 1420 1420 1420 1450 150 160 170 180 180 180 180 180 180 18	External dimensions, width in mm	1579
External dimensions, gross width in mm External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 1763 1763 1763 187 188 189 189 189 189 189 189	External dimensions, depth in mm	476
External dimensions, gross depth in mm 660 Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 600 122 436 436 436 4450	External dimensions, gross height in mm	1374
Net weight in kg 122 Gross weight in kg 136 Maximum floor load in N/m² 1220 Emissions data -70 dB(A) re 20 μPa Emission sound pressure level in the workplace <70 dB(A) re 20 μPa	External dimensions, gross width in mm	1763
Gross weight in kg Maximum floor load in N/m² 1220 Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 136 1220 470 dB(A) re 20 μPa 4.50 4.50 • • • • • • • Features	External dimensions, gross depth in mm	660
Maximum floor load in N/m² Emissions data Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 1220 470 dB(A) re 20 μPa 4.50 • 4.50 • • • • • • • • • • • • •	Net weight in kg	122
Emissions data <70 dB(A) re 20 μPa		136
Emission sound pressure level in the workplace Heat dissipation into the room in MJ/h 4.50 Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 4.50 • • • • • • • • • • • • • • • • • •	Maximum floor load in N/m ²	1220
Heat dissipation into the room in MJ/h Features Automatic finger guard FlexControl footswitch Airing bar Feed-in board 4.50 • • FlexControl footswitch • • • • • • • • • • • • •	Emissions data	
FeaturesAutomatic finger guard•FlexControl footswitch•Airing bar•Feed-in board•	Emission sound pressure level in the workplace	<70 dB(A) re 20 μPa
Automatic finger guard FlexControl footswitch Airing bar Feed-in board • • • • • • • • • • • • •	Heat dissipation into the room in MJ/h	4.50
FlexControl footswitch Airing bar Feed-in board • • • • • • • • • • • • •	Features	
Airing bar Feed-in board • • • • • • • • • • • • • • • • • •	Automatic finger guard	•
Feed-in board •	FlexControl footswitch	•
·	Airing bar	
Pick-off bands •	Feed-in board	•
	Pick-off bands	•



PRI 210 [EL SOM STW AB] Rotary ironer, electrically heated with the latest controls and flexible working height for marine applications.



EAN: 4002516422303 / Material number: 11741300 / Old Material Number: 53210008SOM

Laundry box (optional)	•
Laundry return feed	•
Favourite programme	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Clean and wax heater plate indicator (op	•
Plinth (optional)	•
Option of ironing when seated	•
APRI 319 care set for the heater plate included in the scope of delivery	•
Machine-independent accessories	•
Connection options	
Connection options Payment system (optional)	•
	•
Payment system (optional)	
Payment system (optional) Peak load cut-out/energy management	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols VDE	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols VDE CE	· · · · · · · · · · · · · · · · · · ·
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols VDE CE EAC	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols VDE CE EAC WEEE	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols VDE CE EAC WEEE VDE-EMC	
Payment system (optional) Peak load cut-out/energy management Standards, test certificates and symbols VDE CE EAC WEEE VDE-EMC RCM	