

## PRI 214 [EL SOM STW] Rotary ironer, electrically heated with the latest controls and flexible working height for marine applications.



- Capacity35.0 kg/h\*, roller diameter 210 mm, roller width 1400 mm
- Ideal ergonomics heightadjustable and optional plinth
- State-of-the-art controls Touch display
- Selection of the most important settings favourite programmes
- Perfect rotary ironing performance flexibly positioned heater plate

EAN: 4002516422907 / Material number: 11744580 / Old Material Number: 53214007SOM

| Construction type and version                              |   |
|--|---|
| Construction type  | Laundry infeed and outfeed at the front |
| Can be set up against a wall                               | •                                       |
| Range  | Professional                            |
| Outer casing   | Iron grey                               |
| Roller diameter in mm                                      | 210                                     |
| Working width in mm  | 1400                                    |
| Heater plate material                                      | Aluminium                               |
| Padding  | Supple steel wool                       |
| Ironer cover   | ARAMID needle-felt cloth                |
| Application  |   |
| Suitable for offshore use                                  | •                                       |
| Suitable for marine use                                    | •                                       |
| Performance data   |   |
| Max. ironing performance at 25 % residual moisture in kg/h | 35.0                                    |
| Tested operating hours                                     | 20000                                   |
| Control system   |   |
| Control system   | Touch display                           |
| Touch display (optional)                                   | Touch-Display PRI                       |
| Programme setting  | Setting of defined                      |
|  | programme parameters                    |
| Minimum ironing speed, controlled in m/min                 | 1.5                                     |
| Maximum ironing speed, controlled in m/min                 | 4.0                                     |
| Adjustable temperature                                     | Infinitely variable                     |
| Standard electrical connection                             |   |
| Heating type   | Electric                                |
| Electrical connection                                      | 3 AC 440V 50-60HZ                       |
| Electric heater rating in kW                               | 7.90                                    |
| Total connected load in kW                                 | 8.40                                    |
| Fuse rating in A   | 16                                      |
| Dimensions and weight                                      |   |
| External dimensions, height in mm                          | 1032                                    |
| External dimensions, width in mm                           | 1979                                    |
| External dimensions, depth in mm                           | 650                                     |
| External dimensions, gross height in mm                    | 1374                                    |
| External dimensions, gross width in mm                     | 2163                                    |
| External dimensions, gross depth in mm                     | 660                                     |
| Net weight in kg   | 140                                     |
| Gross weight in kg   | 155                                     |
| Maximum floor load in N/m <sup>2</sup>                     | 1400                                    |
| Emissions data   |   |
| Emission sound pressure level in the workplace             | <70 dB(A) re 20 μPa                     |
| Heat dissipation into the room in MJ/h                     | 11.00                                   |
| Features   |   |
| Automatic finger guard                                     | •                                       |
| FlexControl footswitch                                     | •                                       |
| Feed-in board  | •                                       |
| Pick-off bands   | •                                       |
| Laundry box  |   |

With 25% residual moisture – performance data according to DIN 11 902:<br/>br>The achievable ironing capacity depends on overall conditions such as, for example, the type of laundry and the experience of the operator.



## PRI 214 [EL SOM STW] Rotary ironer, electrically heated with the latest controls and flexible working height for marine applications.



EAN: 4002516422907 / Material number: 11744580 / Old Material Number: 53214007SOM

| Laundry return feed  | • |
|--|---|
| Favourite programme  | • |
| Incorrect feed recognition   | • |
| Air suspension   | • |
| Pause function   | • |
| High contact pressure  | • |
| Clean and wax heater plate indicator (op                                 | • |
| Plinth (optional)  | • |
| Option of ironing when seated  | • |
| APRI 319 care set for the heater plate included in the scope of delivery | • |
| Machine-independent accessories  | • |
| Connection options   |   |
| Payment system (optional)  | • |
| Peak load cut-out/energy management                                      | • |
| Standards, test certificates and symbols                                 |   |
| VDE  | • |
| CE   | • |
| EAC  | • |
| WEEE   | • |
| VDE-EMC  | • |
| RCM  | • |
| Splash-proof IPX0  | • |
| UKCA   | • |
| Complies with Machinery Directive 2006/42/EC                             | • |