Míele

PW 6321 [EL MF] Washing machine, electrically heated With liquid dispenser and individually programmable controls.



- Drum volume 320 I, load capacity 32.0 kg
- Large programme variety application-specific wash programmes
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 47 % %*, g factor447

EAN: 4002516435853 / Material number: 11779650 / Old Material Number: 51632109ZER

| E W. 10020101000007 Matorial Harrison. 111100007 Cla We | |
|--|-----------------|
| Construction type and version | |
| Construction type | Front loader |
| Range | Professional |
| Front | Stainless steel |
| Control panel colour | Stainless steel |
| Load ratio | 1:10 |
| Load in kg | 32.0 |
| Drum volume in I | 320 |
| Door opening [Ø] in mm | 430 |
| Door opening angle in degrees | 180 |
| Door hinge | right |
| Maintenance-free motor with frequency converter | • |
| Honeycomb drum | • |
| Application | |
| Suitable for the hotel and catering industry | • |
| Suitable for retirement and care homes | • |
| Suitable for facility management | • |
| Suitable for dry cleaners | • |
| Suitable for commercial laundries | • |
| Suitable for fire brigades and rescue services | • |
| Suitable for studs, riding schools and stables | • |
| Suitable for universities, nurseries, and schools | • |
| Suitable for hospitals | • |
| Suitable for sports clubs | • |
| Suitable for beauty salons, spas, and fitness centres | • |
| Performance data | |
| Tested virucidal efficacy | • |
| Proven hygiene | • |
| Specific water consumption for cold water connection in I/ | 9.00 |
| kg | |
| Specific energy consumption for cold water connection in | 0.25 |
| kWh/kg | |
| Specific water consumption for hot water connection in I/kg | 8.80 |
| Specific energy consumption for hot water connection in | 0.10 |
| kWh/kg | 000.0 |
| Water consumption with cold water connection in I | 288.0 |
| Energy consumption with cold water connection in kW | 8.00 |
| Programme duration in minutes with cold water connection | 61 |
| Water consumption with hot water connection in I | 281.6 |
| Energy consumption with hot water connection in kW | 3.20 |
| Programme duration in minutes with cold water and hot water connection | 49 |
| Water consumption in ECO programme with cold water | 281.6 |
| connection in I | 201.0 |
| Energy consumption in ECO programme with cold water | 6.20 |
| Programme duration in minutes with cold water connection | 47 |
| in ECO programme | |
| Water consumption in ECO programme with hot water | 284.8 |
| connection in I | |
| Energy consumption in ECO programme with hot water | 1.60 |
| | |

Residual moisture specification relates to a hot rinse during the last rinse cycle.

Míele

PW 6321 [EL MF] Washing machine, electrically heated With liquid dispenser and individually programmable controls.



EAN: 4002516435853 / Material number: 11779650 / Old Material Number: 51632109ZER

| Programme duration in minutes with cold water and hot water connection in ECO programme | 37 |
|--|---|
| Residual moisture with cold rinse in % | 50 |
| Residual moisture with hot rinse in % | 47 |
| Spin speed in rpm | 1000 |
| g factor | 447 |
| Tested operating hours | 30000 |
| Control system | |
| Control system | Profitronic M |
| Programmability | Freely programmable |
| Max. delay start in h | Freely selectable |
| Time left display | • |
| Programme sequence indicator | • |
| Selectable display languages | • |
| Standard/target grp programmes | |
| Basic programmes | • |
| Programmes for the hotel and catering industry | • |
| Programmes for retirement and care homes | • |
| Programmes for facility management | • |
| Programmes for dry cleaners | • |
| Programmes for small businesses | • |
| Programmes for fire brigades and rescue services | • |
| Programmes for studs, riding schools, and stables | • |
| Programmes for hospitals | • |
| Programmes for sports clubs | • |
| Programmes for beauty clinics, spas, and fitness studios | • |
| 1 rogrammos for bodaty offices, opas, and fit foss stadios | |
| Dispensing | |
| Dispensing Detergent drawer | 3 compartments |
| Detergent drawer | 3 compartments |
| Detergent drawer Liquid dispensing module | • |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser | 3 compartments • 12 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] | • |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser | • |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection | 12 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type | • 12 • Electric |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection | 12 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW | • 12 • Electric 3N AC 380-415V 50-60HZ |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union DN 70 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union DN 70 1643 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union DN 70 1643 1089 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union DN 70 1643 1089 1280 |
| Detergent drawer Liquid dispensing module Maximum number of connections for liquid dispenser pumps [number] Empty sensor Standard electrical connection Heating type Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm | • 12 • Electric 3N AC 380-415V 50-60HZ 30.00 31.00 63 2x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union DN 70 1643 1089 1280 1710 |

Míele

PW 6321 [EL MF] Washing machine, electrically heated With liquid dispenser and individually programmable controls.



EAN: 4002516435853 / Material number: 11779650 / Old Material Number: 51632109ZER

| Net weight in kg | 648.0 |
|--|--------------------|
| Gross weight in kg | 699 |
| Maximum floor load in N/m ² | 9206 |
| Emissions data | |
| Emission sound pressure level in the workplace | 73 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 6.10 |
| Features | |
| Patented pre-spin | • |
| Cloth reprocessing | • |
| Imbalance monitoring | • |
| Temperature monitoring | • |
| Special heater element | • |
| Automatic load control+ | • |
| Volumetric flow meter (optional) | • |
| Communication slot | • |
| Emergency switch-off | • |
| Machine-independent accessories | • |
| Efficiency and sustainability | |
| Recycling rate in % | 96 |
| Connection options | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Serial interface module RS 232 (optional) | • |
| Peak-load negotiation / energy management (optional) | • |
| Operating data acquisition | • |
| Water recovery (optional) | • |
| Capacities | |
| Respirator masks [number] | 26 |
| Overalls [number] | 6 |
| Over jackets [number] | 9 |
| Chemical protection suits [number] | 5 |
| Synthetic duvets [number] | 4 |
| Synthetic pillows [number] | 8 |
| Down duvets [number] | 4 |
| Down pillows [number] | 8 |
| Cloths, 22 g [number] | 727 |
| Cotton mops, 40 cm / 190 g [number] | 168 |
| Cotton mops, 50 cm / 220 g [number] | 145 |
| Microfibre mops, 40 cm / 120 g [number] | 267 |
| Microfibre mops, 50 cm / 170 g [number] | 188 |
| Summer horse blankets [number] | 5 |
| Standards, test certificates and symbols | |
| CE | • |
| VDE-EMC | • |
| VDE | • |
| Splash-proof safety rating IPX4 | • |
| WEEE | • |
| RCM | • |
| EAC | • |
| Complies with Machinery Directive 2006/42/EC | • |