Miele

PWM 514 [EL DV DD] Professional washing machine, electric heating with detergent drawer, M Touch Pro.



- Drum volume 130 I, load capacity 14.0 kg
- 14 % less water consumption and 17 % less energy consumption^{*}
- Maximum user convenience with colour touch display M Touch Pro
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

EAN: 4002516435860 / Material number: 11779660 / Old Material Number: 51514001GB

Construction type and version	
Construction type	Front loader
Range	Performance
Front	Iron grey
Control panel colour	Stainless steel
Maximum load with a load ratio of 1:9 in kg	14.0
Load ratio	
Load in kg	14.0
Drum volume in I	130
Door opening [Ø] in mm	415
Door opening angle in degrees	180
Door hinge	right
Automatic door lock	
Innovative suds container	
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in I/kg	7.80
Specific energy consumption for cold water connection in kWh/kg	0.20
Specific water consumption for hot water connection in I/kg	7.20
Specific energy consumption for hot water connection in kWh/kg	0.07
Water consumption with cold water connection in I	109.2
Energy consumption with cold water connection in kW	2.80
Programme duration in minutes with cold water connection	56
Water consumption with hot water connection in I	100.8
Energy consumption with hot water connection in kW	0.98
Programme duration in minutes with cold water and hot water connection	49
Water consumption in ECO programme with cold water connection in I	99.4
Energy consumption in ECO programme with cold water	1.82
	•

^{*} Based on the Coloured items 60 °C programme with a warm water connection, compared to predecessor.



PWM 514 [EL DV DD] Professional washing machine, electric heating with detergent drawer, M Touch Pro.



EAN: 4002516435860 / Material number: 11779660 / Old Material Number: 51514001GB

Programme duration in minutes with cold water connection	40
in ECO programme	
Water consumption in ECO programme with hot water connection in I	98.0
Energy consumption in ECO programme with hot water	0.42
Programme duration in minutes with cold water and hot water connection in ECO programme	36
Residual moisture with cold rinse in %	53
Residual moisture with hot rinse in %	49
Spin speed in rpm	1025
g factor	364
Tested operating hours	30000
Control system	
Control system	M Touch Pro
Programmability	programmable
Max. delay start in h	Freely selectable
Time left display	•
Programme sequence indicator	•
Selectable display languages	•
Option to enter weight prior to start of programme	•
Standard/target grp programmes	
Basic programmes	•
Dispensing	
Detergent drawer	3 compartments
Maximum number of connections for liquid dispenser	12
pumps [number]	
Empty sensor	•
Standard electrical connection	
Heating type	Electric
Electrical connection	3N AC 400V 50HZ
Heater rating in kW	9.00
Total connected load in kW	9.60
Fuse rating in A	16
Possible voltage variant 1	
Electrical connection	3N AC 400V 60HZ
Heater rating in kW	
Treater rating in the	9.00
Total connected load in kW	9.00
Total connected load in kW	9.60
Total connected load in kW Fuse rating in A	9.60
Total connected load in kW Fuse rating in A Water connection/drainage	9.60 16
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th.
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number]	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number]	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, width in mm	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 1350
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, depth in mm	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 1350 799
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, gross height in mm	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 1350 799 995
Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, height in mm External dimensions, depth in mm External dimensions, depth in mm	9.60 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 1350 799 995 1480



PWM 514 [EL DV DD] Professional washing machine, electric heating with detergent drawer, M Touch Pro.



EAN: 4002516435860 / Material number: 11779660 / Old Material Number: 51514001GB

Gross weight in kg	295
Maximum floor load in N/m ²	4453
Emissions data	
Emission sound pressure level in the workplace	67 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	6.48
Features	
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control+	•
Add laundry	•
Programme selection via colour frame	•
Emergency switch-off	•
Machine-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	91
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation / energy management (optional)	•
LAN	•
WiFi	•
Connector Box	•
Capacities	
Synthetic duvets [number]	_ 1
Synthetic pillows [number]	3
Down duvets [number]	_ 1
Down pillows [number]	3
Standards, test certificates and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash-proof safety rating IPX4	•
UKCA	•
WEEE	•
Complies with Machinery Directive 2006/42/EC	•