

PFD 401 DOS [WB SpeedPlus] Freestanding fresh water dishwasher With baskets for hotels, restaurants and catering companies.



- Max. cleaning performance*: 380 plates/h or 20baskets/h
- Easy and safe handing thanks to automatic dispensing
- Versatile processing of two wire or plastic baskets per cycle
- Always the right programme itemspecific solutions
- First-class results thanks to freshwater wash system

EAN: 4002516576921 / Material number: 12066130 / Old Material Number: 61040187GB

Construction type and version	
Construction type	Freestanding dishwasher, front loader
Range	MasterLine
Model	Speedplus
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised
Application	
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for small businesses	•
Suitable for fast food restaurants	•
Suitable for sports clubs	•
Performance data	
Fested virucidal efficacy	•
Proven hygiene	
Circulation pump Qmax in I/min.	390
Shortest programme duration in min.	6
	70
Maximum final rinse temperature in °C	
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	20
Possible to wash plastic baskets on 2 levels	00000
Service life in wash cycles	28000
Miele MOVE	
Network-enabled with Miele MOVE	<u> </u>
Display of machine status and details	•
Receipt of push notifications	<u>•</u>
Assignment of individual machine names	•
_ocation configuration	<u> </u>
Reorder consumables	<u> </u>
Fault management	
Operating data acquisition	<u>•</u>
Self-help function	•
nstallation of remote updates and software updates	•
Control system	
Control system	M Touch Basic
Max. delay start in h	24
Fime left display	•
Programmes [number]	11
Programme sequence indicator	<u> </u>
Choice of display language	•
_anguage-neutral operation	•

^{*} Depending on site conditions (temperature of incoming water / power connection) values given may vary.



PFD 401 DOS [WB SpeedPlus] Freestanding fresh water dishwasher With baskets for hotels, restaurants and catering companies.



EAN: 4002516576921 / Material number: 12066130 / Old Material Number: 61040187GB

Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	5.50
Total connected load in kW	5.90
Fuse rating in A	30-32
Length of mains connection cable in m	1.90
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	2.50
Total connected load in kW	2.90
Fuse rating in A	13
Possible voltage variant 2	
Electrical connection	AC 230V 50HZ
Heater rating in kW	3.00
Total connected load in kW	3.40
Fuse rating in A	16
Water connection/drainage	
-	1
Cold water [number]	1
Hot water [number]	<u> </u>
Required flow pressure in bar	0.40-10.00
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	
Maximum water hardness in mmol/l	10.70
Water protection system	Waterproof system
Water consumption per wash cycle in I	8.00
Length of water inlet hose in cm	170
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions, height in mm	820
External dimensions with lid, height in mm	835
External dimensions, net width in mm	598
External dimensions, net depth in mm	598
External dimensions, gross height in mm	920
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	740
Usable space in wash cabinet, height in mm	559
Usable space in wash cabinet, width in mm	536
Usable space in wash cabinet, depth of upper baske	474
Usable space in wash cabinet, depth of lower basket in mm	516
In-feed height above floor in mm	216
Required niche width in mm	600
Net weight [kg]	75
Gross weight in kg	85
Maximum floor load in N/m ²	1200
Emissions data	
Emissions – sound pressure at workplace	47 dB(A) re 20 μPa
Sound power (LwA) in dB(A) re 1 pW	59.0
Heat dissipation into the room in MJ/h	1.44
Programmes	
Universal	•



PFD 401 DOS [WB SpeedPlus] Freestanding fresh water dishwasher With baskets for hotels, restaurants and catering companies.

Super short



Short Hygiene Cold/Pre-wash Glasses Beer glasses Cutlery Plastics Energy save/Eco Intensive Reactivation Drainage Basket design 2 x E 816 inserts for plates 1 x APFD 215 upper basket 1 x APFD 220 lower basket for inserts 2 x APFD 420 insert for cutlery Height-adjustable upper basket • Combinable with APFD 210 bottle basket Features Drying without 1 combi dispenser in the door for powder cleaning agent and rinsing agent Integrated dispensing pump/dispensing module for liquid cleaning agent Integrated dispensing pump/dispensing module for liquid cleaning agent with fill level indicator Wash cabinet made from high-quality stai In-door salt container Perfect GlassCare Adjustable temperature holding time Adjustable final rinse temperature Optical interface Highly effective filter system with filter monitoring WiFi module A wide range of accessories (optional) **Connection options** External dispensing module for rinse aid

Standards, test certificates and symbols

Splash-protection IPX1 EMC radio suppressed

DIN 10512 DIN EN 17735 Regulation 4 compliant

UKCA

Complies with Machinery Directive 2006/42/EC

EAN: 4002516576921 / Material number: 12066130 / Old Material Number: 61040187GB