

PFD 401 [WB SpeedPlus] Freestanding fresh water dishwasher With baskets for hotels, restaurants and catering companies.



- Max. cleaning performance*: 380 plates/h or 24baskets/h
- Versatile processing of two wire or plastic baskets per cycle
- Excellent user convenience with touch display M Touch Basic
- Always the right programme itemspecific solutions
- First-class results thanks to freshwater wash system

EAN: 4002516577003 / Material number: 12066230 / Old Material Number: 61040115GB

Construction type and design	
Construction type and design	Freestanding dishwasher,
on our doublet type	front loader
Range	MasterLine
Model	Speedplus
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Stainless Steel
Side panels	Stainless steel
Rear panel	Galvanised
Application	
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for guesthouses	•
Suitable for canteens	•
Suitable for offices	•
Suitable for small businesses	•
Suitable for fast food restaurants	•
Suitable for sports clubs	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in I/min.	390
Shortest programme duration in min.	6
Maximum final rinse temperature in °C	70
Cleaning performance, plates/h	380
Cleaning performance, baskets/h	24
Possible to wash plastic baskets on 2 levels	•
Service life in wash cycles	28000
Miele MOVE	
Network-enabled with Miele MOVE	•
Display of machine status and details	•
Receipt of push notifications	•
Assignment of individual machine names	•
Location configuration	•
Reorder consumables	•
Fault management	•
Operating data acquisition	•
Self-help function	•
Installation of remote updates and software updates	•
Controls	
Control system	M Touch Basic
Max. delay start in h	24
Time left display	•
Programmes [number]	11
Programme sequence indicator	•
Choice of display language	•
Language-neutral operation	•

^{*} Depending on site conditions (temperature of incoming water / power connection) values given may vary.



PFD 401 [WB SpeedPlus] Freestanding fresh water dishwasher With baskets for hotels, restaurants and catering companies.

O - Nusi Minhs EAN: 4002516577003 / Material number: 12066230 / Old Material Number: 61040115GB

3N AC 400V 50HZ 3.50 3.90 15-16 1.90 AC 230V 50HZ 3.00 3.40 15-16 1 1 1 0.40-10.00 22
3.50 3.90 15-16 1.90 AC 230V 50HZ 3.00 3.40 15-16 1 1 0.40-10.00 22
3.90 15-16 1.90 AC 230V 50HZ 3.00 3.40 15-16 1 1 0.40-10.00 22
AC 230V 50HZ 3.00 3.40 15-16 1 1 0.40-10.00 22
AC 230V 50HZ 3.00 3.40 15-16 1 1 0.40-10.00 22
AC 230V 50HZ 3.00 3.40 15-16 1 1 0.40-10.00 22
3.00 3.40 15-16 1 1 1 0.40-10.00 22
3.00 3.40 15-16 1 1 1 0.40-10.00 22
3.40 15-16 1 1 0.40-10.00 22
15-16 1 1 0.40-10.00 22 100
1 1 0.40-10.00 22 100
1 0.40-10.00 22 100
1 0.40-10.00 22 100
0.40-10.00 22 100
22 100
100
10.70
Naterproof system
3.00
170
150
320
335
598
598
920
670
740
559
536
174
516
216
600
75
35
1200
47 dB(A) re 20 μPa
59.0
1.44
•
)
)
)
•
•



PFD 401 [WB SpeedPlus] Freestanding fresh water dishwasher With baskets for hotels, restaurants and catering companies.



 ${\sf EAN: 4002516577003 \, / \, Material \, number: \, 12066230 \, / \, Old \, Material \, Number: \, 61040115 GB}$

Beer glasses	•
Cutlery	•
Plastics	•
Energy save/Eco	•
Intensive	•
Reactivation	•
Drainage	•
Basket design	
2 x E 816 inserts for plates	•
1 x APFD 215 upper basket	•
1 x APFD 220 lower basket for inserts	•
2 x APFD 420 insert for cutlery	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•
Features	
Drying	without
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
Wash cabinet made from high-quality stai	•
In-door salt container	•
Perfect GlassCare	•
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Optical interface	•
Highly effective filter system with filter monitoring	•
WiFi module	•
A wide range of accessories (optional)	•
Connection options	
External dispensing module for liquid detergent	•
External dispensing module for rinse aid	•
Standards, certs, symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
Splash-protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
Regulation 4 compliant	•
UKCA	•