

DC 120 WW Professional drying cabinet for particularly gentle drying with two automatic programmes.



- Maximum load size 15 kg,4 ventilation bracket
- Highest efficiency simultaneous drying of all kinds of items
- High utilisation continuous loading with items to be dried
- Best possible protection motionless drying
- Optimum internal and external drying ventilation brackets

EAN: 7330095911541 / Material number: 12173360 / Old Material Number: 52120001EU

Construction type and version	
Construction type	Freestanding appliance
Range	Professional
Front	White
Control panel colour	White
Load size in kg	15
Maximum load capacity	4 protective suits
Door opening angle in degrees	180
Connection for vent ducting, diameter in mm	125
Application	
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Performance data	
Maximum evaporation capacity in g/min	57
Energy consumption per 1 litre evaporated water in kWh	1.90
Shortest programme running time for protective suits in	95
minutes	
Control system	
Control type	Light-touch controls
User interface	Residual moisture
	controlled
Control panel with easy-to-understand symbols	•
Selectable display languages	•
Programmes	
Proofing	•
	_
Normal	
	•
Standard electrical connection	Electric
Standard electrical connection Type of heating	Electric 3N AC 400V 50HZ
Standard electrical connection Type of heating Electrical connection	
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW	3N AC 400V 50HZ
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW	3N AC 400V 50HZ 6.00
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A	3N AC 400V 50HZ 6.00 6.20
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight	3N AC 400V 50HZ 6.00 6.20
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight	3N AC 400V 50HZ 6.00 6.20 10
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm	3N AC 400V 50HZ 6.00 6.20 10
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, net depth in mm	3N AC 400V 50HZ 6.00 6.20 10 1970 1200
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, net depth in mm External dimensions, gross height in mm	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00 1240.00
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Net weight in kg	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00 1240.00 820.00
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00 1240.00 820.00 177.00
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross width in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Emissions data	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00 1240.00 820.00 177.00
Standard electrical connection Type of heating Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm External dimensions, ore the depth in mm External dimensions, gross height in mm External dimensions, gross width in mm External dimensions, gross depth in mm External dimensions, gross depth in mm Net weight in kg Gross weight in kg Emissions data Emission sound pressure level in the workplace	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00 1240.00 820.00 177.00
Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in mm	3N AC 400V 50HZ 6.00 6.20 10 1970 1200 750 2097.00 1240.00 820.00 177.00



DC 120 WW Professional drying cabinet for particularly gentle drying with two automatic programmes.



EAN: 7330095911541 / Material number: 12173360 / Old Material Number: 52120001EU

Glove holders [number]	4
Ventilation brackets [number]	4
Stoppers [number]	2
Capacities	
Protective suits [number]	4
Protective overjackets [number]	4
Standards, test certificates and symbols	
CE	•
EN 60335-2-43	•