

## PDR 511 SL COP HP [EL IGS]

Heat-pump dryers

SlimLine, with time control, for connection to a payment system, 400 V.



- 60 % lower energy consumption than vented dryer\*
- Very easy installation – only 711 mm wide
- Easy to move – direct access underneath
- Shortest cycles thanks to diagonal air flow

\* Heat pump dryers consume up to 60 % less energy than an electrically heated vented dryer.

EAN: 4002516681281 / Material number: 12295740 / Old Material Number: 52511011GB

| Construction type and version                  |                               |
|--|-------------------------------|
| Construction type                              | SlimLine                      |
| Range  | Professional                  |
| Front  | Iron grey                     |
| Fascia color                                   | Stainless steel               |
| Load in kg                                     | 11.0                          |
| Load size with a load ratio of 1:25            | 8.0                           |
| Load size with a load ratio of 1:18            | 11.0                          |
| Load ratio                                     | 1:18                          |
| Drum volume in l                               | 200.00                        |
| Drying system                                  | Heat pump                     |
| Door opening [Ø] in mm                         | 520                           |
| Door opening angle in degrees                  | 180                           |
| Door hinge                                     | left                          |
| Stainless steel drum                           | •                             |
| Stainless steel honeycomb drum                 | No                            |
| Application                                    |                               |
| Suitable for laundrettes                       | •                             |
| Performance data                               |                               |
| Maximum evaporation capacity in l/hour         | 4.50                          |
| Specific energy consumption in kWh/kg          | 0.22                          |
| Programme duration in min.                     | 59                            |
| Control system                                 |                               |
| Control system                                 | M Select Benchmark            |
| Programmability                                | Setting of defined parameters |
| User interface                                 | time-controlled               |
| Time left display                              | •                             |
| Programme sequence indicator                   | •                             |
| Control panel with easy-to-understand symbols  | •                             |
| Standard electrical connection                 |                               |
| Heating type                                   | Heat pump with CleanStream    |
| Electrical connection                          | 3N AC 400V 50HZ               |
| Heater rating, heat pump in kW                 | 6.40                          |
| Total connected load in kW                     | 3.00                          |
| Fuse rating in A                               | 16                            |
| Dimensions and weight of dryer                 |                               |
| External dimensions, height in mm              | 1800                          |
| External dimensions, width in mm               | 711                           |
| External dimensions, depth in mm               | 1075                          |
| External dimensions, gross height in mm        | 1810                          |
| External dimensions, gross width in mm         | 800                           |
| External dimensions, gross depth in mm         | 1180                          |
| Net weight in kg                               | 192.7                         |
| Gross weight in kg                             | 213                           |
| Maximum floor load in N/m <sup>2</sup>         | 2052                          |
| Emissions data                                 |                               |
| Emission sound pressure level in the workplace | 55 dB(A) re 20 µPa            |
| Heat dissipation into the room in MJ/h         | 2.30                          |

## PDR 511 SL COP HP [EL IGS]

Heat-pump dryers

SlimLine, with time control, for connection to a payment system, 400 V.



EAN: 4002516681281 / Material number: 12295740 / Old Material Number: 52511011GB

| <b>Features</b>  |       |
|--|-------|
| Intelligent drum reversal                                    | •     |
| Large-surface fluff filter                                   | •     |
| SoftLift drum ribs   | •     |
| Retractable plinth   | •     |
| Communication slot   | •     |
| Machine-independent accessories                              | •     |
| <b>Efficiency and sustainability</b>                         |       |
| Contains fluorinated greenhouse gases                        | •     |
| Hermetically sealed system                                   | •     |
| Coolant  | R450a |
| Refrigerant quantity in kg                                   | 1.35  |
| Refrigerant global warming potential in kg CO <sub>2</sub> e | 605   |
| Appliance global warming potential in kg CO <sub>2</sub> e   | 877   |
| <b>Connection options</b>                                    |       |
| Payment system (optional)                                    | •     |
| Optical interface for service access                         | •     |
| Peak load cut-out/energy management (optional)               | •     |
| WiFi tumble dryer  | •     |
| Connector Box  | •     |
| LAN module (optional)  | •     |
| <b>Standards, test certificates and symbols</b>              |       |
| CE   | •     |
| VDE  | •     |
| VDE-EMC  | •     |
| Splash-proof safety rating IPX4                              | •     |
| WEEE   | •     |
| UKCA   | •     |
| Complies with Machinery Directive 2006/42/EC                 | •     |