

## PDR 908 HP P [EL] Professional heat-pump dryer, Little Giants With very low energy consumption and short running times. Load capacity 8.0 kg.



- Drum volume 130.00 l, load capacity 8.0 kg
- 50 % less energy consumption than vented dryers\*
- Even more sustainable heat pump with propane as a refrigerant
- Max. user convenience, full-touch colour display M Touch Flex
- Future-proof networking via WiFi \* Heat pump dryers consume up to 50 % less energy than an electrically heated vented dryer.

| EAN: 4002516870647 / Material number: 12752600 / |
|--|
| Old Material Number: 52908163GB                  |
|  |

| Construction type and version  |                         |
|--|-------------------------|
| Construction type and version  | Front loodor stackable  |
| Construction type  | Front-loader, stackable |
| Range  | Performance Plus        |
| Front  | Lotus white             |
| Fascia color   | Stainless steel         |
| Load in kg   | 8.0                     |
| Drum volume in l   | 130.00                  |
| Drying system  | Heat pump               |
| Door opening [Ø] in mm   | 370                     |
| Door opening angle in degrees  | 167                     |
| Door hinge   | left                    |
| Stainless steel honeycomb drum   | Yes                     |
| Application  |                         |
| Suitable for the hotel and catering industry   | •                       |
| Suitable for retirement and care homes   | •                       |
| Suitable for facility management   | •                       |
| Suitable for launderettes  | •                       |
| Suitable for residential homes and apartments  | •                       |
| Suitable for dry cleaners  | •                       |
| Suitable for commercial laundries  | •                       |
| Suitable for small businesses  | •                       |
| Suitable for universities, nurseries, and schools  | •                       |
| Suitable for hospitals   | •                       |
| Suitable for camp sites  | •                       |
| Suitable for sports clubs  | •                       |
| Suitable for beauty salons, spas, and fitness centres  | •                       |
| Suitable for doctors' and dentists' practices  | •                       |
| Suitable for the petrochemicals industry   | •                       |
| Suitable for the food-processing industry  | •                       |
| Suitable for amusement parks & holiday complexes   | •                       |
| Suitable for state/community care facilities   | •                       |
| Performance data   |                         |
| Maximum evaporation capacity in I/hour   | 31                      |
| Specific energy consumption in kWh/kg  | 0.20                    |
| Specific energy consumption for Cottons/Normal drying  | 0.20                    |
| programme with residual moisture at 48 % in kW   | 0.20                    |
| Specific energy consumption for mixed fibre fabrics/Normal   | 0.17                    |
| drying programme with residual moisture a  | 0.11                    |
| Programme duration in min.   | 77                      |
| Programme duration for Cottons/Normal drying programme   | 77                      |
| with residual moisture at 48 % in minutes  |                         |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in | 67                      |
| Control system   |                         |
| Control system   | M Touch Flex            |
| Programmability  | programmable            |
| User interface   | Residual moisture       |
|  | controlled              |



## PDR 908 HP P [EL] Professional heat-pump dryer, Little Giants With very low energy consumption and short running times. Load capacity 8.0 kg.



| Fime left display                               | •                   |
|---|---------------------|
| Programme sequence indicator                    | •                   |
| Language can be selected easily at any time     | •                   |
| Standard electrical connection                  |                     |
| Heating type                                    | Heat pump           |
| Electrical connection                           | 220-240V~ 50HZ      |
| Total connected load in kW                      | 1.44                |
| Fuse rating in A                                | 13                  |
| Dimensions and weight of dryer                  |                     |
| External dimensions, height in mm               | 850                 |
| External dimensions, width in mm                | 596                 |
| External dimensions, depth in mm                | 777                 |
| External dimensions, gross height in mm         | 940                 |
| External dimensions, gross width in mm          | 660                 |
| External dimensions, gross depth in mm          | 820                 |
| Net weight in kg                                | 71.0                |
| Gross weight in kg                              | 77                  |
| Maximum floor load in N                         | 920                 |
| Emissions data                                  |                     |
| Emission sound pressure level in the workplace  | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h          | 3.60                |
| Features  |                     |
| Intelligent drum reversal                       | •                   |
| Axial airflow                                   | •                   |
| Fluff filter in the door                        | •                   |
| Low-maintenance heat exchanger filter system    | •                   |
| PerfectDry                                      | •                   |
| SoftLift drum ribs                              | •                   |
| Gentle tumble function                          | •                   |
| Condensed water drainage                        | •                   |
| Communication slot                              | •                   |
| Drying basket (optional)                        | •                   |
| Drum lighting                                   | •                   |
| Machine-independent accessories                 | •                   |
| Efficiency and sustainability                   |                     |
| Hermetically sealed system                      | •                   |
| Coolant   | R290                |
| Refrigerant quantity in kg                      | 0.14                |
| Refrigerant global warming potential in kg CO2e | 3                   |
| Appliance global warming potential in kg CO2e   | 0.45                |
| Connection options                              |                     |
| Payment system (optional)                       | •                   |
| Optical interface for service access            | •                   |
| WiFi  | •                   |
| LAN module (optional)                           | •                   |
| WiFiConn@ct                                     | •                   |
| Standards, test certificates and symbols        |                     |
| CE  | •                   |



## PDR 908 HP P [EL] Professional heat-pump dryer, Little Giants With very low energy consumption and short running times. Load capacity 8.0 kg.



EAN: 4002516870647 / Material number: 12752600 / Old Material Number: 52908163GB

| VDE  | • |
|--|---|
| VDE-EMC                                      | • |
| Splash-proof safety rating IPX4              | • |
| WEEE   | • |
| UKCA   | • |
| Complies with Machinery Directive 2006/42/FC | • |

Complies with Machinery Directive 2006/42/EC