

PDR 908 HP P [EL]

Professional heat-pump dryer, Little Giants

With very low energy consumption and short running times. Load capacity 8.0 kg.



- Drum volume 130.00 l, load capacity 8.0 kg
- 50 % less energy consumption than vented dryers*
- Even more sustainable heat pump with propane as a refrigerant
- Max. user convenience, full-touch colour display — M Touch Flex
- Future-proof networking via WiFi

EAN: 4002516870760 / Material number: 12752620 / Old Material Number: 52908263GB

Old Material Number: 52908263GB	
Construction type and version	
Construction type	Front-loader, stackable
Range	Performance Plus
Front	Stainless steel
Fascia color	Stainless steel
Load in kg	8.0
Drum volume in I	130.00
Drying system	Heat pump
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for launderettes	•
Suitable for residential homes and apartments	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemicals industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in I/hour	31
Specific energy consumption in kWh/kg	0.20
Specific energy consumption for Cottons/Normal drying	0.20
programme with residual moisture at 48 % in kW	
Specific energy consumption for mixed fibre fabrics/Normal	0.17
drying programme with residual moisture a	
Programme duration in min.	77
Programme duration for Cottons/Normal drying programme with residual moisture at 48% in minutes	77
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in	67
Control system	
Control system	M Touch Flex
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
. Take dollay occirc in in	

 $^{^{\}star}$ Heat pump dryers consume up to 50 % less energy than an electrically heated vented dryer.



PDR 908 HP P [EL]

Professional heat-pump dryer, Little Giants

With very low energy consumption and short running times. Load capacity 8.0 kg.



EAN: 4002516870760 / Material number: 12752620 / Old Material Number: 52908263GB Time left display Programme sequence indicator Language can be selected easily at any time Standard electrical connection Heating type Heat pump 220-240V~ 50HZ Electrical connection Total connected load in kW Fuse rating in A Dimensions and weight of dryer External dimensions, height in mm 850 External dimensions, width in mm 605 External dimensions, depth in mm 777 940 External dimensions, gross height in mm 660 External dimensions, gross width in mm 820 External dimensions, gross depth in mm Net weight in kg 67.0 Gross weight in kg 72 920 Maximum floor load in N **Emissions data** Emission sound pressure level in the workplace <70 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 3.60 **Features** Intelligent drum reversal Axial airflow Fluff filter in the door Low-maintenance heat exchanger filter system PerfectDry SoftLift drum ribs Gentle tumble function Condensed water drainage Communication slot Drying basket (optional) Drum lighting Machine-independent accessories Efficiency and sustainability Hermetically sealed system Coolant R290 0.14 Refrigerant quantity in kg Refrigerant global warming potential in kg CO2e 3 Appliance global warming potential in kg CO2e 0.45 Connection options Payment system (optional) Optical interface for service access WiFi LAN module (optional) WiFiConn@ct Standards, test certificates and symbols CE



PDR 908 HP P [EL]

Professional heat-pump dryer, Little Giants

With very low energy consumption and short running times. Load capacity 8.0 kg.



	·002516870760 / Material number: 12752620 / sterial Number: 52908263GB	
VDE		•
VDE-E	EMC	•
Splash	n-proof safety rating IPX4	•
WEEE		•
TIKCA		•

Complies with Machinery Directive 2006/42/EC