

PDR 307 HP P [EL]

Professional heat-pump dryer, Little Giants

For simple and flexible installation without vent ducting.



- Drum volume 130.00 l, load capacity 7.0 kg
- 50 % less energy consumption than vented dryers*
- Even more sustainable heat pump with propane as a refrigerant
- M Select control unit with a wide range of standard programmes
- Future-proof networking via WiFi

EAN: 4002516870906 / Material number: 12752650 /

Old Material Number: 52307161GB	
Construction type and version	
Construction type	Front-loader, stackable
Range	Evolution
Front	Lotus white
Fascia color	Stainless steel
Load in kg	7.0
Drum volume in I	130.00
Drying system	Heat pump
Door opening [Ø] in mm	370
Door opening angle in degrees	167
Door hinge	left
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for residential homes and apartments	+
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centres	•
Suitable for domestic use	•
Suitable for amusement parks & holiday complexes	•
Suitable for state/community care facilities	•
Performance data	
Maximum evaporation capacity in I/hour	31
Specific energy consumption in kWh/kg	0.20
Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW	0.20
Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture a	0.17
Programme duration in min.	67
Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes	67
Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in	60
Control system	
Control system	M Select
Programmability	programmable
User interface	Residual moisture controlled
Max. delay start in h	24
Time left display	+
Programme sequence indicator	+
Control panel with easy-to-understand symbols	•
Language can be selected easily at any time	+
Standard/target grp programmes	
Basic programmes	•
Standard electrical connection	
	Heat pump

 $^{^{\}ast}$ Heat pump dryers consume up to 50 % less energy than an electrically heated vented dryer.



PDR 307 HP P [EL]

Professional heat-pump dryer, Little Giants

For simple and flexible installation without vent ducting.



EAN: 4002516870906 / Material number: 12752650 / Old Material Number: 52307161GB

Old Material Number: 52307161GB	
Electrical connection	220-240V~ 50HZ
Total connected load in kW	1.44
Fuse rating in A	13
Dimensions and weight of dryer	
External dimensions, height in mm	850
External dimensions, width in mm	596
External dimensions, depth in mm	777
External dimensions, gross height in mm	940
External dimensions, gross width in mm	660
External dimensions, gross depth in mm	820
Net weight in kg	65.5
Gross weight in kg	70
Maximum floor load in N	920
Emissions data	
Emission sound pressure level in the workplace	<70 dB(A) re 20 μPa
Heat dissipation into the room in MJ/h	3.60
Features	
Intelligent drum reversal	•
Axial airflow	•
Fluff filter in the door	•
Low-maintenance heat exchanger filter system	•
PerfectDry	•
SoftLift drum ribs	•
Gentle tumble function	•
Condensed water drainage	•
Drying basket (optional)	•
Drum lighting	•
Machine-independent accessories	•
Efficiency and sustainability	
Hermetically sealed system	•
Coolant	R290
Refrigerant quantity in kg	0.14
Refrigerant global warming potential in kg CO2e	3
Appliance global warming potential in kg CO2e	0.45
Connection options	0.10
Payment system (optional)	
Optical interface for service access	•
WiFi	•
LAN module (optional)	•
WiFiConn@ct	•
Standards, test certificates and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
Complies with Machinery Directive 2006/42/EC	•