


O 175 Upper basket for the optimum loading of laboratory glassware.





- Suitable for narrow-neck and laboratory glassware
- Vertical clearance: 6 3/4 (170) in (mm) mm^{*}
- Equipped with connection for hot air drying
- Powder dispensing not possible

Depending on the laboratory glassware the max. vertical clearance can be lower

Washer-disinfectors, laboratory	•
Machine affiliation	
PG 8535	•
PG 8536	•
Product category	
Insert/module for narrow-neck glassware	•
Injector basket	•
Upper basket	•
Product characteristics	
Material	Stainless steel
Color	Stainless Steel
Maximum vertical clearance in mm	6 3/4 (170)
Application area	
Reprocessing of laboratory glassware	•
Capacity	
Narrow-neck glassware [number]	33
Standard electrical connection	
Number of phases	0
Voltage in V	0
Frequency in Hz	0
Total rated load in kW	0.00
Fuse rating in A	0
Dimensions and weight	
External dimensions, net height in inches	16 1/4 (412)
External dimensions, net width in inches	18 3/4 (475)
External dimensions, net depth in inches	20 15/16 (531)
External dimensions, gross height in inches	10 11/16 (270)
External dimensions, gross width in inches	20 11/16 (525)
External dimensions, gross depth in inches	21 5/16 (540)
Net weight in lbs	14 (6.30)
Gross weight in lbs	16 (7.20)
Accessory pack	
E 351 injector nozzle, Ø 3/16" (4 mm), length 6 5/16" (160 mm) [number]	33
E 353 clip for injector nozzle E 351 [number]	33