


E 352 Injector nozzle for the optimum cleaning of the wash items.





- Suitable for use in a mobile injector unit
- Can be combined with clip E 354
- Ø 6 x 220 mm, screw connection

Product category	
Washer-disinfectors, laboratory	•
Large-capacity washer-disinfectors, laboratory	•
Machine affiliation	
G 7825	•
PG 8527	•
PG 8535	•
PG 8536	•
PG 8504	•
PG 8583	•
PG 8583 CD	•
PG 8593	•
Product category	
Injector nozzle	•
Product characteristics	
Material	Stainless steel
Color	Stainless Steel
A contraction to a contraction	
Application area	
Reprocessing of laboratory glassware	•
Reprocessing of laboratory glassware	0
Reprocessing of laboratory glassware Standard electrical connection	0 0
Reprocessing of laboratory glassware Standard electrical connection Number of phases	
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V	0
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz	0 0
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW	0 0 0.00
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A	0 0 0.00
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight	0 0 0.00 0
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in inches	0 0 0.00 0 8 11/16 (220) in (mm)
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in inches External dimensions, net width in inches	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm)
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, net depth in inches	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm)
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, net depth in inches External dimensions, gross height in inches	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm) 9 1/16 (230)
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross height in inches External dimensions, gross width in inches	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm) 9 1/16 (230) 0 13/16 (20)
Reprocessing of laboratory glassware Standard electrical connection Number of phases Voltage in V Frequency in Hz Total rated load in kW Fuse rating in A Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches	0 0 0.00 0 8 11/16 (220) in (mm) 0 7/16 (10) in (mm) 0 7/16 (10) in (mm) 9 1/16 (230) 0 13/16 (20) 1 3/16 (30)