Míele

PW 6080 Vario [EL AV] Washing machine, electric heating with suspended drum unit, shortest program runtime of 53 min and drain valve.



- Drum volume 2.83 (80) ft³ (I), load size 18 (8.0) lb (kg)
- Large program variety applicationspecific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 44 %*, g-factor520
- * Residual moisture specification relates to a hot rinse during the last rinse cycle.

EAN: 4002515127322 / Material number: 09292330 / Old Material Number: 51608066USA

Old Material Number: 51608066USA	
Construction type and design	
Design	Front loader
Product line	Octoplus
Front	Octo Blue
Load ratio	1:10
Load in lbs	18 (8.0)
Drum volume in cubic feet (I)	2.83 (80)
Door opening $[\emptyset]$ in in.(mm)	14 5/8 (370)
Door opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Stainless steel honeycomb drum	•
Application	
Suitable for hotels and restaurants	•
Suitable for senior living facilities	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centers	•
Suitable for doctors' and dentists' practices	•
Performance data	
Specific water consumption for hot water connection in I/	8.25
kg	
Specific energy consumption for hot water connection in kWh/lb	0.06
Program duration in minutes with cold water connection	57
Program duration in minutes with hot water connection	53
Residual moisture with cold rinse in %	49
Residual moisture with hot rinse in %	44
Spin speed in rpm	1300
g factor	520
Tested operating hours	30000
Control	
Control system	Profitronic L Vario
Control system Programmability	Profitronic L Vario programmable
,	
Programmability	programmable
Programmability Max. delay start in h	programmable 24
Programmability Max. delay start in h Countdown indicator	programmable 24
Programmability Max. delay start in h Countdown indicator Program sequence indicator	programmable 24 •
Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language	programmable 24 •
Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Standard/target group programs	programmable 24 •
Programmability Max. delay start in h Countdown indicator Program sequence indicator Choice of display language Standard/target group programs Basic programmes	programmable 24 • • •

Míele

PW 6080 Vario [EL AV] Washing machine, electric heating with suspended drum unit, shortest program runtime of 53 min and drain valve.



EAN: 4002515127322 / Material number: 09292330 / Old Material Number: 51608066USA	
Programmes for facility management	
Programmes for launderettes	
Programmes for residential homes and apartments	
Programmes for dry cleaners	
Programmes for commercial laundries	*
Programmes for small businesses	*
Programmes for fire brigades and rescue services	<u>*</u>
Programmes for studs, riding schools, and stables	
Programmes for universities, nurseries, and school	•
Programmes for hospitals	•
Programmes for fast food restaurants	•
Programmes for camp sites	•
Programmes for sports clubs	*
Programmes for beauty clinics, spas, and fitness studios	•
Programmes for domestic use	•
Programmes for doctors' and dentists' practices	+
Dispensing	
Detergent dispenser drawer	3 compartments
Patented liquid dispensing adapter	•
Maximum number of connections for liquid dispenser pumps [number]	6
Empty sensor	•
Standard electrical connection	
Type of heating	Electric
Electrical connection	2 AC 220-240V 60HZ
Heater rating in kW	4.20-5.00
Total connected load in kW	4.40-5.20
Fuse rating in A	30
NEMA plug: Twist Lock L6-30	•
Possible voltage variant 1	
Electrical connection	2 AC 208V 60HZ
Heater rating in kW	3.80
Total connected load in kW	4.00
Fuse rating in A	30
Water connection/drainage	
Cold water [number]	1x 1/2" hose w/ 3/4" th.
Hot water [number]	1x 1/2" hose w/ 3/4" th.
Grey water (optional) [number]	union 1 x 1/2" w/ 3/4" union
	DN 70
Dump valve	DN 70
Dimensions and weight External dimensions, not height in inches	40.2/16 (1020)
External dimensions, net height in inches	40 3/16 (1020)
External dimensions, net width in inches	27 9/16 (700)
External dimensions, net depth in inches	28 5/8 (727)
External dimensions, gross height in inches	47 7/8 (1215)
External dimensions, gross width in inches	29 15/16 (760)
External dimensions, gross depth in inches	32 5/16 (820)
Net weight in lbs.(kg)	309 (140.0)



PW 6080 Vario [EL AV] Washing machine, electric heating with suspended drum unit, shortest program runtime of 53 min and drain valve.



EAN: 4002515127322 / Material number: 09292330 / Old Material Number: 51608066USA Gross weight in lbs. 327 (148) Maximum floor load in N 2600 **Emission values** Emissions – sound pressure at workplace <70 dB(A) re 20 µPa Heat dissipation into the room in MJ/h 3.00 **Features** Patented cleaning cloth program Imbalance monitoring Disinfection rinse Temperature monitoring Special heater element Automatic load control Volumetric flow meter Communication slot Appliance-independent accessories Efficiency and sustainability Recycling rate in %95 Connection options Payment system Optical interface for service access ٠ Serial interface module RS 232 (optional) Peak-load negotiation / energy management (optional) Capacities Respirator masks [number] 4-5 Overalls [number] 1 Over jackets [number] 1-2 Synthetic duvets [number] Synthetic pillows [number] 1-2 Feather duvets [number] Feather pillows [number] 1-2 Cloths, 22 g/0.8 oz[number] 182 Cotton mops, 40 cm/15.7 in[number] Cotton mops, 50 cm/19.7 in[number] 36 Microfibre mops, 40 cm/15.7 in [number]] 66 Microfibre mops, 50 cm/19.7 in [number] 47 Summer horse blankets [number] 1-2 Standards, test certificates, and symbols Splash protection IPX4

Complies with Machinery Directive 2006/42/EC