## Miele

PW 5105 Vario [EL AV]
Washing machine, electric heating
with suspended drum unit, shortest program runtime of 53 min and drain valve.



- Drum volume 3.53 (100) ft<sup>3</sup> (l), load size 23 (10.0) lb (kg)
- Large program variety application-specific wash programs
- Gentle laundry care thanks to the Miele honeycomb drum
- Particularly efficient low water and energy consumption
- Perfect spinning results residual moisture 50 %\*, g-factor370

EAN: 4002515127414 / Material number: 09292420 / Old Material Number: 51510566USA

Model and design	
Design	Front loader
Product line	Octoplus
Front	Octo blue
Load ratio	1:10
Load in lbs	23 (10.0)
Drum volume in cubic feet (I)	3.53 (100)
Door opening [Ø] in in.(mm)	14 5/8 (370)
Door opening angle in degrees	180
Door hinging	right
Maintenance-free motor with frequency converter	•
Honeycomb drum	•
Application	
Suitable for the hotel and catering industry	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas, and fitness centers	•
Performance data	
Specific water consumption for hot water connection in I/kg	8.00
Specific energy consumption for hot water connection in kWh/lb	0.06
Program duration in minutes with cold water connection	58
Program duration in minutes with hot water connection	53
Residual moisture with cold rinse in %	54
Residual moisture with hot rinse in %	50
	1100
Spin speed in rpm	370
g factor Tested operating hours	30000
Controls	30000
Control system	Profitronic L Vario
Programmability	programmable
Max. delay start in h	24
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Standard/target group programs	
Basic programmes	•
	•
Programmes for the hotel and catering industry  Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for launderettes	•
Programmes for residential homes and apartments	•
Programmes for dry cleaners	•
rrogrammes for dry deaners	

<sup>\*</sup> Residual moisture specification relates to a hot rinse during the last rinse cycle.

## Míele

PW 5105 Vario [EL AV]
Washing machine, electric heating
with suspended drum unit, shortest program runtime of 53 min and drain valve.



EAN: 4002515127414 / Material number: 09292420 / Old Material Number: 51510566USA

Programmes for commercial laundries	•
Programmes for small businesses	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Programmes for universities, nurseries, and school	•
Programmes for hospitals	•
Programmes for fast food restaurants	•
Programmes for camp sites	•
Programmes for sports clubs	•
Programmes for beauty clinics, spas, and fitness studios	•
Programmes for domestic use	•
Programmes for doctors' and dentists' practices	•
Dispensing	
Detergent dispenser drawer	3 compartments
Patented liquid dispensing adapter	•
Maximum number of connections for liquid dispenser	
pumps [number]	Ü
Empty sensor	•
Standard electrical connection	
Type of heating	Electric
Electrical connection	2 AC 220-240V 60HZ
Heater rating in kW	4.20-5.00
Total connected load in kW	4.40-5.20
Fuse rating in A	30
NEMA plug: Twist Lock L6-30	•
Possible voltage variant 1	
Possible voltage variant 1  Electrical connection	2 AC 208V 60H7
Electrical connection	2 AC 208V 60HZ 3 80
Electrical connection Heater rating in kW	3.80
Electrical connection Heater rating in kW Total connected load in kW	3.80 4.00
Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A	3.80
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage	3.80 4.00 30
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	3.80 4.00
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage	3.80 4.00 30 1x 1/2" hose w/ 3/4" th.
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th.
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number]	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Grey water (optional) [number] Dump valve	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number]  Dump valve  Dimensions and weight	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net width in inches	3.80 4.00 30 1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70 40 3/16 (1020)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, net depth in inches	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net width in inches	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Grey water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross height in inches	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215) 29 15/16 (760)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number]  Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number]  Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215) 29 15/16 (760) 36 1/16 (915)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches Net weight in lbs.(kg) Gross weight in lbs.	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215) 29 15/16 (760) 36 1/16 (915) 327 (148.0) 351 (159)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches Met weight in lbs. Maximum floor loading in N	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215) 29 15/16 (760) 36 1/16 (915) 327 (148.0)
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number]  Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215) 29 15/16 (760) 36 1/16 (915) 327 (148.0) 351 (159) 2750
Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number]  Hot water [number]  Grey water (optional) [number]  Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net depth in inches External dimensions, gross height in inches External dimensions, gross width in inches External dimensions, gross width in inches External dimensions, gross depth in inches Net weight in lbs. Maximum floor loading in N	3.80 4.00 30  1x 1/2" hose w/ 3/4" th. union 1x 1/2" hose w/ 3/4" th. union 1 x 1/2" w/ 3/4" union DN 70  40 3/16 (1020) 27 9/16 (700) 32 9/16 (827) 47 7/8 (1215) 29 15/16 (760) 36 1/16 (915) 327 (148.0) 351 (159)



PW 5105 Vario [EL AV]
Washing machine, electric heating
with suspended drum unit, shortest program runtime of 53 min and drain valve.



EAN: 4002515127414 / Material number: 09292420 / Old Material Number: 51510566USA

Features	
Patented cleaning cloth program	•
Imbalance monitoring	•
Disinfection rinse	•
Temperature monitoring	•
Special heater element	•
Automatic load control	•
Volumetric flow meter	•
Communication slot	•
Appliance-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	95
Connection options	
Payment system	•
Optical interface for service access	•
Serial interface module RS 232 (optional)	•
Peak load cut-out/energy management (optional)	•
Capacities	
Respirator masks [number]	7
Overalls [number]	1-2
Over jackets [number]	2
Synthetic duvets [number]	1
Synthetic pillows [number]	2
Feather duvets [number]	1
Feather pillows [number]	2
Cloths, 22 g/0.8 oz[number]	227
Cotton mops, 40 cm/15.7 in[number]	53
Cotton mops, 50 cm/19.7 in[number]	45
Microfibre mops, 40 cm/15.7 in [number]]	80
Microfibre mops, 50 cm/19.7 in [number]	55
Summer horse blankets [number]	2
Standards/certificates/symbols	
Splash protection IPX4	•
Complies with Machinery Directive 2006/42/EC	•