

DAR 1130 36-inch extractor unit for perfect combination with Ranges and Rangetops.




- Customized kitchen design fully integrated in 33 1/2 (850) in (mm)
- Perfect illumination LED ClearView lighting
- Dishwasher-safe 3 high-quality stainless steel grease filters
- Safe and easy to clean Miele CleanCover
- Auto-vent safety sensor protects against overheating

EAN: 4002515446812 / Material number: 09753480 / Old Material Number: 28113050USA

| Design | |
|--|--------------|
| Insert ventilation hood | • |
| Required accessories | |
| Blower | • |
| Operating modes | |
| Recirculated mode | Exhaust air |
| External operation possible | • |
| User convenience | |
| Rotary knob | • |
| Power levels (number excl. Intensive) | 3 |
| Temperature sensor | |
| CleanCover | • |
| Cleaning convenience | |
| Dishwasher-safe grease collection channel | • |
| Filter system | |
| Number of dishwasher-safe stainless steel baffle filters | 3 |
| Lighting | |
| LED | • |
| Number x W | 3 x 3 W |
| Fan option (buy separately) | 3 x 3 W |
| DRIB XL internal blower in CFM (m³(h) | 1189 |
| DRIB XXL internal blower in CFM (m³/h) | 1869 |
| DREB XL external blower in CFM (m³/h) | 1189 |
| DREB XXL external blower in CFM (m³/h) | 1869 |
| Technical data | 1009 |
| Canopy width in in.(mm) | 33 1/2 (850) |
| Canopy width in inches | 35 15/16 |
| | 17 3/4 (449) |
| Canopy depth in in.(mm) | 22 7/8 (579) |
| Canopy depth in in.(mm) | 42 (19.0) |
| Net weight in lbs. (kg) | |
| Length of electrical wire in ft (m) | 2 (0.8) |
| Standard plug fitted Total connected load in kW | 0.80 |
| | |
| Voltage in V | <u>120</u> |
| Fuse rating in A | <u>15</u> |
| Number of phases | |
| Installation note | |
| Vent connection at top | 0.7/0./050) |
| Diameter of vent connection in in.(mm) | 9 7/8 (250) |
| Standard accessories | |
| Non-return flap | • |



DAR 1130 36-inch extractor unit for perfect combination with Ranges and Rangetops.



DAR1130 (installation drawing)