

PT 8807 HW [PTM ARP]

Vented dryer, heated with hot water

With individually programmable controls and future-oriented heating method.



- Drum volume 28.25 (800.00) ft³ (l), load size 25.0-32.0 kg
- Unique, gentle fabric care – patented honeycomb drum
- Greatest energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics – PerfectDry
- Highest efficiency thanks to innovative hot water heating

EAN: 4002515480663 / Material number: 09906750 / Old Material Number: 52880775USA

Model and design	
Design	Front loader
Linie	Professional
Front	Stainless steel
Load in lbs.(kg)	25.0-32.0
Fill ratio	1:32-1:25
Drum volume in ft ³ (l)	28.25 (800.00)
Drying system	Hot water
Door opening [Ø] in in.(mm)	20 1/2 (520)
Door opening angle in degrees	180
Door hinging	left
Convertible hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fit ness centers	•
Performance data	
Program cycle in min.	54
Tested operating hours	20000
Controls	
Control system	Profitronic M
Programmability	Freely programmable
Program controls	Residual moisture controlled
Max. delay start in h	Can be selected freely
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Standard/target group programs	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Standard electrical connection	
Type of heating	Hot water
Electrical connection	3 AC 208V 60HZ
Electric heater rating in kW	0.00
Heater rating, hot water in kW	12.50

PT 8807 HW [PTM ARP]

Vented dryer, heated with hot water

With individually programmable controls and future-oriented heating method.



EAN: 4002515480663 / Material number: 09906750 / Old Material Number: 52880775USA

Total connected load in kW	1.90
Fuse rating in A	10
Minimum water intake temperature in °F	70
Maximum water intake temperature in °F	90
Volume in m³/h	0.3-1.5
Dimensions and weight	
External dimensions, net height in inches	64 5/8 (1640)
External dimensions, net width in inches	47 1/2 (1206)
External dimensions, net depth in inches	54 1/2 (1384)
External dimensions, gross height in inches	69 9/16 (1766)
External dimensions, gross width in inches	54 3/4 (1390)
External dimensions, gross depth in inches	58 1/16 (1474)
Net weight in lbs. (kg)	702 (318.0)
Gross weight in lbs. (kg)	768 (348)
Maximum floor loading in N	3708
Emissions data	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat output to the room in MJ/h and BTUs /h	3.98
Features	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Low temperature function	•
Communication slot	•
Emergency shut off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Serial interface RS 232 (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
Operating data acquisition	•
Capacities	
Respirator masks [number]	16
Standard and target group programs	6
Over jackets [number]	9
Synthetic duvets [number]	4
Synthetic pillows [number]	8
Feather duvets [number]	4
Feather pillows [number]	8
Cloths, 22 g/0.8 oz [number]	727
Cotton mops, 40 cm [number]	168
Cotton mops, 50 cm [number]	145
Microfibre mops, 40 cm [number]	267
Microfibre mops, 50 cm [number]	188
Summer horse blankets [number]	4-5
Standards/certificates/symbols	
CE	•

PT 8807 HW [PTM ARP]

Vented dryer, heated with hot water

With individually programmable controls and future-oriented heating method.



EAN: 4002515480663 / Material number: 09906750 / Old Material Number: 52880775USA

Splash-proof safety rating IPX4

Complies with Machinery Directive 2006/42/EC

•
•