

PT 8337 [PTM EL BSS ARP]

Vented dryer, electric heating

With individually programmable controls for the maximum in flexibility.



- Drum volume 11.48 (325.00) ft<sup>3</sup> (l), load size 13.0-16.0 kg
- Unique, gentle fabric care – patented honeycomb drum
- Greatest energy efficiency thanks to Air Recycling Plus
- Precision drying of all fabrics – PerfectDry
- Simple operation – easy to clean large fluff filter

EAN: 4002515528457 / Material number: 09986710 / Old Material Number: 52833705USA

Construction type and design	
Design	Front loader
Linie	Professional
Front	Stainless Steel
Load in lbs.(kg)	13.0-16.0
Fill ratio	1:25-1:20
Drum volume in ft <sup>3</sup> (l)	11.48 (325.00)
Drying system	Exhaust air
Door opening [Ø] in in.(mm)	20 1/2 (520)
Door opening angle in degrees	180
Door hinging	left
Convertible hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for fire brigades and rescue services	•
Suitable for studs, riding schools and stables	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fitness centers	•
Performance data	
Maximum evaporation capacity in l/hour and gal. qts./hour	18 (18) gal (US)/min (l)
Program cycle in min.	24
Tested operating hours	20000
Control	
Control system	Profitronic M
Programmability	Freely programmable
Program controls	Residual moisture controlled
Max. delay start in h	Can be selected freely
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Standard/target group programs	
Basic programmes	•
Programmes for the hotel and catering industry	•
Programmes for retirement and care homes	•
Programmes for facility management	•
Programmes for dry cleaners	•
Programmes for fire brigades and rescue services	•
Programmes for studs, riding schools, and stables	•
Standard electrical connection	
Type of heating	Electric
Electrical connection	3 AC 208V 60HZ
Electric heater rating in kW	14.70

PT 8337 [PTM EL BSS ARP]

Vented dryer, electric heating

With individually programmable controls for the maximum in flexibility.



EAN: 4002515528457 / Material number: 09986710 / Old Material Number: 52833705USA

Total connected load in kW	15.40
Fuse rating in A	65
<b>Possible voltage variant 1</b>	
Electrical connection	3 AC 220-240V 60HZ
Heater rating in kW	16.50-19.60
Total connected load in kW	17.30-20.40
Fuse rating in A	65
<b>Dimensions and weight</b>	
External dimensions, net height in inches	55 1/8 (1400)
External dimensions, net width in inches	35 11/16 (906)
External dimensions, net depth in inches	40 3/4 (1035)
External dimensions, gross height in inches	60 1/8 (1526)
External dimensions, gross width in inches	42 15/16 (1090)
External dimensions, gross depth in inches	44 5/16 (1125)
Net weight in lbs. (kg)	365 (165.5)
Gross weight in lbs. (kg)	415 (188)
Maximum floor load in N/m <sup>2</sup>	1857
<b>Emission values</b>	
Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
Heat output to the room in MJ/h and BTUs /h	2.05
<b>Features</b>	
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecyclingPlus	•
Low temperature function	•
Communication slot	•
Emergency shut off	•
Machine-independent accessories	•
<b>Connection options</b>	
Payment system (optional)	•
Serial interface RS 232 (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management	•
Operating data acquisition	•
<b>Capacities</b>	
Respirator masks [number]	12
Standard and target group programs	2
Over jackets [number]	3
Synthetic duvets [number]	1
Synthetic pillows [number]	3
Feather duvets [number]	1
Feather pillows [number]	3
Cloths, 22 g/0.8 oz [number]	320
Cotton mops, 40 cm [number]	68
Cotton mops, 50 cm [number]	59
Microfibre mops, 40 cm [number]	108
Microfibre mops, 50 cm [number]	76
Summer horse blankets [number]	2-3
<b>Standards, test certificates, and symbols</b>	
CE	•

PT 8337 [PTM EL BSS ARP]

Vented dryer, electric heating

With individually programmable controls for the maximum in flexibility.