Míele

KWT 6322 UG Built-under wine storage unit with FlexiFrame and Push2open for greater versatility and top-quality design.



- Simultaneous wine storage in separate temperature zones
- Odorless refrigeration section thanks to Active AirClean filters
- Present the storage of your wine in the perfect light LED lighting
- Optimum wine protection through UV filters in tinted glass front
- Secure storage of wine bottles with pull-out racks

EAN: 4002515539699 / Material number: 10028620 / Old Material Number: 36632200USA

Appliance category	Old Material Number: 36632200USA	
Design Built-in	Appliance category	
Built-in Integrated	Wine storage unit	•
Built-in integrated Built-in built-under Door hinge side Convertible hinging Can be installed side-by-side Pesign Front color Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Number of shelves Aumber of FlexiFrame Wire Racks NoteBoard Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Fechnical data Niche width in inches (mm), min. Niche wight in inches (mm), min. Niche depth in in.(mm) Appliance height in in.(mm) Appliance height in in.(mm) Appliance height in in.(mm) Wine compartment in L Storage time in Case of fault in h Ocurrent consumption in milliampere (mA) Obsidian Black glass Le dight Le consider of shelves LED illumination LED illumination LED illumination LED illumination LED illumination For Stable late N ILED illumination LED illumination For Stable slass Stable slass yless Stable slass yles Ada National Black glass Nead obsider slass No Stable slass yles Ada National Black glass Fight Converted slass Fight Converted slass	Design	
Built-in built-under Door hinge side Convertible hinging Can be installed side-by-side Pesign Front color Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Number of shelves Number of shelves 1 Number of FlexiFrame Wire Racks 3 NoteBoard Vese conviolation and on the shelf of the shelf	Built-in	•
Door hinge side Convertible hinging Can be installed side-by-side Pesign Front color Obsidian Black glass Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Number of FlexiFrame Wire Racks NoteBoard Icectorial temperature display and control Independent temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic door alarm Fechnical data Niche width in inches (mm), max. Niche height in inches (mm), max. Niche height in inches (mm), max. Niche height in inches (mm), max. Appliance width in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance beight in in.(mm) Appliance beight in in.(mm) Appliance beight in in.(mm) Appliance beight in in.(mm) Appliance depth in in.(mm) Appliance beight in case of fault in h Current consumption in milliampere (mA)	Built-in integrated	•
Convertible hinging Can be installed side-by-side Design Front color Obsidian Black glass Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Number of shelves Number of shelves Number of FlexiFrame Wire Racks NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic door alarm Pethical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), max. Niche height in inches (mm), max. Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Vire compartment in L Storage time in case of fault in h Current consumption in milliampere (mA) Current consumption in milliampere (mA)	Built-in built-under	•
Can be installed side-by-side Pesign Front color Obsidian Black glass Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Number of shelves Number of FlexiFrame Wire Racks NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Fechnical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), max. Niche height in inches (mm), max. Appliance width in in.(mm) Appliance width in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) 22 3/8 (820) Appliance depth in in.(mm) Appliance compartment in L Total usable capacity in cu. ft. (I) O.75 I Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA)	Door hinge side	right
Pront color Obsidian Black glass Wine compartment lighting LED illumination User convenience DynaCool • SoftClose door closing damper • Total number of shelves 5 Number of shelves 4 Number of FlexiFrame Wire Racks 3 NoteBoard Yes Low-vibration storage • Control Electronic temperature display and control TouchControl Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) 5 Max. temperature setting range in °F (°C) 20 Safety Lock function • Acoustic door alarm • Acoustic temperature alarm • Optical door alarm Technical data Niche width in inches (mm), min. 23 5/8 (600) Niche height in inches (mm), max. 34 3/8 (870) Niche height in inches (mm), max. 32 3/8 (820) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance height in in.(mm) 22 3/8 (820) Appliance beight in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 32 3/8 (820) Appliance of fault in h 0 Current consumption in milliampere (mA)	Convertible hinging	•
Front color Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Number of shelves Number of FlexiFrame Wire Racks Number of FlexiFrame Wire Racks NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic door alarm Acoustic demperature alarm Optical door alarm Fechnical data Niche width in inches (mm), min. Niche width in inches (mm), min. Niche height in inches (mm), max. Appliance width in in.(mm) Appliance width in in.(mm) Appliance width in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Niche lasse (s) Verse Let Olive illumination LED illumination Inumination Inumination Elet illumination Inumination Inumination LED illumination Inumination Inumination Inumination Inumination Let Olive illumination Inumination Let Olive illumination Inumination Inumination Let Olive illumination Inumination Inumination Let Olive illumination Inumination Let Olive illumination Inumination Inumination Inumination Let Olive illumination Inumination Inum	Can be installed side-by-side	•
Wine compartment lighting User convenience DynaCool SoftClose door closing damper Total number of shelves Sumber of shelves Sumber of shelves Sumber of FlexiFrame Wire Racks Sumber of FlexiFrame Wire Racks Sumber of FlexiFrame Wire Racks Sumber of Shelves Sumber of FlexiFrame Wire Racks Sumber of FlexiFrame Wire Rack	Design	
User convenience DynaCool SoftClose door closing damper Total number of shelves SoftClose door closing damper Total number of shelves SoftClose door closing damper Total number of shelves SoftControl Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature zones Soft function Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	Front color	Obsidian Black glass
DynaCool SoftClose door closing damper Total number of shelves Snumber	Wine compartment lighting	LED illumination
SoftClose door closing damper Total number of shelves Number of shelves Number of FlexiFrame Wire Racks NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	User convenience	
Total number of shelves Number of shelves A Number of FlexiFrame Wire Racks NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	DynaCool	•
Number of shelves Number of FlexiFrame Wire Racks 3 NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature zones Acoustic door alarm Acoustic door alarm Petchnical data Niche width in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Wine Compartment in L Total usable capacity in cu. ft. (l) O.75 I Bordeaux bottles Ves Ves 1 TouchControl	SoftClose door closing damper	•
Number of FlexiFrame Wire Racks NoteBoard Ves Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature zones Min. temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	Total number of shelves	5
NoteBoard Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Wine compartment in L Total usable capacity in cu. ft. (I) O.75 I Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) Touch Corrent one vonction of Touch Control Touch Contro	Number of shelves	4
Low-vibration storage Control Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature zones Min. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic temperature alarm Optical doar alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), min. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Wine compartment in L Total usable capacity in cu. ft. (I) Outrent consumption in milliampere (mA) Current consumption in milliampere (mA)	Number of FlexiFrame Wire Racks	3
Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature zones Min. temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	NoteBoard	Yes
Electronic temperature display and control Independent temperature control of fridge and freezer compartments No. of temperature zones Min. temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), max. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) Wine compartment in L Total usable capacity in cu. ft. (I) Other control fridge and freezer No Non Non Non Appliance in mere setting range in °F (°C) Safety Lock function • Acoustic femperature alarm • Acoustic temperature alarm • Pechnical data Niche width in inches (mm), min. 23 5/8 (600) Niche width in inches (mm), max. 34 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance depth in in.(mm) 23 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) Nine compartment in L 3.32 (94) Total usable capacity in cu. ft. (I) 3.32 (94) O.75 I Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA)	Low-vibration storage	•
Independent temperature control of fridge and freezer compartments No. of temperature zones Min. temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), max. Niche height in inches (mm), max. Niche depth in in.(mm) Appliance width in in.(mm) Appliance height in in.(mm) Appliance depth in in.(mm)	Control	
compartments No. of temperature zones Min. temperature setting range in °F (°C) Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	Electronic temperature display and control	TouchControl
No. of temperature zones 2 Min. temperature setting range in °F (°C) 5 Max. temperature setting range in °F (°C) 20 Safety 2 Lock function • Acoustic door alarm • Acoustic temperature alarm • Optical door alarm • Technical data ** Niche width in inches (mm), min. 23 5/8 (600) Niche width in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), max. 34 3/8 (820) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) O.75 I Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Independent temperature control of fridge and freezer	No
Min. temperature setting range in °F (°C) 5 Max. temperature setting range in °F (°C) 20 Safety Lock function • Acoustic door alarm • Coptical door alarm • Technical data Niche width in inches (mm), min. 23 5/8 (600) Niche width in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 3/8 (820) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 32 3/8 (820)	compartments	
Max. temperature setting range in °F (°C) Safety Lock function Acoustic door alarm	No. of temperature zones	2
Safety Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm * Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. 23 5/8 (600) Niche height in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), max. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (I) 0.75 Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) 2000		5
Lock function Acoustic door alarm Acoustic temperature alarm Optical door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. Niche height in inches (mm), min. 23 5/8 (600) Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm)	Max. temperature setting range in °F (°C)	20
Acoustic door alarm Acoustic temperature alarm Optical door alarm Technical data Niche width in inches (mm), min. Niche width in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 32 3/8 (820) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) Appliance depth in in.(mm) Appliance dep	•	
Acoustic temperature alarm • Optical door alarm • Technical data	Lock function	•
Optical door alarm • Technical data 23 5/8 (600) Niche width in inches (mm), min. 23 5/8 (600) Niche width in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Acoustic door alarm	•
Technical data Niche width in inches (mm), min. 23 5/8 (600) Niche width in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Acoustic temperature alarm	•
Niche width in inches (mm), min. 23 5/8 (600) Niche width in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Optical door alarm	•
Niche width in inches (mm), max. 23 5/8 (600) Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 I Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000		
Niche height in inches (mm), min. 32 3/8 (820) Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 l Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000		23 5/8 (600)
Niche height in inches (mm), max. 34 3/8 (870) Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Niche width in inches (mm), max.	23 5/8 (600)
Niche depth in in.(mm) 22 7/8 (580) Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000		32 3/8 (820)
Appliance width in in.(mm) 23 5/8 (597) Appliance height in in.(mm) 32 3/8 (820) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Niche height in inches (mm), max.	34 3/8 (870)
Appliance height in in.(mm) Appliance depth in in.(mm) Appliance depth in in.(mm) 22 3/4 (577) Weight in lbs.(kg) 109 (49.0) Wine compartment in L 3.32 (94) Total usable capacity in cu. ft. (l) 0.75 Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) 2000	Niche depth in in.(mm)	22 7/8 (580)
Appliance depth in in.(mm) Weight in lbs.(kg) Wine compartment in L Total usable capacity in cu. ft. (I) 0.75 Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) 22 3/4 (577) 109 (49.0) 3.32 (94) 3.32 (94) 0 0 2000	Appliance width in in.(mm)	23 5/8 (597)
Weight in lbs.(kg) Wine compartment in L Total usable capacity in cu. ft. (I) 0.75 Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) 109 (49.0) 3.32 (94) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles 2000	Appliance height in in.(mm)	32 3/8 (820)
Wine compartment in L Total usable capacity in cu. ft. (I) 0.75 Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) 3.32 (94) 3.32 (94) 3.32 (94) 0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles 2000	Appliance depth in in.(mm)	22 3/4 (577)
Total usable capacity in cu. ft. (I) 0.75 Bordeaux bottle capacity (no. of bottles) Storage time in case of fault in h Current consumption in milliampere (mA) 3.32 (94) 34 bottles 0 2000	Weight in lbs.(kg)	109 (49.0)
0.75 Bordeaux bottle capacity (no. of bottles) 34 bottles Storage time in case of fault in h 0 Current consumption in milliampere (mA) 2000	Wine compartment in L	3.32 (94)
Storage time in case of fault in h Current consumption in milliampere (mA) 0 2000	Total usable capacity in cu. ft. (I)	3.32 (94)
Current consumption in milliampere (mA) 2000	0.75 Bordeaux bottle capacity (no. of bottles)	34 bottles
	Storage time in case of fault in h	0
Voltage in V 115	Current consumption in milliampere (mA)	2000
	Voltage in V	115



KWT 6322 UG Built-under wine storage unit

with FlexiFrame and Push2open for greater versatility and top-quality design.



EAN: 4002515539699 / Material number: 10028620 / Old Material Number: 36632200USA


Fuse rating in A	_10
Number of phases	1
Frequency in Hz	60
Wire length in ft (m)	7 (2.4)
Wire length in ft (m) Standard accessories	7 (2.4)


Míele


KWT 6322 UG

Built-under wine storage unit

with FlexiFrame and Push2open for greater versatility and top-quality design.








KWT6312UGS, KWT6322UG, KWT6322UG-1, KWT6322UG edt/cs (installation drawings)

KWT6312UGS, KWT6322UG, KWT6322UG-1, KSK6300, Side by Side (installation drawing)

KWT6322UG, KWT6322UG-1, KWT6322UG edt/cs, Interior dimensions (Installation drawings)



KWT6312UGS, KWT6322UG, KWT6322UG-1, KWT6322UG edt/cs (installation drawings)