

HM16-80 D [EL] Rotary iron, electric with steam function for optimum results and maximum convenience.



- Performance 13.0 kg/h^{*}, roller diameter 6 5/16 (160) in (mm), working width 32 11/16 (830) in (mm)
- Iron comfortably while seated
- Work at your own pace thanks to variable roller speed
- Durable roller padding aramid needle felt cloth
- Easy to store fold-away function

EAN: 4002515636459 / Material number: 10238590 / Old Material Number: 53168002USA

Construction type and design Design	Infeed and outfeed of
	il iloca alla outloca oi
	laundry at the front
Can be set up against a wall	•
Linie	Professional
Outer casing	Lotus white
Drum diameter in in.(mm)	6 5/16 (160)
Working width in in.(mm)	32 11/16 (830)
Heater plate material	Aluminium
Padding	Polyester needle-felt cloth
Ironer cover	ARAMID needle-felt cloth
Application	
Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for residential homes and apartments	•
Suitable for commercial laundries	•
Suitable for off-shore use	•
Suitable for Marine use	•
Suitable for camp sites	•
Suitable for domestic use	•
Performance data	
Max. ironing performance at 20 % residual moisture in kg/h	13.0
Tested operating hours	2500
Control	
Control system	Selector dial
Touch display (optional)	Drehwahlschalter
Minimum ironer speed, can be set in ft/min	2.0
Maximum ironer speed, can be set in ft/min	4.5
Adjustable temperature	In temperature stages
Standard electrical connection	
Type of heating	Electric
Electrical connection	2AC 208-240V 50-60HZ
Electric heater rating in kW	2.80-3.70
Boiler heater rating in kW	0.85
Total connected load in kW	2.90-3.80
Fuse rating in A	20
NEMA plug: 6-20	•
Dimensions and weight	
External dimensions, height in mm	37 13/16 (959)
External dimensions, width in mm	38 13/16 (985)
External dimensions, depth in mm	15 (380)
External dimensions, gross height in inches	22 1/2 (570)
External dimensions, gross width in inches	44 1/8 (1120)
External dimensions, gross depth in inches	17 3/4 (450)
Net weight in kg	86 (39)
Gross weight in lbs.	100 (45)
CHOOS WORTH IN IDS.	382
Maximum floor load in N/m ²	002
•	
Maximum floor load in N/m²	•

With 20% residual moisture – performance data according to DIN 11 902: The achievable laundry throughput depends on overall conditions such as, for example, the type of laundry and the experience of the operator.



HM16-80 D [EL] Rotary iron, electric with steam function for optimum results and maximum convenience.



EAN: 4002515636459 / Material number: 10238590 / Old Material Number: 53168002USA

Fold-away function	•
Finger guard	•
Foot switch	•
Airing bar	•
Feed-in board	•
Laundry return feed	•
Appliance-independent accessories	•
Standards, test certificates, and symbols	
CSA-C-US	•
Complies with Machinery Directive 2006/42/EC	

Complies with Machinery Directive 2006/42/EC