

## PDR 908 HP [EL]

Professional heat-pump dryer, Little Giants

with very low energy consumption and short program runtimes. Load size 18 (8.0) lb (kg).



- Drum volume 4.59 (130.00) ft<sup>3</sup> (l), load size 18 (8.0) lb (kg)
- Tested for intensive use – unique Miele quality
- Top convenience with full-touch color display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof connectivity via Wi-Fi

EAN: 4002516195917 / Material number: 11204480 /  
Old Material Number: 52908159NAM

### Construction type and design

Design	Front-loader, stackable
Linie	Performance Plus
Front	Lotus White
Control panel color	Stainless Steel
Load in lbs.(kg)	18 (8.0)
Drum volume in ft <sup>3</sup> (l)	4.59 (130.00)
Drying system	Heat pump
Door opening [Ø] in in.(mm)	14 5/8 (370)
Door opening angle in degrees	167
Door hinging	left
Stainless steel honeycomb drum	Yes

### Application

Suitable for the hotel and catering industry	•
Suitable for retirement and care homes	•
Suitable for facility management	•
Suitable for laundrettes	•
Suitable for dry cleaners	•
Suitable for commercial laundries	•
Suitable for small businesses	•
Suitable for universities, nurseries, and schools	•
Suitable for hospitals	•
Suitable for camp sites	•
Suitable for sports clubs	•
Suitable for beauty salons, spas and fit ness centers	•
Suitable for doctors' and dentists' practices	•
Suitable for the petrochemical industry	•
Suitable for the food-processing industry	•
Suitable for amusement parks and holiday complexes	•
Suitable for public/community care facilities	•

### Performance data

Maximum evaporation capacity in l/hour and gal. qts./hour	3 (3) gal (US)/min (l)
Specific energy consumption in kWh/kg an d kWh/p	0.20
Specific energy consumption for cottons/Normal drying, residual moisture 48% in kWh/kg	0.20
Specific energy consumption for mixed fabric/Normal drying, residual moisture 40% in kWh/kg	0.17
Program cycle in min.	88
Program cycle time for cottons/Normal drying, residual moisture 48% in min.	88
Program cycle time for cottons/Normal drying, residual moisture 40% in min.	76

### Control

Control system	M Touch Flex
Programmability	programmable
Program controls	Residual moisture controlled
Max. delay start in h	24
Countdown indicator	•

## PDR 908 HP [EL]

Professional heat-pump dryer, Little Giants

with very low energy consumption and short program runtimes. Load size 18 (8.0) lb (kg).



EAN: 4002516195917 / Material number: 11204480 /

Old Material Number: 52908159NAM

Program sequence indicator	•
----------------------------	---

Language can be selected easily at any time	•
---	---

### Standard electrical connection

Type of heating	Heat pump
-----------------	-----------

Electrical connection	2 AC 208-240V 60HZ
-----------------------	--------------------

Total connected load in kW	1.20
----------------------------	------

Fuse rating in A	30
------------------	----

NEMA plug: Twist Lock L6-30	•
-----------------------------	---

### Dimensions and weight of dryer

External dimensions, net height in inches	33 1/2 (850)
---	--------------

External dimensions, net width in inches	23 1/2 (596)
--	--------------

External dimensions, net depth in inches	30 5/8 (777)
--	--------------

External dimensions, gross height in inches	37 1/16 (940)
---	---------------

External dimensions, gross width in inches	26 (660)
--	----------

External dimensions, gross depth in inches	32 5/16 (820)
--	---------------

Net weight in lbs. (kg)	157 (71.0)
-------------------------	------------

Gross weight in lbs. (kg)	170 (77)
---------------------------	----------

Maximum floor load in N	920
-------------------------	-----

### Emission values

Emissions – sound pressure at workplace	<70 dB(A) re 20 µPa
---	---------------------

Heat dissipation into the room in MJ/h	3.60
--	------

### Features

Intelligent drum reversal	•
---------------------------	---

Axial airflow	•
---------------	---

Fluff filter in the door	•
--------------------------	---

Low-maintenance heat exchanger filter system	•
--	---

PerfectDry	•
------------	---

SoftLift drum ribs	•
--------------------	---

Gentle tumble function	•
------------------------	---

Condensed water drainage	•
--------------------------	---

Communication slot	•
--------------------	---

Drying basket (optional)	•
--------------------------	---

Drum lighting	•
---------------	---

Machine-independent accessories	•
---------------------------------	---

### Efficiency and sustainability

Recycling rate in %	95
---------------------	----

Contains fluorinated greenhouse gases	•
---------------------------------------	---

Hermetically sealed system	•
----------------------------	---

Coolant	R134a
---------	-------

Refrigerant quantity in kg	0.59
----------------------------	------

Refrigerant global warming potential in kg CO <sub>2</sub> e	1430
--	------

Appliance global warming potential in kg CO <sub>2</sub> e	844.00
--	--------

### Connection options

Payment system (optional)	•
---------------------------	---

Optical interface for service access	•
--------------------------------------	---

### Standards, test certificates, and symbols

WEEE	•
------	---

c ETL US	•
----------	---