

Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



- Drum volume 3.88 (110) ft³ (l), maximum load size 27 (12.0) lb (kg)
- Top cleaning & consumption values innovative Miele technology
- Ideal operation thanks to touch color display M Touch Pro Plus
- Simple and safe operation thanks to automatic door lock
- Connected for the future using LAN and WiFi

Construction type and design	
Design	Front loader
Product line	Performance Plus
Front	Stainless Steel
Control panel color	Stainless Steel
Maximum load with a load ratio of 1:9 in lbs	27 (12.0)
Load ratio	1:9
Load in lbs	27 (12.0)
Drum volume in cubic feet (I)	3.88 (110)
Door opening [Ø] in in.(mm)	16 3/8 (415)
Door opening angle in degrees	180
Door hinging	right
Automatic door lock	•
Innovative suds container	•
Maintenance-free motor with frequency converter	•
Patented honeycomb drum 2.0	•
Application	
Suitable for off-shore use	•
Suitable for Marine use	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Specific water consumption for cold water connection in gal/lb	6.20
Specific energy consumption for cold water connection in kWh/lb	0.14
Specific water consumption for hot water connection in I/kg	5.90
Specific energy consumption for hot water connection in kWh/lb	0.06
Water consumption for cold water connection in I	74.4
Water consumption for cold water connection in Mops standard program in gal	142.2
Energy consumption for cold water connection in kWh	1.68
Energy consumption for cold water connection in Mops standard program in kWh	2.50
Program duration in minutes with cold water connection	49
Water consumption for hot water connection in I	70.8
Water consumption for hot water connection in Mops standard program in gal	139.9
Energy consumption for hot water connection in kW	0.72
Energy consumption for hot water connection in Mops standard program in kWh	1.00
Program duration in minutes with hot water connection	42
Water consumption in ECO program for cold water connection in I	69.6
Energy consumption in ECO program for cold water connection in kWh	1.20
Program duration in minutes for ECO program with cold water connection	34
Water consumption in ECO program for hot water connection in I	68.4



Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



Energy consumption in ECO program for hot water	0.36
connection in kWh	
Program duration in minutes for ECO program with hot water connection	31
Program runtime in minutes for Mops standard program with cold water connection	54
Program runtime in minutes for Mops standard program with hot water connection	47
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	44
Residual moisture when processing cleaning cloths in %	25
Spin speed in rpm	1150
g factor	458
Tested operating hours	30000
Control	
Control system	M Touch Pro Plus
Programmability	Freely programmable
Max. delay start in h	Can be selected freely
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Option to enter weight prior to start of program	
Standard/target group programs	
Basic programmes	•
Dispensing	
1 0	2 comportmente
Detergent dispenser drawer	3 compartments
Maximum number of connections for liquid disconcer	10
Maximum number of connections for liquid dispenser	12
pumps [number]	
pumps [number] Empty sensor	
pumps [number] Empty sensor Standard electrical connection	•
pumps [number] Empty sensor Standard electrical connection Type of heating	• Electric
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection	Electric 3 AC 480V 60HZ
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW	• Electric 3 AC 480V 60HZ 9.80
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW	Electric 3 AC 480V 60HZ 9.80 10.40
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	• Electric 3 AC 480V 60HZ 9.80
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1	Electric 3 AC 480V 60HZ 9.80 10.40 16
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connection Total connection Total connection	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connection Heater rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water rating in A Water connection/drainage	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connected load in kW Fuse rating in A Water connection/drainage Cold water [number]	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number]	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hard water (optional) [number]	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hard water (optional) [number]	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 53 3/16 (1350)
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Water connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hord water (optional) [number] Dump valve Dimensions and weight External dimensions, net width in inches	Electric 3 AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 53 3/16 (1350) 31 1/2 (799)
pumps [number] Empty sensor Standard electrical connection Type of heating Electrical connection Heater rating in kW Total connected load in kW Fuse rating in A Possible voltage variant 1 Electrical connection Heater rating in KW Total connected load in kW Fuse rating in A Water connected load in kW Fuse rating in A Water connection/drainage Cold water [number] Hot water [number] Hard water (optional) [number] Dump valve Dimensions and weight External dimensions, net height in inches External dimensions, net width in inches External dimensions, net depth in inches	Electric AC 480V 60HZ 9.80 10.40 16 3 AC 440V 60HZ 8.20 8.80 16 3 x 1/2" hose w/ 3/4" union 1x 1/2" hose w/ 3/4" th. union 2 x 1/2" w/ 3/4" union DN 70 53 3/16 (1350) 31 1/2 (799) 36 7/16 (924)



Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.

External dimensions, gross depth in inches	44 1/2 (1130)
Net weight in lbs.(kg)	638 (289.0)
Gross weight in lbs.	680 (308)
Maximum floor load in N/m ²	4502
Emission values	
Emissions – sound pressure at workplace	65 dB(A) re 20 µPa
Heat dissipation into the room in BTU/h	6.48
Features	
Patented preliminary drainage	•
Patented cleaning cloth program	•
3-dimensional imbalance monitoring	•
Disinfection rinse	•
Efficient scoop-and-ladle ribs	•
EcoSpeed	•
Spring-in-spring system	•
Temperature monitoring	•
Special heater element	•
Automatic load control Plus	•
Volumetric flow meter (optional)	•
Weighing base (optional)	•
Add laundry	•
Program selection via color frame	•
Emergency shut off	•
Appliance-independent accessories	•
Efficiency and sustainability	
Recycling rate in %	91
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak-load negotiation/energy management (optional)	•
Water recovery (optional)	•
LAN	•
WiFi	•
Connector Box	
Capacities	
· · · · · · · · · · · · · · · · · · ·	10
Respirator masks [number] Helmets [number]	3
	·
Overalls [number]	<u>2</u> 3
Over jackets [number]	
Chemical protection overalls [number]	
Synthetic duvets [number]	
Synthetic pillows [number]	2
Feather duvets [number]	
Feather pillows [number]	2
Cloths, 22 g/0.8 oz[number]	289
Cotton mops, 40 cm/15.7 in[number]	64
Cotton mops, 50 cm/19.7 in[number]	56
Microfibre mops, 40 cm/15.7 in [number]]	100
Microfibre mops, 50 cm/19.7 in [number]	72
Mops, office, 100 g [quantity]	120
Mops, stairway, 150 g [quantity]	80



Professional washing machine, electrically heated, with drain valve and detergent drawer, M Touch Pro Plus freely programmable, for marine use.



Summer horse blankets [number]	2
Standards, test certificates, and symbols	
CE	•
VDE-EMC	•
VDE	•
Splash protection IPX4	•
UKCA	•
WEEE	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•