## Míele

PDR 928 [EL SOM] Vented dryer, electric heating with programmable M Touch Pro controls, for marine applications.



- Drum volume 17.66 (500.00) ft<sup>3</sup> (l), load size45 (20.0) lb (kg) – 62 (28.0) lb (kg)
- Unique, gentle fabric care patented honeycomb drum
- Maximum energy efficiency thanks to Air Recycling Flex
- Precision drying of all fabrics PerfectDry
- Connected for the future using LAN and WiFi

EAN: 4002516410928 / Material number: 11722730 / Old Material Number: 52928008SOM

O controlling to a control of the	
Construction type and design	
Design	Front loader
Linie	Performance Plus
Front	Stainless Steel
Load size with a load ratio of 1:25	45 (20.0)
Load size with a load ratio of 1:18	62 (28.0)
Drum volume in ft <sup>3</sup> (l)	17.66 (500.00)
Drying system	Exhaust air
Door opening [Ø] in in.(mm)	20 1/2 (520)
Door opening angle in degrees	180
Door hinging	left
Convertible hinging	•
Stainless steel honeycomb drum	Yes
Application	
Suitable for off-shore use	•
Suitable for Marine use	•
Performance data	
Specific energy consumption in kWh/kg an d kWh/p	0.51
Program cycle in min.	24
Service life in drying cycles	40000
Control	
Control system	M Touch Pro
Programmability	programmable
Program controls	Residual moisture
	controlled
Max. delay start in h	24
Countdown indicator	•
Program sequence indicator	•
Choice of display language	•
Standard electrical connection	
Type of heating	Electric
Electrical connection	3 AC 480V 50/60HZ
Electric heater rating in kW	31.80
T	
Total connected load in kW	33.00
Fuse rating in A	33.00 50
Fuse rating in A	
Fuse rating in A  Possible voltage variant 1	50
Fuse rating in A  Possible voltage variant 1  Electrical connection	50 3 AC 440V 50/60HZ
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW	50 3 AC 440V 50/60HZ 27.00
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW	3 AC 440V 50/60HZ 27.00 28.20
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A	3 AC 440V 50/60HZ 27.00 28.20
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer	3 AC 440V 50/60HZ 27.00 28.20 50
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640)
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches  External dimensions, net width in inches	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640) 47 1/2 (1206)
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches  External dimensions, net width in inches  External dimensions, net depth in inches	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640) 47 1/2 (1206) 40 1/8 (1019)
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches  External dimensions, net depth in inches  External dimensions, net depth in inches  External dimensions, gross height in inches	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640) 47 1/2 (1206) 40 1/8 (1019) 69 9/16 (1766)
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches  External dimensions, net depth in inches  External dimensions, gross height in inches  External dimensions, gross height in inches  External dimensions, gross width in inches	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640) 47 1/2 (1206) 40 1/8 (1019) 69 9/16 (1766) 54 3/4 (1390)
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches  External dimensions, net depth in inches  External dimensions, gross height in inches  External dimensions, gross width in inches  External dimensions, gross width in inches  External dimensions, gross width in inches  External dimensions, gross depth in inches	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640) 47 1/2 (1206) 40 1/8 (1019) 69 9/16 (1766) 54 3/4 (1390) 43 5/8 (1108)
Fuse rating in A  Possible voltage variant 1  Electrical connection  Heater rating in kW  Total connected load in kW  Fuse rating in A  Dimensions and weight of dryer  External dimensions, net height in inches  External dimensions, net depth in inches  External dimensions, gross height in inches  External dimensions, gross width in inches  External dimensions, gross width in inches  External dimensions, gross width in inches  External dimensions, gross depth in inches  External dimensions, gross depth in inches  External dimensions, gross depth in inches  Net weight in lbs. (kg)	50 3 AC 440V 50/60HZ 27.00 28.20 50 64 5/8 (1640) 47 1/2 (1206) 40 1/8 (1019) 69 9/16 (1766) 54 3/4 (1390) 43 5/8 (1108) 537 (243.3)



PDR 928 [EL SOM] Vented dryer, electric heating with programmable M Touch Pro controls, for marine applications.



EAN: 4002516410928 / Material number: 11722730 / Old Material Number: 52928008SOM

Emission values	
Emissions – sound pressure at workplace	58 dB(A) re 20 μPa
Heat output to the room in Mi/h and BTUs /h	3.30
Features	0.00
Intelligent drum reversal	•
Axial airflow	•
Large-surface fluff filter	•
PerfectDry	•
SoftLift drum ribs	•
AirRecycling Flex	•
Communication slot	•
Emergency shut off	•
Machine-independent accessories	•
Connection options	
Payment system (optional)	•
Optical interface for service access	•
Peak load cut-out/energy management (optional)	•
WiFi tumble dryer	•
Connector Box	•
LAN module (optional)	•
Capacities	
Respirator masks [number]	12
Standard and target group programs	3
Over jackets [number]	5
Synthetic duvets [number]	2
Synthetic pillows [number]	3
Feather duvets [number]	2
Feather pillows [number]	5
Cloths, 22 g/0.8 oz [number]	545
Cotton mops, 40 cm [number]	105
Cotton mops, 50 cm [number]	91
Microfibre mops, 40 cm [number]	167
Microfibre mops, 50 cm [number]	118
Summer horse blankets [number]	3
Standards, test certificates, and symbols	
CE	•
VDE	•
VDE-EMC	•
Splash-proof safety rating IPX4	•
WEEE	•
UKCA	•
EAC	•
Complies with Machinery Directive 2006/42/EC	•