



- Large touch display with proximity sensor – M Touch + MotionReact
- Individual coffee enjoyment with 3 bean containers CoffeeSelect
- Perfect care fully automatic with AutoDescale and AutoClean
- Perfectly positioned: thanks to the patented CupSensor
- 2 coffees at once at the touch of a button OneTouch for Two

EAN: 4002516419464 / Material number: 11733840 / Old Material Number: 29784540USA

Construction type and design	
Built-in bean-to-cup coffee machine VitroLine	•
	•
ArtLine Color	Stainless Steel/Clean Touch
	Steel
Convenience features	
AromaticSystemFresh	•
CoffeeSelect	•
OneTouch preparation	•
One Touch and OneTouch for Two	•
DoubleShot	•
Programmable User profile	10
Flavor preserving conical grinding unit	•
Grinding grade selectable	•
Ground quantity programmable	•
Water quantity programmable	•
Water temperature programmable	•
Amount of milk can be programmed	•
Amount of milk froth can be programmed	•
Pre-brewing programmable	•
TeaTimer	•
User convenience	
Networking with Miele@home	•
Control panel	M Touch
MotionReact: light comes on when movement is detected	•
MotionReact: display comes on when movement is detected	•
CupSensor	•
Height adjustment of infinitely adjustable central spout min in .(cm)	1 5/8 (4.0)
Height adjustment of infinitely adjustable central spout max in in.(cm)	6 1/2 (16.5)
PerformanceMode	•
EasyClick milk container	•
DirectWater	•
ComfortDoor	•
Hidden door handle	•
BrilliantLight	•
Brew unit lighting	•
Expert mode	•
MultiLingua	•
MyMiele	•
Help function	•
No. of bean types	3
No. of bean containers	3
Bean container capacity, each in oz (g)	300
Capacity of bean container B in g	150
Capacity of bean container C in g	150
Bean container capacity, total in oz (g)	21.16 (600)
Removable bean container	•





EAN: 4002516419464 / Material number: 11733840 / Old Material Number: 29784540USA

Capacity of water container in fl oz (I)	91.3 (2.7)
Milk container capacity in I	0.7
Capacity of waste container in servings	17
Drip tray capacity in fl oz (l)	54.1 (1.6)
Easily accessible containers	•
Time-of-day display	•
Time synchronization	•
Date display	•
Programmable switch-on time	<del>`</del>
Programmable switch-off time	•
	<del>`</del>
Programmable stand-by time	<b>•</b>
Individual settings	
Drink specialties	00.000
Adjustable beverage portion size in ml	20-300
Ristretto, single	
Ristretto, double	•
Espresso, single	•
Espresso, double	<u>•</u>
Coffee, single	•
Coffee, double	•
Long coffee, single	•
Long coffee, double	•
Cappuccino, single	•
Cappuccino, double	•
Latte macchiato, single	•
Latte macchiato, double	•
Hot milk, single	•
Latte macchiato, double	•
Milk froth, single	•
Milk froth, double	•
Espresso macchiato, single	•
Espresso macchiato, double	•
Cappuccino italiano, single	•
Cappuccino italiano, double	•
Flat white, single	•
Flat white, double	•
Café au lait, single	•
Café au lait, double	•
Caffè latte, single	•
Caffè latte, double	•
Caffè americano, single	•
Caffè Americano, double	•
Long black, single	•
Long black, double	•
Allwater	•
Warm water, double	•
Hot water, single	•
Hot water, double	•
	•
Black tea, single	
Black tea, double Herbal tea, single	•
	•
Herbal tea, double	•








## CVA 7845

Built-in coffee machine with DirectWater

Perfectly combinable design with CoffeeSelect + AutoDescale for highest demands.








CVA7445, CVA7845, installation drawing, side view, Flush insert


 $7/8^{\ast}$  –  $22^{\star}$  mm – Glass, 15/16^{\ast} –  $23.3^{\star\star}$  mm – Stainless steel

CVA7440, CVA7445, CVA7840, CVA7845, installation

drawing, view from above, 60 cm, Flush inset


CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Flush inset





-22 11/16" (-577 mm)


CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Flush inset



CVA7440, CVA7745, CVA7840, CVA7845, installation drawing, built in,  $60\ {\rm cm},$  Flush inset

 $7/8^{\rm "}$  –  $22^{\star}$  mm – Glass, 15/16^{\rm "} – 23.3^{\star\star} mm – Stainless steel


CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Flush inset



 $\ensuremath{\mathsf{CVA7445}}$  ,  $\ensuremath{\mathsf{CVA7845}}$  , installation drawing, 60 cm, Flush insert


A – Cut-out (1 1/2" x 20" / 38 mm x 508 mm) in the bottom of the cabinet for power cord and ventilation, – Electrical and water supplies are recommended to be placed in adjacent cabinetry., Additional cabinet depth is required when placing the electrical and water supplies behind the appliance., E = Electric connection, W = Water connection


CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Flush inset




CVA7445, CVA7845, side view, 60 cm, Proud 7/8" - 22\* mm - Glass, 15/16" - 23.3\*\* mm - Stainless steel












CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Proud




CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Proud



CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Proud



CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Proud



CVA7445, CVA7845, installation drawing, installation, 60 cm, Proud

A – Cut-out (1 1/2" x 20" / 38 mm x 508 mm) in the bottom of the cabinet for power cord and ventilation, – Electrical and water supplies are recommended to be placed in adjacent cabinetry., Additional cabinet depth is required when placing the electrical and water supplies behind the appliance., E = Electric connection, W = Water connection

CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, view from above, 60 cm, Proud

CVA7440, CVA7445, CVA7840, CVA7845, installation drawing, built in, Einbau, 60 cm, Proud