

PRI 210 [EL SOM STW AB]

Rotary iron, electric

with the latest controls and flexible working height for marine applications.



- Performance 30.0 kg/h*, roller diameter 8 5/16 (210) in (mm), working width 39 3/8 (1000) in (mm)
- Ideal ergonomics heightadjustable and optional base
- State-of-the-art controls Touch display
- Selection of the most important settings favorite programs
- Perfect rotary ironing performance flexibly positioned heater plate

EAN: 4002516422419 / Material number: 11741310 / Old Material Number: 53210009SOM

0	
Construction type and design	lafa al a al a 15 de 5
Design	Infeed and outfeed of laundry at the front
Can be set up against a wall	aunury at the front
Linie	Professional
Outer casing	Iron Grey
Drum diameter in in.(mm)	8 5/16 (210)
Working width in in.(mm)	39 3/8 (1000)
Heater plate material	Aluminium
Padding	Supple steel wool
Ironer cover	ARAMID needle-felt cloth
Application	A LAMB RECGIE TEIL CIOTT
Suitable for off-shore use	•
Suitable for Marine use	
Performance data	
Max. ironing performance at 15 % residual moisture in kg/h	30.0
Tested operating hours	20000
Control	20000
Control system	Touch display
Touch display (optional)	Touch-Display PRI
Program setting	Setting of defined program
Togram setting	parameters
Minimum ironer speed, can be set in ft/min	1.5
Maximum ironer speed, can be set in ft/min	4.0
Adjustable temperature	Infinitely variable
Standard electrical connection	This itery verices to
Type of heating	Electric
Electrical connection	3N AC 400V 50-60HZ
Electric heater rating in kW	4.50
Total connected load in kW	5.00
Fuse rating in A	16
Dimensions and weight	
External dimensions, height in mm	40 11/16 (1032)
External dimensions, width in mm	62 3/16 (1579)
External dimensions, depth in mm	18 3/4 (476)
External dimensions, gross height in inches	54 1/8 (1374)
External dimensions, gross width in inches	69 7/16 (1763)
External dimensions, gross depth in inches	26 (660)
Net weight in kg	269 (122)
Gross weight in lbs.	300 (136)
Maximum floor load in N/m ²	1220
Emission values	
Emissions – sound pressure at workplace	<70 dB(A) re 20 μPa
Heat output to the room in Mj/h and BTUs /h	4.50
Features	
Finger guard	•
FlexControl footswitch	•
Airing bar	•
Feed-in board	•
Laundry pick-off bands	•

With 15% residual moisture – performance data according to DIN 11 902: The achievable laundry throughput depends on overall conditions such as, for example, the type of laundry and the experience of the operator.



PRI 210 [EL SOM STW AB]

Rotary iron, electric

with the latest controls and flexible working height for marine applications.



EAN: 4002516422419 / Material number: 11741310 / Old Material Number: 53210009SOM

Laundry crates (optional)	•
Laundry return feed	•
Favorites program	•
Incorrect feed recognition	•
Air suspension	•
Pause function	•
High contact pressure	•
Heater plate cleaning and waxing indicator	•
Plinth (optional)	•
Option of ironing when seated	•
APRI 319 care set for the heater plate included in the scope of delivery	•
Appliance-independent accessories	•
Connection options	
Connection options Payment system (optional)	•
	•
Payment system (optional)	
Payment system (optional) Peak load cut-out/energy management	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols VDE	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols VDE CE	· · · · · · · · · · · · · · · · · · ·
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols VDE CE EAC	•
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols VDE CE EAC WEEE	
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols VDE CE EAC WEEE VDE-EMC	
Payment system (optional) Peak load cut-out/energy management Standards, test certificates, and symbols VDE CE EAC WEEE VDE-EMC RCM	